

This is a repository copy of Effect of a heat treatment on the precipitation behavior and tensile properties of alloy 690 steam generator tubes.

White Rose Research Online URL for this paper: http://eprints.whiterose.ac.uk/102510/

Version: Supplemental Material

Article:

Lee, T-H., Suh, H-Y., Han, S-K. et al. (2 more authors) (2016) Effect of a heat treatment on the precipitation behavior and tensile properties of alloy 690 steam generator tubes. Journal of Nuclear Materials, 479. pp. 85-92. ISSN 0022-3115

https://doi.org/10.1016/j.jnucmat.2016.06.038

Reuse

This article is distributed under the terms of the Creative Commons Attribution-NonCommercial-NoDerivs (CC BY-NC-ND) licence. This licence only allows you to download this work and share it with others as long as you credit the authors, but you can't change the article in any way or use it commercially. More information and the full terms of the licence here: https://creativecommons.org/licenses/

Takedown

If you consider content in White Rose Research Online to be in breach of UK law, please notify us by emailing eprints@whiterose.ac.uk including the URL of the record and the reason for the withdrawal request.



- \bullet The intergranular carbide was identified as chromium rich (Cr-rich) $M_{23}C_6$ carbide.
- The $M_{23}C_6$ carbides are closely related to the grain boundary characteristics.
- The mechanical properties are associated with the precipitation of Cr carbides.