UNIVERSITY OF LEEDS

This is a repository copy of Numerical investigation on particle resuspension in turbulent duct flow via DNS-DEM: Effect of collisions.

White Rose Research Online URL for this paper: http://eprints.whiterose.ac.uk/104504/

Version: Accepted Version

Proceedings Paper:

Zhang, H, Trias, FX, Gorobets, A et al. (3 more authors) (2014) Numerical investigation on particle resuspension in turbulent duct flow via DNS-DEM: Effect of collisions. In: Onate, E, Oliver, J and Huerta, A, (eds.) Proceedings. 11th World Congress on Computational Mechanics (WCCM XI), 5th European Conference on Computational Mechanics (ECCM V), and 6th European Conference on Computational Fluid Dynamics (ECFD VI), 20-25 Jul 2016, Barcelona, Spain. International Centre for Numerical Methods in Engineering (CIMNE), pp. 2718-2725. ISBN 978-84-942844-7-2

Reuse

Unless indicated otherwise, fulltext items are protected by copyright with all rights reserved. The copyright exception in section 29 of the Copyright, Designs and Patents Act 1988 allows the making of a single copy solely for the purpose of non-commercial research or private study within the limits of fair dealing. The publisher or other rights-holder may allow further reproduction and re-use of this version - refer to the White Rose Research Online record for this item. Where records identify the publisher as the copyright holder, users can verify any specific terms of use on the publisher's website.

Takedown

If you consider content in White Rose Research Online to be in breach of UK law, please notify us by emailing eprints@whiterose.ac.uk including the URL of the record and the reason for the withdrawal request.



eprints@whiterose.ac.uk https://eprints.whiterose.ac.uk/

NUMERICAL INVESTIGATION ON PARTICLE RESUSPENSION IN TURBULENT DUCT FLOW VIA DNS-DEM: EFFECT OF COLLISIONS

Hao Zhang^{†,‡}, F. Xavier Trias[†], Andrey Gorobets^{†,§}, Dongmin Yang^{\$}, Assensi Oliva[†], Yuanqiang Tan[‡]

[†]Heat and Mass Transfer Technological Center, Technical University of Catalonia ETSEIAT, C/Colom 11, 08222 Terrassa, Spain

[‡]School of Mechanical Engineering, Xiangtan University, Hunan 411105, China [§] Keldysh Institute of Applied Mathematics of RAS, 4A, Miusskaya Sq., Moscow, 125047, Russia

^{\$} School of Civil Engineering, University of Leeds, Leeds LS2 9JT, UK

Key words: Particle resuspension, Turbulent duct flow, DNS-DEM, Collisions

We focus on the numerical prediction of particle-laden turbulent flows in a straight duct at $Re_{\tau} = 300$ that is defined as $Re_{\tau} = Hu_{\tau}/\nu$ based on the duct hydraulic diameter H = 0.02m, the mean friction velocity u_{τ} and the kinematic viscosity ν . The streamwise length of the duct is $4\pi H$ and the fluid is water. The kinematics and trajectory of the discrete particles as well as the particle-particle interaction are described by the discrete element method (DEM) [1] while the hydrodynamic model of the fluid phase is based on the direct numerical simulation (DNS) [2, 3]. Unlike the particle transportation process in pipes with circular cross section [4, 5], the motion of the particles in square duct can be affected by the secondary vortexes which are known as the secondary flow of Prandtl's second kind. Therefore, the particles show more stochastic motions than those in the homogeneous and iostropic turbulent flows. Moreover, inter-particle collisions play an important role on the particle behavior. In this study, the effect of collisions on the particle resuspension process is investigated with special emphasis.

Initially, 20000 particles of 50 μm are randomly generated in the fully developed turbulent flow field, the particles have the same velocities as the fluid flow. The periodic boundary condition is used in the streamwise direction. The collisions between the particles and between the particles and the four bounded walls are treated via a soft-sphere DEM [6]. Numerical simulations are carried out with and without collisions, respectively. Fig. 1 displays the snapshot of the particle and velocity distributions in the duct with collisions. For the sake of presenting better visual, only 20% of the particles are shown without changing the main trend of the distribution characteristic. It is shown that the instantaneous particle distribution is obviously influenced by the secondary flows, the velocities of



Figure 1: 2D snapshots of particle distribution with velocity vectors at t = 12s. Red point for the particle, black arrow for the velocity.

the particles emerge almost random distributions that related to the local fluid structure. However, the intimate motions are decoupled by the gravitational force that leads to a progressive segregation of the particles within the upper half of the duct and accumulation within the lower half. Due to the secondary velocities towards the corners, two arms are lifted within the upper half of the duct that also prevent the particle deposition.

The lower half of the duct is separated into 50 squares, namely five partitions in the z-direction and ten partitions in the y-direction, each region in the z-direction containing ten squares is marked by A, B, C, D, E. The resuspension rate is defined as the ratio of the number of resuspended particles to the total number of particles within each square. Further results will be presented in the final paper and in the conference.

REFERENCES

- Cundall, P. In: Muller led, ed. Proc Symp Int Soc Rock Mechanics, Rotterdam: Balkama A A 1, 8–12 (1971).
- [2] Trias, F. X., Soria, M., Oliva, A., and Perez-Segarra, C. D. Journal of Fluid Mechanics 586, 259–293 9 (2007).
- [3] Zhang, H., Trias, F., Tan, Y., Y.Sheng, and Oliva, A. 23rd International Conference on Parallel Computational Fluid Dynamics, Barcelona, 1–5 (2011).
- [4] Tan, Y., Zhang, H., Yang, D., Jiang, S., Song, J., and Sheng, Y. Tribology International 46(1), 137 – 144 (2012).
- [5] Zhang, H., Tan, Y., Yang, D., Trias, F. X., Jiang, S., Sheng, Y., and Oliva, A. Powder Technology 217, 467 – 476 (2012).
- [6] Zhang, H., Tan, Y., Shu, S., Niu, X., Trias, F. X., Yang, D., Li, H., and Sheng, Y. Computers & Fluids 94(0), 37 – 48 (2014).