



UNIVERSITY OF LEEDS

This is a repository copy of *Electro-osmotic piles*.

White Rose Research Online URL for this paper:
<http://eprints.whiterose.ac.uk/125827/>

Version: Accepted Version

Article:

Mohd Nizar, KN and Clarke, BG orcid.org/0000-0001-9493-9200 (2014) Electro-osmotic piles. *Proceedings of the Institution of Civil Engineers - Ground Improvement*, 167 (2). pp. 135-144. ISSN 1755-0750

<https://doi.org/10.1680/grim.12.00023>

Reuse

Items deposited in White Rose Research Online are protected by copyright, with all rights reserved unless indicated otherwise. They may be downloaded and/or printed for private study, or other acts as permitted by national copyright laws. The publisher or other rights holders may allow further reproduction and re-use of the full text version. This is indicated by the licence information on the White Rose Research Online record for the item.

Takedown

If you consider content in White Rose Research Online to be in breach of UK law, please notify us by emailing eprints@whiterose.ac.uk including the URL of the record and the reason for the withdrawal request.



eprints@whiterose.ac.uk
<https://eprints.whiterose.ac.uk/>

Table 3 A description of the test series

Series	Layout Codes	Comment	Remarks
Time of treatment	Q3	1 central anode; 8 cathodes	Treated with 1 day, 3 days, 5 days, 7 days, 15 days, and maximum days of treatment until the anode is corroded
	A1	2 anodes; 2 cathodes	
Numbers and arrangement of electrodes	Q2	4 anodes; 1 central cathode	
	Q4	1 central cathode; 8 anodes	
	Q1	4 cathodes; 1 central anode	
	Q3	1 central anode; 8 cathodes	
	A1	2 anodes; 2 cathodes	Forming a 124 mm square
	A2	4 anodes; 4 cathodes	at 62 mm radians from the centre, and 49 mm between anode to cathode
Different Applied Voltages	Q4	1 central cathode; 8 anodes	5 Volts, 10 Volts, and 20 Volts
	A2	4 anodes; 4 cathodes	5 Volts, and 10 Volts
	Q2	4 anodes; 4 cathodes	5 Volts, and 10 Volts