



UNIVERSITY OF LEEDS

This is a repository copy of *Shape optimisation of assembled single-layer grid structure with semi-rigid joints*.

White Rose Research Online URL for this paper:

<https://eprints.whiterose.ac.uk/id/eprint/154618/>

Version: Published Version

Proceedings Paper:

Liu, F and Tsavdaridis, K orcid.org/0000-0001-8349-3979 (2019) Shape optimisation of assembled single-layer grid structure with semi-rigid joints. In: OPTARCH2019 – Optimization Driven Architectural Design. 1st International Conference on Optimization Driven Architectural Design, 05-07 Nov 2019, Amman, Jordan. OPTARCH

This article is protected by copyright. This is an author produced version of a conference abstract published in the Proceedings for OPTARCH2019 – Optimization Driven Architectural Design.

Reuse

Items deposited in White Rose Research Online are protected by copyright, with all rights reserved unless indicated otherwise. They may be downloaded and/or printed for private study, or other acts as permitted by national copyright laws. The publisher or other rights holders may allow further reproduction and re-use of the full text version. This is indicated by the licence information on the White Rose Research Online record for the item.

Takedown

If you consider content in White Rose Research Online to be in breach of UK law, please notify us by emailing eprints@whiterose.ac.uk including the URL of the record and the reason for the withdrawal request.



eprints@whiterose.ac.uk
<https://eprints.whiterose.ac.uk/>

Shape optimisation of assembled single-layer grid structure with semi-rigid joints

Fengcheng LIU¹, Konstantinos Daniel Tsavdaridis^{2*}

¹PhD Candidate, School of Civil Engineering, University of Leeds
LS2 9JT, Leeds UK
cnfl@leeds.ac.uk

²Associate Professor of Structural Engineering, School of Civil Engineering, University of Leeds
LS2 9JT, Leeds UK
K.Tsavdaridis@leeds.ac.uk

ABSTRACT

It is generally known that the mechanical properties of connecting joints in assembled structures, such as strength and bending stiffness, have a great influence on the mechanical behaviour of the structure. Observations from earlier studies by Fathelbab (1987) confirmed that joint stiffness has a considerable effect on the load-displacement behaviour of a structure. Then, various types of joints have been experimented for their respective mechanical performances by Kato et al. (1998) and Ma et al. (2013), which have demonstrated different effects on reticulated shells. Furthermore, some new semi-rigid joints were developed by Feng et al. (2017), such as the ring-sleeve joint and the double-ring joint. It is worth to note that there are few studies of shape optimisation of assembled single-layer grid structure considering the effects of semi-rigid joints.

This paper takes the effect of the semi-rigid joints into account to optimise an assembled single-layer grid structure. Based on experimental results of the semi-rigid joints, finite element models of a single-layer grid structure with semi-rigid joints are established, and spring elements, as shown as Fig.1, are used to simulate the joint stiffness. The optimisation process is completed with the collaboration of ANSYS and MATLAB data. The research goal is to minimise the total strain energy. Genetic algorithm is used for the optimisation, and nodal z-coordinates are chosen as variables. The effect of the semi-rigid joints on the shape optimisation is studied by changing the joint stiffness. With this method, the optimal shapes of the assembled grid structure with different joint stiffness and improved buckling load are obtained.




Fig. 1 Space beam and virtual spring model

References

- [1] Fathelbab, F.A. (1987) The effect of joints on the stability of shallow single layer lattice domes. Ph.D. thesis, Univ. of Cambridge, U.K.
- [2] Kato, S., Mutoh, I. and Shomura, M. (1998) Collapse of semi-rigidly jointed reticulated domes with initial geometric imperfections. *J. Constr. Steel Res.*, 48(2-3), pp. 145-168.
- [3] Ma, H., Fan, F., Chen, G., Cao, Z. and Shen, S. (2013) Numerical analyses of semi-rigid joints subjected to bending with and without axial force. *Journal of Constructional Steel Research*, 90(5), pp. 13-28.
- [4] Feng, R., Liu., Yan, G. and Chang, X. (2017) Mechanical behavior of Ring-sleeve joints of single-layer reticulated shells. *Journal of Constructional Steel Research*, 128, pp. 601-610.