

This is a repository copy of *Crack tip fields 4*.

White Rose Research Online URL for this paper: http://eprints.whiterose.ac.uk/138555/

Version: Accepted Version

## Article:

Palin-Luc, T., James, N., Hong, Y. et al. (4 more authors) (2018) Crack tip fields 4. International Journal of Fatigue, 115. p. 1. ISSN 0142-1123

https://doi.org/10.1016/j.ijfatigue.2018.08.039

Article available under the terms of the CC-BY-NC-ND licence (https://creativecommons.org/licenses/by-nc-nd/4.0/).

## Reuse

This article is distributed under the terms of the Creative Commons Attribution-NonCommercial-NoDerivs (CC BY-NC-ND) licence. This licence only allows you to download this work and share it with others as long as you credit the authors, but you can't change the article in any way or use it commercially. More information and the full terms of the licence here: https://creativecommons.org/licenses/

## **Takedown**

If you consider content in White Rose Research Online to be in breach of UK law, please notify us by emailing eprints@whiterose.ac.uk including the URL of the record and the reason for the withdrawal request.



## **Guest editorial: Characterisation of crack tip fields**

Joint special issues of the International Journal of Fatigue (IJFatigue, Elsevier) and Fatigue & Fracture of Engineering Materials & Structures (FFEMS, Wiley) containing selected and fully peer reviewed papers from the 4th IJFatigue and FFEMS Joint Workshop on Characterisation of Crack Tip Fields held in Bonifacio, France over April 10 – 12, 2017.

Single parameter characterisation of the crack/notch tip field using fracture mechanics parameters like K, J or CTOD has been extremely powerful in advancing predictive technologies for critical or sub-critical crack growth. It has also become clear over the last 40 years that single parameter approaches have limitations particularly in dealing with crack growth phenomena arising from crack tip shielding, often resulting from the plastic enclave surrounding a crack. Influences of this enclave on the crack tip stress field ahead of the crack are maximised during cyclic loading. In the case of a parameter like the stress intensity factor which characterises the crack tip field via an elastic approximation, it is not surprising that any set of plasticity-induced circumstances which perturb the size of the plastic enclave and its associated strain field lead to predictive difficulties.

Over the last 30 years, a considerable research effort has explored these areas of difficulty, including short cracks, plasticity-induced closure, variable amplitude and mixed-mode loading, as well as notch effects. Increasing attention has hence been focused on using more than one fracture mechanics parameter. Attention has been directed, for example, towards incorporating the *T*-stress (the second term in a Williams-type expansion of the crack tip stresses) into life prediction methods, as the *T*-stress affects both the extent and shape of crack tip plasticity. It would therefore be expected to be influential in plasticity-related crack growth phenomena. The situation is further complicated where a crack experiences multiaxial loading and additional Mode II and III fracture mechanics parameters are necessary. Alongside this, new analytical models have been proposed and advanced experimental techniques now allow greatly improved measurement of 2D and 3D fields associated with the crack tip zone.

These issues were discussed in the fourth international workshop on Characterisation of Crack Tip Fields which was organized by both the French Society for Metallurgy and Materials, SF2M (<a href="www.sf2m.fr">www.sf2m.fr</a>) and the Italian Group of Fracture (<a href="www.gruppofratura.it">www.gruppofratura.it</a>). This workshop retained the successful format of the first three workshops<sup>1</sup>, based on a largely invited group of delegates and allowance of enough time for discussion after each paper with a final overall discussion on the topic in the closing session of the workshop, with the aim of obtaining an agreed summary of the current state of the area and the remaining problem areas.. The following main points were recorded in these discussions as being important:

- small cracks may require different parameters to long cracks for crack tip field characterisation;
- environment for small crack growth is important:
- interpretation of very slow crack growth rate (gigacycle regime) is an open question;
- shielding effects (including crack closure mechanisms) require further study;
- ensuring accuracy, repeatability, compatibility and correlation between various experimental techniques is key to making progress;
- the use of full field experimental measurement techniques (volumetric as well as surface) has to be encouraged:
- engineering applications and academic research need to be considered concurrently.

The papers selected for these joint Special Issues of IJFatigue and FFEMS present a range of research that illustrates both the complexity of the topic and the current endeavours that are giving detailed consideration to a number of these aspects.

The next IJFatigue and FFEMS Joint Workshop on Characterisation of Crack Tip Fields is proposed to take place in Heidelberg, Germany, between 8-10 April 2019.

The Guest Editors of this special issue warmly thank all the authors for their contributions and hope

<sup>1</sup> Forni di Sopra, Italy, 7 – 9 March 2011; Malaga, Spain, 15–17 April 2013; Urbino, Italy, 20–22 April 2015

that this overview of current thinking in the area of crack tip fields in relation to fatigue and fracture is useful for the research community.

**Guest Editors** 

Thierry Palin-Luc Arts et Metiers ParisTech, France

Neil James University of Plymouth, UK

Youshi Hong Institute of Mechanics, Chinese Academy of Sciences, China

Luca Susmel University of Sheffield, UK

Franck Morel Arts et Metiers ParisTech, France

Nicolas Saintier Arts et Metiers ParisTech, France

Sylvie Pommier ENS Paris-Saclay, University Paris Saclay, France