



UNIVERSITY OF LEEDS

This is a repository copy of *High spatial and temporal resolution vehicular emissions in south-east Brazil with traffic data from real-time GPS and travel demand models*.

White Rose Research Online URL for this paper:
<http://eprints.whiterose.ac.uk/155761/>

Version: Accepted Version

Article:

Ibarra-Espinosa, S, Ynoue, RY, Ropkins, K orcid.org/0000-0002-0294-6997 et al. (2 more authors) (2020) High spatial and temporal resolution vehicular emissions in south-east Brazil with traffic data from real-time GPS and travel demand models. *Atmospheric Environment*, 222. 117136. ISSN 1352-2310

<https://doi.org/10.1016/j.atmosenv.2019.117136>

© 2020 Elsevier Ltd. All rights reserved. This manuscript version is made available under the CC-BY-NC-ND 4.0 license <http://creativecommons.org/licenses/by-nc-nd/4.0/>.

Reuse

This article is distributed under the terms of the Creative Commons Attribution-NonCommercial-NoDerivs (CC BY-NC-ND) licence. This licence only allows you to download this work and share it with others as long as you credit the authors, but you can't change the article in any way or use it commercially. More information and the full terms of the licence here: <https://creativecommons.org/licenses/>

Takedown

If you consider content in White Rose Research Online to be in breach of UK law, please notify us by emailing eprints@whiterose.ac.uk including the URL of the record and the reason for the withdrawal request.



eprints@whiterose.ac.uk
<https://eprints.whiterose.ac.uk/>

High spatial and temporal resolution vehicular emissions in South-East Brazil with traffic data from real-time GPS and travel demand models

Sergio Ibarra-Espinosa^{a,b}, Rita Yuri Ynoue^a, Karl Ropkins^c, Xuelei Zhang^b, Edmilson Dias de Freitas^a

^a*Departamento de Ciências Atmosféricas, Instituto de Astronomia, Geofísica e Ciências Atmosféricas, Universidade de São Paulo, Brazil*

^b*Key Laboratory of Wetland Ecology and Environment, Northeast Institute of Geography and Agroecology, Chinese Academy of Sciences, Changchun 130102, China*

^c*Institute for Transport Studies, University of Leeds*

Abstract

Vehicular emissions are one of the most important source of pollution in urban centers, impacting air quality with a deleterious effect on human health and ecosystems. Air quality managers rely on emissions inventories to characterize pollution and sources. In this study we predicted vehicular emissions, using three sources of traffic data: 1) travel demand model outputs consisting of traffic simulations of light-duty vehicles, trucks, 2) and urban buses, and 3) a massive data set of real-time GPS coordinates of light-duty vehicles and trucks. The study area comprises the metropolitan areas of São Paulo, Santos, Vale de Paraíba, Sorocaba, and Campinas, which have a population of more than 30 million inhabitants. Once we generated hourly traffic flows, we used the Vehicular Emissions Inventory Model (VEIN) to predict fuel consumption and emissions. Emissions using travel demand model for the metropolitan area of São Paulo are CO 177406 t/y, NO_x 73554 t/y, NMHC 33999 t/y and PM_{2.5} 2281 t/y. The emissions using GPS data were higher than using travel demand outputs, because GPS average speeds were lower, producing higher emission factors.

Keywords: VEIN, Vehicular Emissions, Travel demand, Brazil, GPS

1. Introduction

In urban centers, vehicles are the most important source of air pollution [1]. The biggest urban agglomeration in South America is located in Southeast of Brazil, conformed by the Metropolitan Area of São Paulo (MASP) located near
5 to other 4 metropolitan areas: Baixada Santista (hereafter identified as Santos), Vale do Paraíba (in this work it will be identified by the name of its main city São José Dos Campos - SJDC), Sorocaba and Campinas, as shown on Fig. 1. Altogether these 5 metropolitan areas accounted for more than 30 million of inhabitants in 2016 according to the Brazilian Institute of Geography and
10 Statistics [2]. Air quality simulations conducted in these regions confirms that the main source of air pollution is road transportation [3, 4, 5]. An emissions inventory is a spatial and temporal characterization of the release of the mass of pollutants into the atmosphere which serves as a decision making tool and provides inputs for air quality modeling [6]. Therefore, improving the accuracy
15 of emission inventorying activities would help to improve the assessment of environmental policies, evaluate the emissions impacts on the climate, ecosystem and population exposure.

A key element to develop high temporal and spatial resolution bottom-up vehicular emissions inventories is the availability of traffic data. Some studies
20 use macro [7] and micro [8, 9] traffic simulations to estimate vehicular emissions. Others use traffic counts to allocate or produce traffic flow to later estimate emissions [10]. However, most of studies are often limited to the cruder top-down approaches based on aggregated traffic fleet information [11, 12]. Obviously, transportation emissions based on more representative traffic flow estimates
25 and emission factors would improve air quality management and modeling.

Recently, vehicular activity has been generated using data from Internet transportation companies. For instance, GPS datasets have been used to improve travel demands models (TDM) [13] to estimate emissions. Another approach consisted transform categorical congestion maps speed and traffic flow
30 estimates [14]. While these approaches are promising they still rely on secondary

data as the congestion maps and not the primary source of data. Also, it is not assured that the driving cycle associated with the categorization of the level of congestion informed by the Internet companies is representative elsewhere.

In this study we estimated road transportation emissions using three sources of traffic data in developing bottom-up vehicular emissions inventories: 1) 120 million GPS observations of light-duty Vehicles (LDV) and trucks from the company Maplink (<http://transito.maplink.global/>), 2) travel demand model simulations of light-duty and trucks from the Company of Traffic and Engineering of São Paulo (CET, <http://cetsp.com.br/>) and 3) travel demand model simulations for Urban Buses (UB) from the Secretary of Transport and Mobility (Sptrans, <http://www.sptrans.com.br/>). In contrast to other studies, we make direct use of primary GPS location data in this study and provide further details of the methods to extract traffic flow and speed information in an accompanying paper [15].

To work with this new type of data we improved the Vehicular Emissions Inventory Model (VEIN) [16], which is an R package available at <https://CRAN.R-project.org/package=vein> [17]. VEIN predicts hot and cold exhaust, evaporative, wear and resuspension emissions, and also provides further emission specification for chemical mechanisms and spatial geo-processing tasks associated with handling of gridded emissions. We used the emission factors from the official environmental agency of São Paulo [6], however, as these factors are constant by type of vehicle and year they entered into the market, we generated speed-dependent functions based on these values. Our objective is to estimate bottom-up vehicular emissions using traffic flow from real-time GPS and traffic demand models outputs, to produce emissions maps and compare results.

2. Material and Methods

2.1. Study area

The study area is delimited by the coordinates -47.856 to -45.484 degrees of longitude and -24.488 to -22.467 degrees of latitude. The area is located

60 at Southeast Brazil and covers the metropolitan areas of São Paulo (MASP),
 Santos, Sao José do Campos (SJDC), Sorocaba and Campinas. The area of
 study is shown in Fig 1. The political delimitation of each metropolitan area
 are smaller than the regions presented, with exception of MASP. In other words,
 we added more municipalities into each metropolitan area because we have data
 65 for the whole area, and not only for each geopolitical defined metropolitan area.




Figure 1: Area of study: Metropolitan Areas (delimited by black lines), topography (shaded) and road network (colored lines)

2.1.1.1. Road network

We used transport network data from OpenStreetMap [18] to add road layouts to Fig. 1. The OpenStreetMap data included several non-road transport networks (rail, pedestrian paths, etc). We excluded these by downloading the
 70 data with the QGIS software [19] and filtering only streets with the following

attributes: *motorway, trunks, primary, secondary, tertiary* and *residential* and the associated 'link' junction streets. The road network of Fig. (1) shows how the metropolitan areas are connected by motorways and trunk roads inside each region.

2.2. Traffic activity data

75

This study is focused in comparing emissions inventories using three sources of traffic data: GPS position of vehicles that feeds the Internet traffic site Maplink (<http://transito.maplink.global/>); Traffic simulations from Traffic Engineering Company (CET <http://www.cetsp.com.br/>) in São Paulo for Light Duty Vehicles (LDV) and Trucks; and Traffic simulation of Urban Buses (UB) from SPtrans (<http://www.sptrans.com.br/>)

80

2.2.1. Traffic simulations

The Traffic Engineering Company of São Paulo (CET) is the agency that performs the transport planning in São Paulo city. They have a specific department dedicated to 4-stage traffic simulations using data from an Origin-Destination-Survey (ODS) [20] which started in the decade of 1950 in São Paulo. A classic reference of a 4-stage modeling transport is presented in the work of Ortuzar and willumsen (2002) [21]. The 4 stages of the traffic modeling includes characterization of trip attractions and productions by zone in some regions, distribution of these trips, preferred mode of transport for traveling and finally the allocation of the trips at each mode, in our case into the road network. The survey is made by Metro (<http://www.metro.sp.gov.br/>), which is the underground company in São Paulo, every 10 years with a smaller update after 5 years. The information gathered in the ODS is massive with the participation of thousand of commuters, helping to identify characteristics of the trips inside MASP. CET uses the information from the survey and performs the travel demand modelling. In this case, it is a macro or strategic travel demand simulation which represents the equilibrium between offer and supply of transportation at maximum load of the road network, that is, at the morning rush hour, which is from 08 to 09

85

90

95

100 local time.

The CET travel demand simulation provide initial and final identification number of node, volume of light-duty vehicles $\text{veh} \cdot \text{h}^{-1}$, trucks, $\text{veh} \cdot \text{h}^{-1}$, number of lanes, capacity $\text{veh} \cdot \text{h}^{-1}$, free flow speed $\text{km} \cdot \text{h}^{-1}$, peak speed $\text{km} \cdot \text{h}^{-1}$, type of street and travel-time for each link.

105 The Secretary of Transport and Mobility of São Paulo (SPTrans) is the agency responsible for public transportation by buses, and also uses origin-destination survey [20] to make traffic simulation for the rush hour.

The traffic simulations for light-duty vehicles, trucks and buses are shown on Fig. 2. Light-duty vehicles activity is more concentrated in urban motorways located near to the center of the city. There are streets where Light-duty vehicles traffic flows exceed more than $15,000 \text{ veh} \cdot \text{h}^{-1}$. Trucks are concentrated on motorways around the city where flows can exceed $7,000 \text{ veh} \cdot \text{h}^{-1}$. As with light-duty vehicles, Bus activity is concentrated near the center of the city, but also has an east to south-west gradient. Bus flow can exceed $5,000$ per street $\text{veh} \cdot \text{h}^{-1}$.
115 As the travel demand model only covers morning peak hour, we used expansion factors to extrapolate to the 168 hours a week [7, 16]. The expansion factors were generated using hourly traffic counts from toll stations administrated by the Transportation Agency (ARTESP <http://www.artesp.sp.gov.br>) located near the city.

120 We obtained 124 million GPS observations of Cars and Trucks for the study area for the period between 2014-10-06 00:00 and 2014-10-12 23:00. This data set of 145 hours was filled to sum 168 hours of a week of data. We generated traffic flows for light-duty vehicles and trucks by associating average speed and data-base of traffic counts and speed recordings by type of street. The process
125 used to extract traffic flow information from these GPS records is described in detail in an associated MethodsX paper[15].

Table 1 shows the a summary of the traffic data developed for this study. The GPS data includes passenger cars (PC) and Trucks. The second source of data is travel demand model simulation of light duty vehicles (LDV) and Trucks
130 and the third is also TDM of buses. Therefore, we aggregated the traffic data




Figure 2: CET Traffic simulation of (a) Light-duty vehicles and (b) Trucks, and (c) SPTrans simulation of buses from 08 to 09LT.

using two methods, the first method was named **A** which is formed by GPS recordings from light and trucks vehicles and TDM from buses. The second method was named **B** which is formed by TDM outputs from light vehicles, trucks and buses.

2.2.2. Vehicular composition

135

We considered 5 general types of vehicles: passenger cars (PC), light-commercial vehicles (LCV), trucks, buses and motorcycles (MC). The vehicular composition divides these categories by engine size and gross weight [7]. As the input traffic data does not include specific type of vehicles, we used the vehicular composition from CETESB for São Paulo [6]. Cars from GPS recordings and light-duty vehicles from traffic simulation were split into 73.70 % PC, 13.90 %

140

Table 1: Sources of traffic data used in this study

Data	Method A	Method B
1) GPS: PC + Trucks	PC (GPS)	PC (TDM)
2) TDM: LDV + Trucks	Trucks (GPS)	Trucks (TDM)
3) TDM: Bus	Bus (TDM)	Bus (TDM)

TDM is travel demand model.

light-commercial vehicles and 12.40 % motorcycles, the other percentages are shown on Table (2). In this way, we have a vehicular composition which is similar to the CETESB, however, we further identified the engine size of passenger cars using data from the using data of the National Association of Cars
145 Manufacturers of Brazil (ANFAVEA, [22]).

In Brazil there are mostly three types of automotive motors, 4-strokes, flex 4-strokes and diesel-compression. Standard 4-strokes engines uses gasohol, which is gasoline with 25% of ethanol (E25). Flex engines can use gasoline with any
150 mixture of ethanol between 25% and 100%, so drivers are able to choose gasoline blends between E25 and E100. Compression engines use diesel with 5% of biodiesel (B5). We consider fleet statistics of engine size, weight and type of fuel used from the report of vehicular emissions inventory for São Paulo [6]. Passenger cars were divided by size of the engine with sales statistics of
155 the National Association of Car Manufacturers [22] as: 38.14% ≤ 1400 cc, 58.12% $1400 < cc \leq 2000$ and 3.74% > 2000 cc. Motorcycles were divided with sales statistics of the National Association of Motorcycles Manufacturers [23] as: 84.24% ≤ 150 cc, 12.32% $150 < cc \leq 500$ and 3.44% > 500 cc. Each category is then distributed by age of vehicle, using the data from official inventory for São Paulo [6]. The categories Bus SP and ABus (Articulated
160 Bus), shown on Table 2, are urban public transportation. According to SPtrans (<http://www.sptrans.com.br/indicadores/>) the average age of UB was 5.2 in 2014, therefore, we adjusted the max age of this category to 10 years of use so

that the average age approximately 5.

2.3. Calibration of traffic

165

Vehicular emissions inventories must be validated. European Commission for emissions inventorying guidelines recommend that fuel consumption estimates be normalized by fuel sales in a region [24]. In the case of bottom-up approaches, the inventory is calibrated by factoring the traffic flow because the length of the road is constant. The fuel sales information comes from the Yearbook of Energy and Statistics for São Paulo State 2014 [25] covering each municipality in São Paulo State. The total amount of fuel sold in 2014 for automotive use and for each metropolitan region is shown on Fig. 3. Most of fuel sales are in MASP because it is the bigger area with most inhabitants and number of vehicles with $4.65 \cdot 10^9$ litres of gasohol, $3.02 \cdot 10^9$ litres of ethanol and $3.14 \cdot 10^9$ litres of diesel. In MASP, the consumption of gasohol is clearly higher than the consumption of gasohol in other regions, while the consumption of the different type of fuels is more similar in the other regions. This could result in a higher emissions ratio of hydrocarbons versus nitrogen oxides in MASP, with implications in tropospheric ozone formation. Specifically, some studies have shown that the increase of gasohol over ethanol locally reduces O_3 , while increasing NO_X and CO [26] and reducing hydrocarbon emissions, would reduce ozone formation [27, 28].

170

175

180

The fuel sold for automotive use is not always used for that purpose. For example, a small fraction of electric generators use diesel or (less commonly) gasoline purchased from transport sector suppliers. Therefore, we expect that a fraction of the fuel sales were used for other uses. In order to account for such usage, we applied the assumption that 20% of B5 was used for other purposes than automotive. This means that the fuel consumption estimated from the traffic would be 80% B5 and 100% E25 and E100. There is no available information about diesel sold for electricity generation but we believe this value is reasonably conservative.

185

190

Table 2: Vehicular composition used in this study.

Veh	Fuel	Size	%	Veh	Fuel	Size	%	
PC	E25	<1400 cc	14.21	MC	E25	<150 cc	74.04	
		1400-2000 cc	21.65			150-500 cc	10.83	
		>2000 cc	1.39			>500 cc	3.02	
	FE25	<1400 cc	8.5		FE25	<150 cc	3.77	
		1400-2000 cc	12.93			150-500 cc	0.55	
		>2000 cc	0.83			>500 cc	0.15	
	FE100	<1400 cc	14.48		FE100	<150 cc	6.42	
		1400-2000 cc	22.07			150-500 cc	0.94	
		>2000 cc	1.42			>500 cc	0.28	
	E100	<1400 cc	0.93		Trucks	B5	3.8-6 t	8.38
		1400-2000 cc	1.42				6-10 t	25.5
		>2000 cc	0.09				10-15 t	15.28
LCV	E25		39.13			15-40 t*	24.98	
	FE25		15.21			15-40 t**	25.85	
	FE100	<3.8 t	25.9	Bus		<15 t	9.07	
	E100		1.18	Coach		>18 t	13.5	
	B5		18.56	Bus SP	B5	<15 t	17.23	
				Bus SP		15-18 t	28.81	
				ABus SP		15-18 t	14.07	

Note: * Rigid Trucks < 15 t and Articulated Trucks < 40 t. ** Rigid Trucks < 15 t and Articulated Trucks > 40 t.




Figure 3: Fuel sales for 2014 for metropolitan areas Campinas, MASP, Santos, SJDC and Sorocaba.

2.4. Emissions modeling

2.4.1. Aggregation of traffic flow

Hourly traffic flow information was extracted for light-duty vehicles and trucks from GPS records with a spatial coverage of all the metropolitan areas for this study. The traffic simulations from CET and SPtrans includes one morning rush traffic data for a typical working day of 2014, including volume of light-duty vehicles, trucks and buses for MASP. With this information we configured the traffic flows that cover all regions with two methods:

Method A: Traffic from GPS records in all regions. MASP with travel demand simulation of urban buses from SPtrans.

Method B: Traffic from GPS records except MASP. MASP with traffic simulation from CET and SPtrans of light-duty vehicles, trucks and buses.

We included travel demand simulation of urban buses in method A, because GPS data only considers light-duty vehicles and trucks, The proportion between buses from SPTrans and trucks from CET is 0.27. Therefore, including the bus flow from SPTrans into GPS data set, requires keeping the same proportion. This was accomplished by factoring the buses inside the GPS data-set by 0.17, which was obtained by multiplying 0.27 times the proportion of GPS trucks and

buses. The method B uses GPS records for all regions with exception of MASP where travel demand simulations are used instead.

2.4.2. *VEIN model*

The Vehicular Emissions INventory (VEIN) model [16] is an R package that
215 estimates bottom-up or top-down vehicular emissions. VEIN estimates hot and cold exhaust, evaporative, wear and re-suspension emissions. VEIN can use either morning rush hour data or hourly data for different hours as an input. Here, we used data from all hours when working with traffic information extracted from GPS records and morning rush hour information when working
220 with traffic simulations. In this latter case where other hours were not output by the model, VEIN provides functions to extrapolate morning traffic and speeds to other hours. This data was divided according to estimated vehicular composition (type, engine size, weight and fuel) without considering the emission standards. So, for example, passenger cars using gasohol with engine lesser
225 than 1400 cc is one category of vehicle composition. Then, age distribution was applied to each vehicular composition category. This allows to have the vehicular composition by age, for example: passenger cars using gasohol with engine lesser than 1400 cc with one year of use. The age distribution was based on statistics on vehicles in circulation from sources including licensing records
230 [6].

Emission Standards can then be assigned to these subcategories on the basis of age of vehicle. Emission factors available in VEIN are from: the official emissions inventory for São Paulo State developed by the Environmental Company [6], the European emission guidelines [24], and the International Vehicular
235 Emissions model [29]. Besides, the model has functions to transform constant emission factors into speed functions. Finally, VEIN also imports functions from the model eixport [30] which exports emissions information in several different useful formats.

2.4.3. Emissions Factors

VEIN model allows the user to choose between local emission factors, speed functions from Ntziachristos and Samaras (2016) [24] or scaled factors to incorporate speed variation into local factors. In the case of São Paulo, the vehicular emissions inventory reports the emission factors of new vehicles that entered into the market each year [6]. These factors are the average emission certification values for: the Federal Test Procedure (FTP-75) for 4-strokes light-duty vehicles; the World Motorcycle Test Cycle for motorcycles; and the European Stationary Cycle for heavy-duty vehicles. The Federal Test Procedure consists in three phases: cold start, stabilized and hot start. It has a duration of 1877 seconds and a distance of 17789.56 m with an average speed of $34.2 \text{ km} \cdot \text{h}^{-1}$ [31]. World Motorcycle Test Cycle consists in three parts of 600 seconds, the first part covers a distance of 4065 m in an average speed of $24.4 \text{ km} \cdot \text{h}^{-1}$, the second part 9111 m and $54.7 \text{ km} \cdot \text{h}^{-1}$, and the third part 15736 m and $94.4 \text{ km} \cdot \text{h}^{-1}$, which gives a weighted mean of $71.55 \text{ km} \cdot \text{h}^{-1}$ [31]. The European Stationary Cycle is a cycle for testing the engine in a dynamometer at different combinations of engine speed, load and weight with different duration [32].

Brazilian emission factors covers the following pollutants from exhaust and evaporative processes: CO, NO_x, PM, SO₂, HC, NMHC, Aldehyde, CO₂ and N₂O [6]. We assigned the vehicular composition with the categories of the European Emissions Guidelines [24], including equivalence of emission standards [16]. This allowed us to create an scaled emission factor between the local source of Brazilian emission factors and the speed dependent functions from Ntziachristos and Samaras (2016) [24]. As a result, we incorporated speed variation into the local emission factors. The scaling process consists in identify speed functions so that, at the speed of the driving cycles, it will return exactly the same value of the local emission factors [6]. European Stationary Cycle driving cycle does not have driven speed and instead it has motor speed, so we are assigning the speed of Federal Test Procedure-75, which is $34.2 \text{ km} \cdot \text{h}^{-1}$. In the case of World Motorcycle Test Cycle for motorcycles, the speed is 54.7

km · h⁻¹ according to the reference report on driving cycles from the Transport
and Research Laboratory (TRL) [31]. This adjustment is done automatically
270 by the function `ef_ldv_scaled` and `ef_hdv_scaled` in VEIN [16].

The European speed functions emission factors depend on the EURO emis-
sion standards [24]. Therefore, in order to select the right speed function, it
is necessary do an equivalence between Brazilian and European Emission stan-
275 dards. Both emission standards are relatively similar but in Brazil they are
delayed. Brazilian emission standards are named Proconve for light-duty vehi-
cles and heavy-duty vehicles and Promot for motorcycles [33]. Proconve L6 is
equivalent to Euro V phase, L3 to Euro II, L2 to Euro I and L1 to Pre-Euro.
In the case of heavy-duty vehicles, Proconve P7 is equivalent to Euro V, P5 to
280 Euro III, P4 to Euro II, P3 to Euro I and the rest of the older fleet is equiva-
lent to the Pre-Euro phase. Motorcycles are directly equivalent, Promot M3 to
Euro III, M2 to Euro II, MI to Euro I. This equivalence was made based on the
site <http://www.transportpolicy.net/region/south-america/brazil>, and already
proposed for Brazil [16]. In the absence of local data, we estimated deteriora-
285 tion on basis of accumulated mileage for CO, NO_X and HC emissions using the
European emission guidelines method [24].

The emission factors are numerous so we selected only some to show in
Fig. 4. The highest emission factors of CO are due to older passenger cars at
two speeds with 71.50 g · km⁻¹. Newer vehicles emit less due to technological
290 improvements made according to the stringent emission standards. The Fig. 4
shows a) CO, c) NO_X, d) HC, and f) PM emission factors g · km⁻¹ for passenger
cars using gasohol and b) CO, d) NO_X, f) HC and h) PM emission factors for
light trucks as function of speed and age of use. In all cases, when older vehicles
are at lower speeds, the emissions factors are higher. The emission factors by age
295 of use have incorporated the deterioration effect due to accumulated mileage.
Hence, it is possible to see a peak of emissions around 20 years of use in panels
a), c) and e). The emission factors by age of use have a general trend of lower
certification emissions values for newer vehicles, despite that occasionally, new
vehicles can have values a little higher than those of previous year. Brazilian

provides emission factors for light-duty vehicles since 1976 and for heavy-duty 300
vehicles, since 1999, but for this study we are assuming that the oldest
vehicle in circulation is 40 years of use, as shown on Fig. 4. This figure also
shows the average speed of GPS traffic data of $26.64 \text{ km} \cdot \text{h}^{-1}$ with red lines, and
the speed of travel demand simulation of $39.58 \text{ km} \cdot \text{h}^{-1}$ with black lines. The
average speeds shown as red and black lines of Fig. 4 covers the whole 168 305
hours. As the average speed of GPS is lower than travel demand simulation,
results in higher emission factors in most of cases, with exception of PM which
does not vary with speed.

Evaporative emissions are due to the vaporization of fuel, driven by varia-
tions in ambient temperatures. VEIN includes methods to estimate evaporative 310
emissions based on the European Council emissions guidelines [34]. Also, VEIN
includes CETESB emission factors, which are average values from emissions cer-
tification test Sealed Housing for Evaporative Determination (SHED)[6]. The
standard consists in 1 g for only 2 hour/test, while in China, Europe and USA
the duration of the tests covers 24 hours, 48 hours or 72 hours [35]. Therefore, 315
CETESB emission factors are presumably low. The emissions factors for
diurnal ($\text{g} \cdot \text{day}^{-1}$), hot_soak ($\text{g} \cdot \text{trip}^{-1}$) and running_losses ($\text{g} \cdot \text{trip}^{-1}$) evapo-
rative emissions, for 4-strokes PC and LCV and temperatures in ranges of and
 20°C and 35°C are shown on Fig. 5. For comparison, it was added European
emission factors [34] showing that diurnal emissions are lower than European, 320
hot-soak are relatively similar and running-losses are higher. As conclusion,
CETESB emissions factors still provide insightful information. Vehicles older
than 28 years produce higher emissions and, unsurprisingly, evaporative emis-
sions increase with temperature.

To our knowledge, the only evaporative emission factors available in liter- 325
ature with Brazilian chemical composition in the fuel comes from CETESB.
However, as our activity is traffic flow on streets, we had to transform the evap-
orative emission factors suitable. Hence, we converted each emission factor into
 $\text{g} \cdot \text{km}^{-1}$. We divided the emission factors of diurnal evaporative ($\text{g} \cdot \text{day}^{-1}$) with
the daily mileage ($\text{km} \cdot \text{day}^{-1}$) by age of use of each type of vehicle. We used 330




Figure 4: Exhaust emission factors ($\text{g} \cdot \text{km}^{-1}$) depending on speed and age of use for Passenger Cars using Gasohol of a) CO, c) NO_x , e) HC, g) PM, and Light Trucks using Diesel of b) CO, d) NO_x , f) HC and h) PM .

the mileage functions inside VEIN that are based on odometer reading of more than 1.6 million vehicles from inspection and maintenance programs made in São Paulo [36], these functions return the annual mileage which was divided by 365 to obtain the daily mileage. The other emission factors in $\text{g} \cdot \text{trip}^{-1}$ were converted to $\text{g} \cdot \text{day}^{-1}$ multiplying by $4.6 \text{ trips} \cdot \text{day}^{-1}$ and then we divided by the daily mileage $\text{km} \cdot \text{day}^{-1}$ by age of use of each type of vehicle. Therefore we used

this value from the statistics of the [37], U.S. Department of Transportation. The sum of the three types of evaporative emission factors are shown in Fig. 5. To our knowledge, there are no statistics with the number of trips per day in São Paulo. Evaporative emissions factors, as shown on Fig. 5, have a clear pattern of higher emissions in older vehicles. 340




Figure 5: Sum of Diurnal, Hot-Soak and Running Losses evaporative emission factors ($\text{g}\cdot\text{km}^{-1}$) by age of use for an averaged temperature between 20°C and 35°C . 345

3. Results

3.1. Traffic calibration

Traffic data from all sources were calibrated according to local fuel sales. Table 3 shows the calibration factors for traffic by type of fuel and region. This indicates that, prior to calibration, GPS-based methods tended to overestimate traffic activity values for both gasohol (E25) and ethanol (E100) fueled vehicles and underestimate flows for diesel (B5) fueled vehicles, except at MASP. This region has more *motorways* and *trunks* than other regions, so may be more sensitive to the use of speed as proxy for other traffic properties, described in de- 350

Table 3: Calibration factors for traffic by type of fuel in each region and scenario

Region	E25		E100		B5	
	Factor	%	Factor	%	Factor	%
MASP (Method A)	0.495	101.22	0.393	100.05	0.0124	84.14
Campinas (Method A)	0.2695	101.01	0.262	100.61	4.63	84.39
SJDC (Method A)	0.362	100.27	0.238	100.16	3.7	85.40
Santos (Method A)	0.265	100.09	0.164	100.73	5.15	85.61
Sorocaba (Method A)	0.181	100.50	0.199	100.55	3.5	85.56
MASP (Method B)	1.135	100.41	0.905	100.47	0.36	85.46

tail in an associated MethodsX paper[15]. Simulation-based activity values were only available to MASP, but these tended to require less aggressive calibration.

3.2. Emissions inventories

Table 4 shows the emissions inventories for each region; CO₂* is expressed as 10⁶t and Vehicles times kilometers (VKM)** as 10¹². In all regions, light vehicles are more responsible for emissions of CO, HC, NH₃ and CH₄, and heavy vehicles for PM, NO_X and SO₂. In the case of CO₂, the emissions are more equally distributed between these vehicles. Consistent with their VEIN profiles, lighter vehicles emits more CO, NMHC, NH₃ and CH₄, whilst heavier vehicles produce more PM, NO_X and SO₂, and CO₂ emissions are more evenly distributed across the vehicle fleet. The total emissions for MASP area are 3021.3 t · y⁻¹ and 2281.1 t · y⁻¹ of PM, 283322.6 t · y⁻¹ and 177406.8 t · y⁻¹ of CO, 89462.6 t · y⁻¹ and 73554.6 t · y⁻¹ of NO_X, 89485.4 t · y⁻¹ and 33999.3 t · y⁻¹ of NMHC, 2310.4 t · y⁻¹ and 1670.6 t · y⁻¹ of NH₃, 2019.8 t · y⁻¹ and 2000.1 t · y⁻¹ of SO₂, 6018.7 t · y⁻¹ and 4156.9 t · y⁻¹ of CH₄ and 21.72 Mt · y⁻¹ and 21.05 Mt · y⁻¹ of CO₂, from Method A (GPS) and Method B (travel demand simulation), respectively. The emissions from Method A are higher than Method B for all pollutants, however, the values for CO₂ are practically the same.

In MASP, the aggregation of emissions from passenger cars, light-commercial

vehicles and motorcycle account for 6.84% and 8.06 % of PM, 96.04% and 370
95.16% of CO, 29.37% and 29.65% of NO_X, 96.69% and 93.96% of NMHC,
98.69% and 97.89% of NH₃, 29.66% and 23.88% of SO₂, 98.73% and 99.09% of
CH₄ and 67.22% and 68.05% of CO₂, from GPS and travel demand simulation,
respectively. The results present convergence between percentages of emissions
using both methods, in agreement with other studies [38, 39, 40, 6]. 375

Emissions were higher in MASP by comparison to other regions, reflect-
ing trends in the activity data. For example, in the cases of PM, CO, NO_X,
NMHC, CH₄ and CO₂, the highest emissions were all obtained for MASP using
GPS methods, which estimated the lowest VKM values and speeds, as shown in
Fig. 4. This is because lower speeds are associated with congestion and higher 380
emissions in the VEIN source profiles. As this is highly likely to be represen-
tative of the situation in MASP by comparison to, e.g., Santos, this highlights
the importance of incorporating the most representative measures of kinematic
parameters into vehicular emissions inventorying methods.

The vehicular emissions inventories produced in this study also attempt to 385
estimate the potential influence of vehicle age. With this in mind, we present
figures showing the total amount of pollutants by age of vehicle. This allows
us to propose a regional *signature* for each pollutant, which we define as the
total amount of emissions by vehicle age, see e.g. Fig. 6. To understand these
figures it is necessary to remember that emission factors are higher for older 390
(by comparison to newer) vehicles as shown on Fig. 4 due to the deterioration
of vehicles, and also due to the fleet distribution. Emissions of CO and HC
shows three peaks, for vehicles newer than 10, at 20 and older than 30 years.
The reason of the first peak is the rapid increase in fleet size between 2000 and
2011. The second peak is associated with 19-23 year old vehicles. According to 395
the Manual of Air Pollution Control Program by Motor Vehicles [41], vehicles
with catalytic systems entered the fleet with the Brazilian emissions standard
Proconve L2, in 1992. Therefore, the second peak is due to vehicles of this era
with deteriorated catalytic systems. The third peak is due to relatively small,
but much older fleet with higher associated emission factors. Emissions of NO_X 400

Table 4: Emissions ($t \cdot y^{-1}$) for each regions and scenario in 2014 .

Region	Veh	PM	CO	NO _x	NMHC	NH ₃	SO ₂	CH ₄	CO ₂ *	VKM**
Camp Method A	PC	20.80	72743.70	7214.00	25056.00	741.80	174.50	1741.90	4.06	61.67
	LCV	52.50	7033.50	1752.50	4480.60	103.90	32.00	233.00	0.83	10.41
	HGV	2424.40	6660.30	42079.70	1830.30	24.40	942.20	23.10	3.98	9.78
	MC	0.00	11636.10	780.00	1151.50	8.70	10.30	224.30	0.28	10.47
Santos Method A	PC	5.40	17640.30	1868.00	6159.00	173.50	36.90	417.10	0.90	2.40
	LCV	13.70	1846.40	442.60	1134.60	25.20	7.30	56.00	0.20	0.43
	HGV	775.90	2052.50	13191.80	546.20	7.80	296.90	7.40	1.25	0.61
	MC	0.00	3275.00	222.30	297.80	2.20	2.70	57.50	0.07	0.46
SJDC Method A	PC	5.80	19148.50	1988.90	6630.60	187.30	40.60	449.00	0.99	2.73
	LCV	14.60	2025.70	474.40	1218.40	27.10	8.00	60.20	0.22	0.48
	HGV	513.30	1434.30	8965.40	393.50	5.20	202.00	4.90	0.85	0.39
	MC	0.00	3440.30	232.40	319.40	2.40	2.90	61.40	0.08	0.52
Soro Method A	PC	5.00	17708.90	1856.20	6061.70	186.00	43.80	433.60	1.00	1.97
	LCV	12.70	1834.00	444.00	1068.10	25.70	7.80	57.90	0.20	0.33
	HGV	556.80	1409.60	9254.60	364.10	5.60	208.40	5.30	0.88	0.36
	MC	0.00	3146.30	215.70	275.00	2.10	2.60	54.60	0.07	0.32
MASP Method A	PC	58.40	216870.40	19458.40	70080.00	1974.60	477.80	4689.70	11.40	493.06
	LCV	147.50	24418.70	4851.90	12983.20	281.60	92.60	628.50	2.43	101.06
	HGV	2555.70	7865.30	47567.40	2349.50	25.80	1071.60	24.40	4.49	70.24
	Bus	259.70	3364.00	15624.40	615.30	4.40	349.20	51.90	2.63	5.56
	MC	0.00	30804.20	1960.50	3457.40	24.00	28.60	624.20	0.77	105.36
MASP Method B	PC	53.70	127637.80	16307.70	30435.90	3422.40	278.20	3069.50	11.01	1932.57
	LCV	136.8	14021.70	3810.90	5692.70	339.30	178.50	433.9	2.63	356.35
	HGV	1582.2	6089.56	38455.53	1486.64	28.42	1125.89	17.05	4.92	122.25
	Bus	84.65	1319.95	5853.24	207.30	1.64	201.63	15.87	1.10	10.15
	MC	0.00	28622.60	1863.30	3382.80	25.20	11.90	651.40	0.76	336.43
MASP CETESB	PC	56	103858	11909	24302		302		7.16	
	LCV	10	18484	6118	4071		387		2.23	
	HGV	756	3440	20054	985		667		2.97	
	Bus	410	2842	15117	658		69		1.58	
	MC	69	34271	1134	4808		138		0.45	

Camp is Campinas, SJDC is São José Dos Campos, MASP is Metropolitan Area of São

Paulo. CO₂* are divided by 10⁶, VKM are divided by 10¹²

and PM shown on Fig. 6 exhibit a less similar trend with a higher central peak, that associates with newer vehicles.




Figure 6: Signature of vehicular emissions in $t \cdot y^{-1}$ by age of use and source of traffic in all metropolitan regions.

The emission maps of CO, NO_x, HC and PM for traffic data from Method A, and Method B and their difference are shown in Fig. 7. CO maps generated using Method A and Method B data look reasonably similar and their difference shows CO from Method A data is higher, specially in urban central motorways. In the case of NO_x, maps generated using travel demand model data clearly indicate a stronger contribution from the motorway ring road to the south of MASP. This is less pronounced for Method A data derived NO_x maps because speeds from *trunks* and *motorways* were used as a proxy for traffic flow. The difference of NO_x shows also the ring Method B produced more emissions than Method A into the motorway ring road, however, Method A produced more emissions towards the center of the city. The HC emissions seems to be similar with CO, with hot-spots in the center of the city and the difference also showing more contribution from Method A data. The emissions of PM follows a similar pattern to NO_x, with a clear contribution from Method B in the motorway ring.

There is also an emissions peak in a street in the south west part of the region, at longitude 47.5 W and latitude 24.4 S, due to high truck activity in this area. We used satellite data to corroborate this finding.

420 The hourly emissions of CO, NO_x, NMHC and PM, for the 168 hours of the study period are shown in Fig. 8, at the left the scenario with Method A and the right the scenario with Method B for MASP. Emissions estimated with Method A have a similar pattern for different pollutants, and, in the case of Method B, morning rush traffic flows were extrapolated using temporal factors
425 of the same normalized traffic counts from the nearest toll stations from São Paulo. Emissions from GPS data presents profiles relatively constants for CO and NMHC, with lower emissions at night and early morning, and lower emissions on weekends. In the case of NO_x the profile is more marked, reflecting the contributions from Buses as estimated using the SPTrans traffic simulation. On
430 contrast, emissions from the Method B have marked profiles in all emissions.

4. Discussion and uncertainty

This paper attempts to contribute to our understanding of air pollution by developing detailed bottom-up vehicular emissions inventories, using as its basis real-world GPS and simulation data on speeds and flows of different vehicle types, and regional fuel sales re-scaling to account for provide a potentially
435 more robust measure of vehicle activity. This also uses VEIN [16] to incorporate vehicle age adjusted emission factors for local fleets in Southeastern Brazil. Although we believe this provide a good measure of local traffic-related emissions, we also feel it is important to acknowledge that each stage of the inventorying
440 process included difficulties, challenges, assumptions and uncertainty, and that these provide opportunities for future improvements.

Developing a bottom-up vehicular emissions inventory with data from massive GPS (multiple-vehicle type) recordings is, to our knowledge, a new approach approach and methods may require further refinement but this paper provides,
445 at the very least, an exploratory analyses. The use of large GPS data sets as




Figure 7: Emission maps of CO, NO_x, NMHC and PM, in t · year⁻¹, due traffic activity from scenarios Method A (left) and Method B (center) and difference between the two (right) in 2014.




Figure 8: Hourly emissions of CO, NO_x, HC and PM, in $t \cdot h^{-1}$ due traffic activity from scenarios Method A (left) and Method B in MASP (right).

a source of traffic activity information seems an obvious step-forward by comparison to traditional used in traditional emissions inventorying projects. That said, it is important to acknowledge that the certainty of outputs is influenced by the quality and frequency of GPS, its degree of fleet coverage and its potential bias, for example, towards newer vehicles or commercial fleets as coverage of these is likely to be higher. As the traffic flow calculation is based on average speed by vehicle, if the frequency of the GPS observation is higher the uncertainty on the speed calculation and hence the traffic flow is reduced and it is likely that newer fleets can count with GPS with the mentioned characteristics. Data sets and methods such as these that consider multiple vehicle types and attempt to re-scale measurements according to independent measures of fleet sizes provide an obvious step-forward by contrast to earlier GPS-based methods that extrapolate GPS data from one sub-group of drivers to all of the vehicle fleet independent of driver or vehicle type. Access to larger and more complete data sets with improve with time, as, hopefully, will our access to more detailed data, allowing us to move beyond the use of current compromises such as the use of speed as proxy for traffic flow.

The process of generating trucks flow from GPS recordings consisted in using the speed of trucks and when there is no available information, the average speed of all vehicles only for *motorways* and *trunks* type of streets. This process seems appropriate for light-duty vehicles but in the case of trucks could lead to assignment in the same streets of light-duty vehicles which could not necessary be truth. Circulation of trucks deliver goods and this determine the route they follow. Therefore, this traffic flow could not have an exact spatial representation. This could be reason why PM and NO_x emissions from from GPS have different spatial distribution on Fig. 7 than the generated with travel demand models. This figure shows clearly a ring of NO_x and PM emissions surrounding the city of São Paulo in emission maps generated using travel demand simulation but not with GPS data. On the other hand, this data provided insights of trucks flow that hardly could be obtained from other sources. For example, trucks on the Santos Region are important because this city is a port, attracting

and generating goods delivery using trucks. Traffic data from GPS in Santos identified streets with high number of trucks near the port and also, in the streets at south est of the study area. We corroborated this findings with Google image
480 satellites (not shown here). Traffic speeds from GPS was used for generating traffic flow based on a set of traffic and speed measurements for MASP during 2012, [42]. Unequivocally, updating and enhancing this information with new data sets could improve traffic flow generation. Therefore, traffic data from Internet GPS recordings is a promising new traffic data source for emissions
485 inventories.

Where travel demand simulation was used, for example for CET light-duty vehicles and trucks morning rush hour SPtrans Urban buses, these incorporated uncertainties regarding the exact number of vehicles circulating. CET performs traffic counts to calibrate traffic simulations [42] in the mains routes
490 at MASP. Both simulations include a limited number of local streets as virtual links located at the centroid of each zone of origin-destination survey. These links represent real traffic over virtual links, therefore, provides an associated element of uncertainty. However, most of traffic occurs in mains streets, such as *motorways*, *trunks* and *primary*, therefore the uncertainty of virtual links
495 should be small for a emissions grid.

Traffic calibration using fuel sales resulted in consistent traffic flows regarding the origin of the data. This can be seen in the CO₂ emissions which resulted in $21 \cdot 10^6 \cdot \text{y}^{-1}$ in MASP using both scenarios. In the absence of complete GPS coverage, calibration according to fuel sales seems our most appropriate option,
500 especially with regard to CO₂ emissions which depends most directly on fuel consumption. There is a source of uncertainty in fuel consumption of diesel, because sales statistics [25] shows total diesel, without discriminating the fuel used only for automotive purpose. For instance, there are many electricity generators that consumes diesel. In addition, as trucks travel long distance for delivering
505 goods, fuel bought for trucks could consumed outside the study area adding uncertainty. We believe that the using the criteria of calibrating the vehicles that consumes diesel so that it represents the 85% of diesel sales is conservative, but

it is at the moment an assumption that we are applying until better information is available.

The emissions estimated were consistent in each region. The difference in MASP region for each pollutant presents differences associated with the speeds and amount of vehicles. As Table 4 shows, the VKM in MASP Method B is $2796 \cdot 10^{12} \cdot \text{y}^{-1}$, but in MASP Method A is $775 \cdot 10^{12} \cdot \text{y}^{-1}$, approximately 3.4 times lower. However, the emissions in MASP Method Method A are higher in pollutants emitted more for gasohol and ethanol vehicles. This emissions are due to lower speeds because emission factors are higher when lower the speeds as shown on Fig. 4, which speed variation comes from emission factors of European emission guidelines [24]. This highlights the importance of including kinematic parameters in the estimation of vehicular emissions. Regarding the emission factors, there are elements of uncertainty in the emission factors measurement. Brazilian emission factors of light-duty vehicles and motorcycle comes from dynamometer measurements [6] and it has been discovered that these emissions are not representative of real world emissions [43], in addition, car manufacturers incorporated software in the vehicles to cheat emission certification tests. In Brazil, the Institute of Natural Resources and Environment (IBAMA) fined Volkswagen with USD $15 \cdot 10^6$ after a tests using portable emissions measurements in Brazil made by the Environmental Company of São Paulo [44]. However, the diesel fleet of light-duty vehicles is small and the impacts on vehicular estimation may not be significant. These examples all strongly suggest that that Brazilian emission factors could be underestimated and highlight the need for a coordinated program of real world emissions measurements work in Brazil. In addition, there are uncertainty also in the deterioration factors used in this study, because they were calculated in Europe [24] and they may not fully represent Brazilian vehicular deterioration. Lastly, the emission factors in [6] are based on certification tests using the FTP-75 driving cycle. The factors are all-cycle values, independent of test phase, and it is known that, firstly, emissions vary significantly with driving conditions and environment, and, secondly, that cold start emissions can be very important, and they increase when

the temperature decrease [24].

540 There are other corrections that could improve the emission factors, such
as the incorporation of percentage of load in trucks and the effect of the road
gradient. This could be important in the streets that connect São Paulo and
Santos, because the load could be different in each trip. In addition, the road
545 gradient is likely to be significant because Santos is on the coast, whilst São
Paulo is over 760 meters above sea level. The streets with the highest gradients
are located near Cubatão, an industrial district between Santos and São Paulo,
and including this effect would change the atmospheric chemistry in simulations
at the interface between both cities.

We compared our inventory of MASP simulation and GPS Sorocaba, Camp-
550 inas, Santos and SJDC with the emissions of different cities in Latin America
shown on Table (5). The first comparison is between the official emissions in-
ventory for São Paulo, which uses a top-down approach with statistics of fleet
and representative speeds. In this case, the CO emissions are quite similar, our
estimate being only 10% higher, but differences for other pollutants are bigger,
555 for example, our CO₂ estimate is 50% higher.

The comparison with the official inventories for the other cities shows that
our emissions are higher in all cases. The difference in the emissions is that
our traffic flow was calibrated with fuel sales and also due the influence if the
speed in emission factor. The comparison between MASP and Rio de Janeiro
560 and Buenos Aires shows the estimates in those cities are higher, which could
be due to the fact the the base years are 2010 and 2006 respectively and the
circulating fleet had older technology allowing more emissions. Porto Alegre
emissions were also relatively high but here the estimate is based on the 2004
fleet. The comparison with Santiago seems to give reasonable estimates despite
565 that the fleet is older, however, the number of vehicles circulating in Santiago is
smaller because of the size of the city and road network. The comparison with
Manizales seems to be reasonable for most pollutants, except for CO which our
estimates are lower in most cities. The only city in which the HC emissions were
significant higher than NO_x was Manizales. This seems to relate to evaporative

Table 5: Comparison with vehicular emissions inventories in different cities ($t \cdot y^{-1}$)

City	PM	CO	NO _X	NMHC	CO ₂ · 10 ⁶	Reference
MASP, BR	2281	177406	73554	33999	21.05	*
MASP, BR	1484	162896	54334	34824	14.28	[6]
RJ, BR	2917	583667	68400	69689		[40]
Santos, BR	795	24814	15724	8138	2.43	*
Santos, BR	182	13497	6157	2628	1.38	[6]
Sorocaba, BR	574	24098	11770	7769	2.16	*
Sorocaba, BR	257	20203	8832	4070	1.9	[6]
SJDC, BR	533	26048	11661	8562	2.13	*
SJDC, BR	271	27406	10116	5287	2.4	[6]
Campinas, BR	2497	98073	51826	30871	9.14	*
Campinas, BR	377	34890	13851	7180	3.3	[6]
Porto Alegre, BR	2350	195740	34111	23450		[45]
Manizales, CO	800	43400	4900	9600	0.45	[46]
Santiago, CL	1275	199884	40126	16668	7.3	[47]
Buenos Aires, AR	6370	569000	81900	69800	11.5	[39]

*: This study

570 emissions estimations, which here incorporate local survey data on both the
distribution of trips and number of engine start-ups. The survey found that
there were typically 5 trips per day for light vehicles. By contrast, we adopted
a value of 4.5 taken from the literature. This small difference appears to have
a large impact on evaporative emissions estimations, suggesting that any new
575 evidence on this parameter could significantly enhance the robustness of the
emissions inventory for São Paulo.

5. Conclusions

This study investigated vehicular emissions in Southeastern Brazil using two
sources of traffic data 1): traffic flows using travel demand model outputs and 2)
580 a massive data set of GPS location of cars and trucks. The increased availability
of internet GPS traffic data provides us with the opportunity to use much more
representative measures of vehicle activity when developing new emissions in-
ventories. However, care must be taken when dealing with such data, especially
in obtaining representative speeds, due to the low frequency of consecutive GPS
585 readings of the same vehicle.

Arguably, at this stage traffic simulation provides the most straight-forward
and, perhaps even most reliable, option for sourcing traffic activity data, but
this is a rapidly evolving field, and work such as this highlights the potential
role, and associated challenges, for those seeking to make best use of local GPS
590 data in such work.

The calibration factors for travel demand models in Table 3 are closer to
one, meaning that the estimates of on-road fuel consumption derived from travel
demand model outputs are more representative. Therefore, we encourage city
planners to use travel demand model data when undertaking environmental
595 assessments of city projects.

Acknowledgments

The authors would like to thank CETESB, CET, ARTESP, CAPES Financial code 001 (program by the Ministry of Education, Brazil) and the Fundação da Universidade de São Paulo. The authors thank the program Becas Chile from CONICYT (Ministry of Education, Chile), scholarship Resolución Exenta N 9198/214. The authors also thank the support provided by the Northeast Institute of Geography and Agroecology, Chinese Academy of Sciences. These entities provided invaluable support to this study. 600

References

- [1] M. J. Molina, L. T. Molina, Megacities and atmospheric pollution, *Journal of the Air & Waste Management Association* 54 (6) (2004) 644–680. 605
- [2] IBGE, Ibge divulga as estimativas populacionais dos municípios em 2016, <http://cgp.cfa.org.br/ibge-divulga-as-estimativas-populacionais-dos-municipios-em-2016/>; accessed 09-August-2017 (2016). 610
- [3] M. d. F. Andrade, R. Y. Ynoue, E. D. Freitas, E. Todesco, A. Vara Vela, S. Ibarra, L. D. Martins, J. A. Martins, V. S. B. Carvalho, Air quality forecasting system for southeastern brazil, *Frontiers in Environmental Science* 3 (2015) 1–12. doi:10.3389/fenvs.2015.00009.
- [4] A. Vara-Vela, M. F. Andrade, P. Kumar, R. Y. Ynoue, A. G. Muñoz, Impact of vehicular emissions on the formation of fine particles in the são paulo metropolitan area: a numerical study with the wrf-chem model, *Atmos. Chem. and Phys.* 16 (2016) 777–797. doi:10.5194/acp-16-777-2016. 615
- [5] G. Hoshyaripour, G. Brasseur, M. d. F. Andrade, M. Gavidia-Calderón, I. Bouarar, R. Y. Ynoue, Prediction of ground-level ozone concentration in são paulo, brazil: deterministic versus statistic models, *Atmospheric environment* 145 (2016) 365–375. 620

- [6] CETESB, Emissões veiculares no estado de são paulo 2014, <http://veicular.cetesb.sp.gov.br/relatorios-e-publicacoes/> (2015).
- 625 [7] R. M. Corvalán, M. Osses, C. M. Urrutia, Hot emission model for mobile sources: application to the metropolitan region of the city of santiago, chile, *Journal of the Air & Waste Management Association* 52 (2) (2002) 167–174.
- [8] L. I. Panis, S. Broekx, R. Liu, Modelling instantaneous traffic emission
630 and the influence of traffic speed limits, *Science of the total environment* 371 (1-3) (2006) 270–285.
- [9] M. Nyhan, S. Sobolevsky, C. Kang, P. Robinson, A. Corti, M. Szell, D. Streets, Z. Lu, R. Britter, S. R. Barrett, et al., Predicting vehicular emissions in high spatial resolution using pervasively measured transportation data and microscopic emissions model, *Atmospheric environment* 140
635 (2016) 352–363.
- [10] E. Kinnee, J. Touma, R. Mason, J. Thurman, A. Beidler, C. Bailey, R. Cook, Allocation of onroad mobile emissions to road segments for air toxics modeling in an urban area, *Transportation Research Part D: Transport and Environment* 9 (2) (2004) 139 – 150.
640 doi:<http://dx.doi.org/10.1016/j.trd.2003.09.003>.
URL <http://www.sciencedirect.com/science/article/pii/S1361920903000877>
- [11] C. Gómez, C. González, M. Osses, B. Aristizábal, Spatial and temporal
645 disaggregation of the on-road vehicle emission inventory in a medium-sized andean city. comparison of gis-based top-down methodologies, *Atmospheric environment* 179 (2018) 142–155.
- [12] S. A. A. Rafee, L. D. Martins, A. B. Kawashima, D. S. Almeida, M. V. B. Morais, R. V. A. Souza, M. B. L. Oliveira, R. A. F. Souza, A. S. S. Medeiros, V. Urbina, E. D. Freitas, S. T. Martin, J. A. Martins, Mo-
650 bile and stationary sources of air pollutants in the amazon rainforest: a

numerical study with wrf-chem model, *Atmos. Chem. and Phys.* (2017) 1–35 doi:10.5194/acp-2016-1190.

URL <http://www.atmos-chem-phys-discuss.net/acp-2016-1190/>

- [13] C. K. Gately, L. R. Hutyra, S. Peterson, I. S. Wing, Urban emissions hotspots: Quantifying vehicle congestion and air pollution using mobile phone gps data, *Environmental pollution* 229 (2017) 496–504. 655
- [14] D. Yang, S. Zhang, T. Niu, Y. Wang, H. Xu, K. M. Zhang, Y. Wu, High-resolution mapping of vehicle emissions of atmospheric pollutants based on large-scale, real-world traffic datasets, *Atmospheric Chemistry and Physics* 19 (13) (2019) 8831–8843. 660
- [15] S. Ibarra-Espinosa, R. Ynoue, M. Giannotti, K. Ropkins, E. D. de Freitas, Generating traffic flow and speed regional model data using internet gps vehicle records, *MethodsX* 6 (2019) 2065 – 2075. doi:<https://doi.org/10.1016/j.mex.2019.08.018>. 665
- [16] S. Ibarra-Espinosa, R. Ynoue, S. O’Sullivan, E. Pebesma, M. D. F. Andrade, M. Osses, Vein v0.2.2: an r package for bottom-up vehicular emissions inventories, *Geoscientific Model Development* 11 (6) (2018) 2209–2229. doi:10.5194/gmd-11-2209-2018. 670
URL <https://www.geosci-model-dev.net/11/2209/2018/>
- [17] S. Ibarra-Espinosa, D. Schuch, vein: Vehicular Emissions Inventories, r package version 0.7.4 (2019).
URL <https://atmoschem.github.io/vein/>
- [18] OpenStreetMap contributors, Planet dump retrieved from <https://planet.osm.org> , <https://www.openstreetmap.org> (2017). 675
- [19] QGIS Development Team, QGIS Geographic Information System, Open Source Geospatial Foundation (2017).
URL <http://qgis.osgeo.org>

- [20] Metro, Pesquisa origem e destino, accessed on 10-08-2017 (2017).
680 URL "https://transparencia.metrosp.com.br/dataset/
pesquisa-origem-e-destino"
- [21] J. d. D. Ortuzar, L. G. Willumsen, Modelling transport, Vol. 3, Wiley,
2002.
- [22] ANFAVEA, Estatísticas produção, vendas e exportação de autoveículos,
685 <http://www.anfavea.com.br/estatisticas.html> (2014).
- [23] ABRACICLO, Anuario 2014, <http://www.abraciclo.com.br/> (2014).
- [24] L. Ntziachristos, Z. Samaras, Emep/eea emission inventory guidebook; road
transport: Passenger cars, light commercial trucks, heavy-duty vehicles
including buses and motorcycles, European Environment Agency, Copen-
690 hagen.
- [25] S. de Energia Electrica, Anuario estatístico de energéticos por município
no estado de são paulo 2014, Tech. rep., Governo do Estado de São Paulo
(2014).
- [26] A. Salvo, F. M. Geiger, Reduction in local ozone levels in urban são paulo
695 due to a shift from ethanol to gasoline use, *Nature Geoscience* 7 (6) (2014)
450.
- [27] D. Alvim, L. Gatti, S. Correa, J. Chiquetto, G. Santos,
C. de Souza Rossatti, A. Pretto, J. Rozante, S. Figueroa, J. Pend-
harkar, P. Nobre, Determining vocs reactivity for ozone forming potential
700 in the megacity of são paulo, *Aerosol and Air Quality Research* 18.
[doi:10.4209/aaqr.2017.10.0361](https://doi.org/10.4209/aaqr.2017.10.0361).
- [28] M. Andrade, P. Kumar, E. Freitas, R. Ynoue, J. Martins, L. Martins,
T. Nogueira, P. Perez-Martinez, R. Maura de Miranda, T. Albuquerque,
F. Gonçalves, B. Oyama, Y. Zhang, Air quality in the megacity of são paulo:
705 Evolution over the last 30 years and future perspectives, *Atmospheric En-
vironment In Press*. [doi:10.1016/j.atmosenv.2017.03.051](https://doi.org/10.1016/j.atmosenv.2017.03.051).

- [29] N. Davis, J. Lents, M. Osses, N. Nikkila, M. Barth, Part 3: Developing countries: development and application of an international vehicle emissions model, *Transportation Research Record: Journal of the Transportation Research Board* 8 (1939) (2005) 155–165. 710
- [30] S. Ibarra-Espinosa, D. Schuch, eixport: Exporting emissions, r package version 0.2.10 (2017).
URL <https://github.com/ibarraespinosa/eixport>
- [31] T. Barlow, S. Latham, I. McCrae, P. Boulter, A reference book of driving cycles for use in the measurement of road vehicle emissions, TRL Published Project Report. 715
- [32] Dieselnet, European Stationary Cycle (ESC), ECOpoint Inc. (2017).
URL <https://www.dieselnet.com/standards/cycles/esc.php>
- [33] M. de Medio Ambiente, Air pollution control program by motor vehicles; proconve/promot, http://www.ibama.gov.br/phocadownload/veiculosautomotoresmanual%20proconve%20promot_english.pdf, accessed: 2017-10-17 (2011). 720
- [34] G. Mellios, L. Ntziachristos, Emep/eea emission inventory guidebook; gasoline evaporation from vehicles, Tech. rep., European Environment Agency, Copenhagen (2016). 725
- [35] Y. Wu, S. Zhang, J. Hao, H. Liu, X. Wu, J. Hu, M. P. Walsh, T. J. Wallington, K. M. Zhang, S. Stevanovic, On-road vehicle emissions and their control in china: A review and outlook, *Science of the Total Environment* 574 (2017) 332–349.
- [36] A. D. C. Bruni, M. P. Bales, Curvas de intensidade de uso por tipo de veículo automotor da frota da cidade de são paulo, Tech. rep., CETESB, <http://veicular.cetesb.sp.gov.br/wp-content/uploads/sites/35/2013/12/curvas-intensidade-uso-veiculos-automotores-cidade-sao-paulo.pdf> (2013). 730

- 735 [37] Bureau of Transportation Statistics, Daily passenger travel, Tech. rep. (2017).
URL https://www.rita.dot.gov/bts/sites/rita.dot.gov.bts/files/publications/highlights_of_the_2001_national_household_travel_survey/html/section_02.html
- 740 [38] A. D'Angiola, L. E. Dawidowski, D. R. Gómez, M. Osses, On-road traffic emissions in a megacity, *Atmospheric Environment* 44 (4) (2010) 483–493.
- [39] A. D'Angiola, L. E. Dawidowski, D. R. Gómez, M. Osses, On-road traffic emissions in a megacity, *Atmospheric Environment* 44 (4) (2010) 483 – 493. doi:<https://doi.org/10.1016/j.atmosenv.2009.11.004>.
- 745 URL <http://www.sciencedirect.com/science/article/pii/S1352231009009352>
- [40] C. D. R. de Souza, S. D. Silva, M. A. V. da Silva, D. Márcio de Almeida, A. P. Barboza, Inventory of conventional air pollutants emissions from road transportation for the state of rio de janeiro, *Energy Policy* 53 (2013) 125–
- 750 135.
- [41] P. C. de Macedo, D. de Moraes Gomes, E. A. Pereira, M. B. Veloso, Air Pollution Control Program by Motor Vehicles, 3rd Edition, Vol. 3, Brazilian Institute of Environment and Renewable Natural Resources (IBAMA), Brasília, Brazil, 2011.
- 755 [42] S. Ibarra-Espinosa, Traffic counts both ways cet 2012 sao paulo, Tech. rep., Medeley Data, accessed on 10-08-2017 (2017). doi: "10.17632/rz2cymv6c2.1".
URL "http://dx.doi.org/10.17632/rz2cymv6c2.1"
- [43] L. Pelkmans, P. Debal, Comparison of on-road emissions with emissions measured on chassis dynamometer test cycles, *Transportation Research Part D: Transport and Environment* 11 (4) (2006) 233–241.
- 760

- [44] IBAMA, Ibama confirma multa de R 50 milhoes por fraude em testes de emissao e exige recall da Volkswagen (2017).
URL <http://www.ibama.gov.br/noticias/422-2017/1032-ibama-confirma-multa-de-r-50-milhoes-por-fraude-em-testes-de-emissao-e-exige-recall-da-volkswagen>
- [45] E. C. Teixeira, S. Feltes, E. R. R. d. Santana, Estudo das emissões de fontes móveis na região metropolitana de porto alegre, rio grande do sul, Química Nova 31 (2) (2008) 244–248.
- [46] C. González, C. Gómez, N. Rojas, H. Acevedo, B. Aristizábal, Relative impact of on-road vehicular and point-source industrial emissions of air pollutants in a medium-sized andean city, Atmospheric Environment 152 (2017) 279–289. 770
- [47] J. Escobar, et al., Actualización del inventario de emisiones de contaminantes atmosféricos en la región metropolitana 2005, DICTUC, Pontificia Universidad Católica de Chile. Santiago: Comisión Nacional Del Medio Ambiente Región Metropolitana. 775