

This is a repository copy of *Mixed Criticality on Multi-cores Accounting for Resource Stress and Resource Sensitivity*.

White Rose Research Online URL for this paper: https://eprints.whiterose.ac.uk/id/eprint/188036/

Version: Accepted Version

Proceedings Paper:

Davis, Robert Ian orcid.org/0000-0002-5772-0928 and Bate, Iain orcid.org/0000-0003-2415-8219 (2022) Mixed Criticality on Multi-cores Accounting for Resource Stress and Resource Sensitivity. In: Abdeddaïm, Yasmina, Cucu-Grosjean, Liliana, Nelissen, Geoffrey and Pautet, Laurent, (eds.) RTNS 2022 - Proceedings of the 30th International Conference on Real-Time Networks and Systems. 30th International Conference on Real-Time Networks and Systems, RTNS 2022, 07-08 Jun 2022 ACM International Conference Proceeding Series. ACM, FRA, pp. 103-115.

https://doi.org/10.1145/3534879.3534883

Reuse

Items deposited in White Rose Research Online are protected by copyright, with all rights reserved unless indicated otherwise. They may be downloaded and/or printed for private study, or other acts as permitted by national copyright laws. The publisher or other rights holders may allow further reproduction and re-use of the full text version. This is indicated by the licence information on the White Rose Research Online record for the item.

Takedown

If you consider content in White Rose Research Online to be in breach of UK law, please notify us by emailing eprints@whiterose.ac.uk including the URL of the record and the reason for the withdrawal request.



Mixed Criticality on Multi-cores Accounting for Resource Stress and Resource Sensitivity

Robert I. Davis

rob.davis@york.ac.uk Department of Computer Science, University of York York, UK

ABSTRACT

10

11

12

15

17

18

19

20

21

22

23

24

25

27

28

29

30

31

32

33

34

35

36

37

42

43

44

45

47

48

49

50

51

55

56

57

58

The most significant trend in real-time systems design in recent years has been the adoption of multi-core processors and the accompanying integration of functionality with different criticality levels onto the same hardware platform. This paper integrates mixed criticality aspects and assurances within a multi-core system model. It bounds cross-core contention and interference by considering the impact on task execution times due to the stress on shared hardware resources caused by co-runners, and each task's sensitivity to that resource stress. Schedulability analysis is derived for four mixed criticality scheduling schemes based on partitioned fixed priority preemptive scheduling. Each scheme provides robust timing guarantees for high criticality tasks, ensuring that their timing constraints cannot be jeopardized by the behavior or misbehavior of low criticality tasks.

CCS CONCEPTS

• Computer systems organization → Real-time systems; Real-time systems; • Software and its engineering -> Real-time schedulability; Real-time schedulability.

KEYWORDS

real-time, multi-core, mixed criticality, fixed priority, schedulability analysis, cross-core contention, interference

ACM Reference Format:

Robert I. Davis and Iain Bate. 2022. Mixed Criticality on Multi-cores Accounting for Resource Stress and Resource Sensitivity. In Proceedings of the 30th International Conference on Real-Time Networks and Systems (RTNS '22), June 7-8, 2022, Paris, France. ACM, New York, NY, USA, 13 pages. https://doi.org/10.1145/3534879.3534883

1 INTRODUCTION

The most significant trend in real-time systems design in recent years has been the migration from using single-core to multi-core processors [1, 2] and the accompanying integration of functionality of different criticality levels onto the same hardware platform, i.e. the advent of mixed criticality systems [65].

Permission to make digital or hard copies of all or part of this work for personal or classroom use is granted without fee provided that copies are not made or distributed for profit or commercial advantage and that copies bear this notice and the full citation on the first page. Copyrights for components of this work owned by others than ACM must be honored. Abstracting with credit is permitted. To copy otherwise, or republish, to post on servers or to redistribute to lists, requires prior specific permission and/or a $fee.\ Request\ permissions\ from\ permissions@acm.org.$

RTNS '22, June 7-8, 2022, Paris, France

© 2022 Association for Computing Machinery. ACM ISBN 978-1-4503-9650-9/22/06...\$15.00

https://doi.org/10.1145/3534879.3534883

Iain Bate

61

67

68

69

70

71

72

73

74

75

76

80

81

82

83

86

87

88

89

90

93

94

95

96

100

101

102

103

104

105

106

107

108

109

110

111

112

113

114

115

116

iain.bate@york.ac.uk Department of Computer Science, University of York York, UK

In mixed criticality systems, the main challenge is to provide appropriate levels of assurance, such as timing guarantees, to software tasks that have different levels of criticality. Crucially, this needs to be done without having to treat all of the tasks as having the highest level of criticality, with the attendant increase in verification costs and reduction in usable system capacity that would entail. In multi-core systems, the main challenge is to bound and correctly account for the effects of cross-core contention over shared hardware resources, due to tasks running on different cores, and the impact that has on task response times and consequently on system schedulability.

In this paper, we consider mixed criticality multi-core systems with two criticality levels. More specifically, HI- and LO-criticality tasks running on a multi-core processor that are subject to crosscore contention and interference over shared hardware resources. In this context, HI-criticality tasks must be afforded robust timing guarantees, such that their timing constraints cannot be jeopardized by the behavior or misbehavior of LO-criticality tasks running on either the same or different cores. Following Vestal's model [65], LOcriticality tasks have a single low assurance estimate of their standalone Worst-Case Execution Time (WCET), whereas HI-criticality tasks have two such estimates; one low assurance estimate and a larger high assurance estimate that may, for example, include provision for error handling code that is not expected to execute during normal operation [50].

Multi-core processors typically share hardware resources, such as the interconnect and the memory hierarchy, between cores. Unfortunately, a consequence of these hardware design decisions is that the execution time of a task running on one core can be impacted by co-running tasks on other cores contending with it for access to shared hardware resources. This increase in execution time is referred to as interference.

Work on micro-benchmarks [36, 44, 56, 60, 61] has sort to characterize the maximum amount of interference that a task can be subject to, assuming a given multi-core hardware configuration. Further research on the Multi-core Resource Stress and Sensitivity (MRSS) task model [30, 31] takes this idea a step further, aiming to bound the total amount of interference that can occur from two different perspectives by employing additional task parameters:

- (1) The Resource Sensitivity of a task characterizes the maximum increase in its execution time that can occur due to contention over a specific resource emanating from any possible co-runner.
- (2) The Resource Stress of a task characterizes the maximum increase in the execution time of any possible co-runner due to contention over a resource emanating from the task.

The resource sensitivity and resource stress parameters of a task characterize, in a simple but useful way, the impact on that task's execution time of contention over the resource and the behavior of the arbitration policy in controlling access to it. See [30, 31] for a discussion of how the resource sensitivity and resource stress parameters can be obtained.

By combining measures of resource stress and resource sensitivity, analysis of the MRSS task model can more accurately bound the amount of interference that can actually occur. The MRSS task model retains the advantages of the two-step approach that is traditionally employed on single-core systems, providing a separation of concerns between timing analysis and schedulability analysis, and has been validated via a proof-of-concept case study on multi-core hardware [30, 31].

This paper builds on the MRSS task model and its schedulability analysis for partitioned fixed priority preemptive scheduling on multi-core systems. The main contribution of this work is the integration of mixed criticality and multi-core in the form of the MRSS task model, along with the derivation of schedulability analysis for four mixed criticality scheduling schemes.

The remainder of the paper is organized as follows: Section 2 discusses related work. Section 3 introduces the system model, terminology, and notation used. Section 4 presents schedulability analysis for the four mixed criticality schemes studied, with a systematic evaluation of their performance given in Section 5. Finally, Section 6 concludes with a summary.

2 RELATED WORK

In this section, we outline prior work on: (i) mixed criticality fixed priority scheduling schemes for single-core processors, since those schemes form the basis for partitioned multi-core systems; (ii) mixed criticality systems on multi-cores that seeks to enforce limits on the amount of cross-core contention and interference that can occur; and (iii) single criticality multi-core systems that integrate interference effects into schedulability analysis.

Since Vestal's seminal paper [65] in 2007, mixed criticality systems have become a hot topic of real-time systems research, see [20, 21] for a survey and a more recent review. Many of these papers focus on scheduling schemes that are based on fixed priorities, most notably Static Mixed Criticality (SMC) [11] and Adaptive Mixed Criticality (AMC) [12]. AMC is considered the most effective fixed priority scheme [43] for single cores, and has been extended to account for many additional aspects including: preemption thresholds [68, 69], multiple criticality levels [37], criticality-specific task periods [13], changes in priority [10], communications [18], deferred preemption [19], a fast return to LO-criticality behavior [15, 16], weakly-hard constraints [38], probabilistic task models [54], design optimization [71], context switch costs [28], robustness and resilience [23], implementation overheads [51], semi-clairvoyant timing behavior [22, 70]. An exact analysis for AMC has also been developed for periodic task sets with offsets [6, 58]. Finally, a modified AMCR runtime protocol [17] has been developed that delays the onset of degraded behaviour where LO-criticality jobs are dropped.

The first work to discuss mixed criticality within the context of multi-core systems was by Anderson et al. [4, 55], with later work in this area addressing overheads [26, 42], showing the advantages of using different partitioning and isolation techniques at different criticality levels [47], and reconciling issues of data sharing [25] and simultaneous multithreading [9].

In the context of multi-core systems, much of the prior work on mixed criticality has sort to limit the amount of interference that can occur. To achieve this, criticality-based partitioning is typically assumed, with HI-criticality tasks allocated on one core, and LO-criticality tasks to other cores. Here, one way of limiting interference is to monitor the execution time of each HI-criticality task and to abort co-running LO-criticality tasks when no more interference can be tolerated [48]. A more subtle approach is to throttle the resource access bandwidth available to the LO-criticality cores, temporarily suspending execution on those cores whenever the maximum permitted number of accesses in a given period has been reached [67].

Research into the timing analysis and schedulability analysis of multi-core systems has also become a hot topic of real-time systems research over the past 15 years, see [53] for a survey. Of specific interest here is the integration of interference effects into schedulability analysis.

Early work in this area [63] used arrival curves to model the memory bus accesses of each task, and how delays due to contention impact task response times. Subsequently, more detailed analysis [39, 49, 59, 64] divided each task into a sequence of blocks and used information about the number of accesses within each block to provide more refined results. Further work [57] proposed using a WCET-matrix and WCET-sensitivity values to characterize the variation in task execution times for different numbers of contending cores. A later more detailed analysis [5] considered different execution times dependent on specific co-runners, but suffered from significant scalability issues.

An alternative approach [27] used request functions to model the maximum number of resource accesses from each task in a given time interval, and integrated this request function into response time analysis. Further work [46, 66] along this line provided detailed analysis of the contention caused by memory accesses, accounting for variations in latencies due to different memory states.

Subsequently, the Multi-core Response Time Analysis (MRTA) framework [3, 29] was introduced, aimed at combining the demands that tasks place on difference types of shared resources with the resource supply provided by those resources, and integrating the resulting explicit interference directly into response time analysis. This framework was later built upon to analyze bus arbitration policies on a many-core processor [62]. Further, the symmetry between processing and resource access has been leveraged to derive a suspension-based schedulability analysis [24], with similar performance to MRTA.

3 SYSTEM MODEL

In this paper, we assume a mixed criticality multi-core system with m homogeneous cores that executes tasks under various scheduling schemes, based on partitioned fixed priority preemptive scheduling.

With partitioning, tasks are assigned to a specific core and do not migrate from one core to another.

The mixed criticality system is assumed to have two criticality levels: HI and LO. Each task τ_i is characterised by its criticality level L_i , which is either HI or LO. Each LO-criticality task τ_j has a single estimate $C_j(LO)$ of its WCET when executing stand-alone. By contrast, each HI-criticality task τ_k has two estimates $C_k(LO)$ and $C_k(HI)$ of its WCET when executing stand-alone, where $C_k(HI) \geq C_k(LO)$. (Note for ease of presentation of the analysis in Section 4, we assume that $C_j(HI) = C_j(LO)$ for LO-criticality tasks). Each task τ_i has a minimum inter-arrival time or period T_i between releases of its jobs, and a constrained relative deadline D_i , where $D_i \leq T_i$.

Each task τ_i is assumed to have a priority that is unique across all cores, with hp(i) used to denote the set of tasks with higher priority than task τ_i . The priorities of tasks are unrelated to their criticality levels. The notation Γ_X is used to denote the set of tasks that execute on the same core, with index x, as the task of interest τ_i . Similarly, Γ_y is used to denote the set of tasks that execute on a different core with index y.

The tasks are assumed to be independent, but may access a set of shared hardware resources $r \in H$, thus causing interference on the execution of tasks on other cores via cross-core contention.

Further aspects of the model are based on the concept of resource sensitive contenders and resource stressing contenders [30, 31].

A resource stressing contender maximizes the stress on a resource r by repeatedly making accesses to it that cause the most contention. Running a resource stressing contender in parallel with a task creates the maximum increase in execution time for the task due to contention over resource r emanating from any single co-runner.

A resource sensitive contender for a resource r suffers the maximum possible interference by repeatedly making accesses to the resource that suffer the most contention. Running a resource sensitive contender in parallel with a task creates the maximum increase in execution time for any single co-running contender due to contention over resource r emanating from the task.

Each task τ_i is characterised by its resource sensitivity X_i^r and its resource stress Y_i^r for each shared hardware resource $r \in H$. X_i^r captures the maximum increase in execution time of task τ_i (from C_i to $C_i + X_i^r$) when it is executed in parallel with a resource stressing contender for resource r. Thus X_i^r models how much task τ_i behaves like a resource sensitive contender. Similarly, Y_i^r captures the increase in execution time of a resource sensitive contender for resource r, when it is executed in parallel with task τ_i . Hence Y_i^r models how much task τ_i behaves like a resource stressing contender. With this model, the execution time of a task τ_i running on one core, subject to interference via shared hardware resource r from a single task τ_k running in parallel on one other core, is increased by at most $\min(X_i^r, Y_k^r)$ i.e. from C_i to $C_i + \min(X_i^r, Y_k^r)$. Assuming the worst-case stress on resource r emanating from any arbitrary tasks on m-1 other cores, the execution time of task τ_i is increased from C_i to at most $C_i + (m-1)X_i^r$. Finally, the multicore system is assumed to be symmetrical, and so the cross-core contention between two tasks over a resource does not depend on the two specific cores on which those tasks run.

We do not assume dual values¹ for resource sensitivity X_i^r and resource stress Y_i^r based on criticality. For a LO-criticality task, these values reflect its LO-criticality execution behavior, but cannot impact the guarantees afforded to HI-criticality tasks under the analysis described in this paper. For a HI-criticality task the values reflect its worst-case i.e. HI-criticality execution behavior.

The Real-Time Operating System (RTOS) is required to provide standard per task execution time monitoring and budget enforcement facilities. The RTOS is assumed to abort any job of a task τ_i that does not complete within its execution time budget $B_i(L_i)$. This budget is set to $C_i(L_i) + \sum_{r \in H} (m-1)X_i^r$, where H is the set of shared hardware resources, m is the number of cores, and L_i is the criticality level of the task. The budget $B_i(L_i)$ thus accounts for the WCET of the task when faced with the worst-case stress on every resource r, from any arbitrary tasks on all of the other m-1 cores. Assuming that the parameters $C_i(L_i)$ and X_i^r represent sound upper bounds, then budget enforcement will only occur if the task itself executes erroneously. (Note, no enforcement is assumed on the number of accesses that can be made to shared hardware resources).

The schedulability tests introduced in this paper are named using the following convention: **CpSched-m-X-MCS**, where **C** indicates a contention-based test for **p** partitioned scheduling, using the basic scheduling policy **Sched**, which is **FPPS**. The test is for *m* cores, makes use of information *X*, which is either **D** or **R** meaning the deadlines or the response times of the tasks on other cores, or **fc** meaning fully composable, i.e. the test does not rely on any information about the tasks running on the other cores, or **no** meaning no effects of contention are included. Finally, **MCS** is the mixed criticality scheme employed, which is either **NMC**, **SMC**, **AMC**, or **AMCR**, as described in Section 4. This naming convention builds on that introduced in [30, 31] for schedulability tests compatible with the MRSS task model.

4 SCHEDULING SCHEMES AND ANALYSES

In this section, we derive schedulability analysis for partitioned fixed priority preemptive scheduling of mixed criticality systems on multi-cores, under four different mixed criticality scheduling schemes, in each case accounting for cross-core contention and interference, according to the MRSS task model.

Most scheduling schemes for mixed criticality systems identify two distinct modes of behavior. A *normal* or *LO*-criticality mode, which comprises the expected behavior of the system, and an *abnormal* or *HI*-criticality mode, which is expected to be rarely if ever entered as a consequence of the runtime behavior of *HI*-criticality tasks.

There are disparate views within the real-time systems community as to the timing requirements for mixed criticality systems [20], while most works assume that *LO*-criticality tasks do not have to meet their deadlines in abnormal mode, and can potentially be dropped, others [34, 35] argue that this represents a disconnect with respect to industry practice and standards. The argument against missing deadlines and job dropping is that

¹In this first paper combining mixed criticality and the MRSS model, we choose not to use dual values so as to simplify the overall model and analyses. Models and analyses for mode specific resource sensitivity and resource stress are left for future work).

criticality is not synonymous with importance, and thus the functionality of LO-criticality tasks cannot simply be discarded. In this section, we derive analyses for different schemes that reflect these different viewpoints. Four schemes are considered:

- No Mixed Criticality (NMC): Assumes that jobs of all tasks are required to meet their deadlines in both normal and abnormal modes. Under NMC no runtime mode change operations are required. NMC provides a baseline for systems where missing deadlines or dropping jobs is not acceptable even for LO-criticality tasks.
- Static Mixed Criticality (SMC) [11]: Assumes that jobs of LO-criticality tasks continue to execute and to be released in abnormal mode, but are not required to meet their deadlines in that mode. Under SMC no runtime mode change operations are required.
- 3. Adaptive Mixed Criticality (AMC) [12]: Assumes that no new jobs of *LO*-criticality tasks are released in abnormal mode, and that any previously released jobs of *LO*-criticality tasks are not required to meet their deadlines in that mode. With AMC, the RTOS is responsible for runtime mode change operations, and for ensuring that *LO*-criticality tasks do not release new jobs in abnormal mode.
- 4. Adaptive Mixed Criticality with modified runtime protocol (AMCR) [17]: AMCR is similar to AMC, but uses a modified runtime protocol that delays the time at which LO-criticality tasks stop releasing new jobs in abnormal mode, see Section 4.4 for details.

In this paper, we assume that each core is considered separately and independently in terms of the runtime mode change operations performed by the RTOS; however, in contrast the timing requirements placed upon the tasks are defined by the overall system behavior, with different levels of timing assurance required for *HI*- and *LO*-criticality tasks as follows:

- R1 LO-criticality tasks require assurance that they will meet their timing constraints (deadlines) under *normal* system behavior, i.e. under the condition that *all* tasks on *all* cores comply with their LO-criticality execution time $C_i(LO)$, resource sensitivity X_i^r , and resource stress Y_i^r parameters.
- R2 HI-criticality tasks require more robust assurance that they will meet their timing constraints at all times (irrespective of the behavior or misbehavior of other tasks) i.e. subject only to the condition that they comply with their own HI-criticality execution time $C_i(HI)$ and resource sensitivity X_i^r parameters.

4.1 No Mixed Criticality (NMC)

In this section, we build upon the schedulability analysis for the MRSS task model given in [30, 31], making use of the context-dependent schedulability tests for *LO*-criticality tasks, and the fully composable context-independent schedulability test for *HI*-criticality tasks, see Sections 3.1 and 3.3 of [30] respectively.

Adding cross-core interference considering each resource $r \in H$ to the standard response time analysis [8, 45] for fixed priority preemptive scheduling, we can compute the worst-case response

time for mixed criticality tasks under the NMC scheme as follows:

$$R_{i}(L_{i}) = C_{i}(L_{i}) + \sum_{j \in \Gamma_{x} \land j \in hp(i)} \left[\frac{R_{i}(L_{i})}{T_{j}} \right] C_{j}(L_{j})$$

$$+ \sum_{r \in H} I_{i}^{r}(R_{i}(L_{i}))$$

$$(1)$$

where $I_i^r(R_i(L_i))$ is an upper bound on the interference that may occur within the response time of task τ_i , via shared hardware resource r, due to tasks executing on the other cores.

The interference term $I_i^r(R_i(L_i))$ depends on: (i) the total resource sensitivity for resource r, denoted by $S_i^r(R_i(L_i), x)$, for the tasks executing on the same core x as task τ_i within its response time $R_i(L_i)$; and (ii) the total resource stress on resource r, denoted by $E_i^r(R_i(L_i), y)$, that can be produced by tasks executing on each of the other cores y within an interval of length $R_i(L_i)$.

$$I_{i}^{r}(R_{i}(L_{i})) = \sum_{\forall y \neq x} \min(E_{i}^{r}(R_{i}(L_{i}), y), S_{i}^{r}(R_{i}(L_{i}), x))$$
 (2)

This is the case, since the maximum interference due to contention from each core y cannot exceed the total resource stress $E_i^r(R_i(L_i), y)$ from that core within an interval of length $R_i(L_i)$.

The total resource sensitivity $S_i^r(R_i(L_i), x)$ is computed based on the jobs that may execute on the same core x within the worst-case response time of task τ_i , thus we have²:

$$S_i^r(R_i(L_i), x) = X_i^r + \sum_{j \in \Gamma_X \land j \in \text{hp}(i)} \left[\frac{R_i(L_i)}{T_j} \right] X_j^r$$
 (3)

The total resource stress $E_i^r(R_i(L_i), y)$ due to tasks that execute on another core y in the interval $R_i(L_i)$ can be upper bounded in three different ways.

When analysing a HI-criticality task τ_i , the total resource stress $E_i^r(R_i(L_i), y)$ is assumed to be infinite, and hence the schedulability test for that task becomes context-independent and fully composable, since the computed response time is unaffected by any changes to the parameters of the tasks that execute on the other cores. In other words, when (4) is used, (1), (2), and (3) become dependent only on the set of tasks executing on the same core as τ_i .

$$E_i^r(R_i(L_i), y) = \infty (4)$$

When analysing a *LO*-criticality task τ_i , the total resource stress $E_i^r(R_i(L_i), y)$ can be upper bounded in two ways, making use of either the deadlines or the response times of the contending tasks that execute on the other cores:

$$E_i^r(R_i(L_i), y) = \sum_{i \in \Gamma_n} \left[\frac{R_i(L_i) + D_j}{T_j} \right] Y_j^r \tag{5}$$

$$E_i^r(R_i(L_i), y) = \sum_{j \in \Gamma_u} \left[\frac{R_i(L_i) + R_j(L_j)}{T_j} \right] Y_j^r$$
 (6)

Here, the upper bound on the worst case does not correspond to synchronous release of the contending tasks at the start of the interval $R_i(L_i)$, but rather to a scenario where the first job of a contending task executes as late as possible within its own period

²Note, for systems where memory accesses issued by a preempted lower priority task on the same core may be still pending after a context switch, then the analysis needs to also include such additional accesses.

(i.e. assumed in (5) to be just before its deadline, and assumed in (6) to be just before its response time) and then further jobs of that task execute as early as possible in their subsequent periods. Further, for the purposes of ensuring a correct upper bound, resource stress from each contending job is assumed to be able to occur instantaneously. This leads to a sound, but potentially somewhat pessimistic upper bound $E_i^r(R_i(L_i), y)$. However, to provide a tighter bound would require highly detailed information about the timing of resource accesses within each task. Note that tasks of any priority can cause contention when executing on the other cores.

 Bounding the total resource stress $E_i^r(R_i(L_i), y)$ via (5) or (6) results in a context-dependent schedulability test for LO-criticality task τ_i , since schedulability of the task is dependent on the parameters of the contending tasks that execute on the other cores. Using (6), the response times of the LO-criticality tasks on the same and different cores become interdependent; however, schedulability can still be determined via fixed point iteration. In this case, an outer iteration starts with $R_j(L_j) = C_j(L_j)$ for every task τ_j in the system, and repeatedly computes the response times for all tasks on all cores. This is done using the $R_j(L_j)$ values in the right hand side of (6) from the previous round, until all response times either converge, in other words are unchanged from the previous round, or one of them exceeds the associated deadline.

The correctness of the context-dependent schedulability test [30, 31], embodied in (1), (2), (3) and either (4) or (5), is sufficient to ensure compliance with the timing assurance requirement $\mathbf{R1}$ for LO-criticality tasks. In fact the test provides a stronger guarantee, ensuring that LO-criticality tasks are schedulable provided that all HI-criticality tasks comply with their HI-criticality stand-alone execution times $C_i(HI)$, rather than their LO-criticality stand-alone execution times $C_i(LO)$ as required by $\mathbf{R1}$. However, all tasks must still comply with their resource sensitivity X_i^r , and resource stress Y_i^r parameters for the guarantee to hold.

We now show that the requirement R2 for robust timing assurance of HI-criticality tasks is also met. Each HI-criticality task τ_i is analysed using the fully composable context-independent schedulability test, comprising (1), (2), (3), and (4). This test effectively assumes that the contribution to the response time of task τ_i from each job of another task τ_k that executes on the same core is bounded by $B_k(L_k) = C_k(L_k) + \sum_{r \in H} (m-1)X_k^r$, (see Section 3 for details of how $B_k(L_k)$ is defined and why this is a valid bound). If a job of task τ_k has not completed after executing for a time $B_k(L_k)$ due to internal overrun of its own code, or extra interference resulting from a higher than expected level of resource sensitivity, then the RTOS will prevent the job of task τ_k from continuing to execute. Hence the RTOS prevents other tasks that execute on the same core within the response time of *HI*-criticality task τ_i from compromising its timing constraints. Since the fully composable schedulability test considers the maximum possible interference of $\sum_{r \in H} (m-1)X_i^r$ occurring during the execution of task τ_i , then provided that the stand-alone execution time $C_i(HI)$ and the resource sensitivity parameters (X_i^r) of task τ_i have been correctly upper bounded, then the task will complete its execution within its budget, irrespective of the level of resource stress emanating from potentially misbehaving

tasks on other cores. Hence, task τ_i has robust assurance that it will meet its deadline, assuming of course that it has been deemed schedulable by the test.

Three NMC schedulability tests are evaluated in Section 5:

- CpFPPS-m-fc-NMC: Uses the context-independent test, comprising (1), (2), (3), and (4), for all tasks.
- **CpFPPS-***m***-D-NMC**: Uses the context-independent test, comprising (1), (2), (3), and (4), for *HI*-criticality tasks, and the deadline based context-dependent test, comprising (1), (2), (3), and (5), for *LO*-criticality tasks.
- **CpFPPS-***m-***R-NMC**: Uses the context-independent test, comprising (1), (2), (3), and (4), for *HI*-criticality tasks, and the response time based context-dependent test, comprising (1), (2), (3), and (6), for *LO*-criticality tasks, and also to compute $R_j(L_j)$ for *HI*-criticality tasks, used as an intermediate value in (6).

4.2 Static Mixed Criticality (SMC)

In this section, we extend the analysis presented in section 4.1 to cater for the Static Mixed Criticality (SMC) scheme [11]. The only difference in the schedulability analysis for SMC compared to NMC is that with SMC, LO-criticality tasks are only required (as per $\bf R1$) to be schedulable when all tasks comply with their LO-criticality stand-alone execution time parameters. As a consequence, the response time analysis is modified as follows. Equation (1) is replaced by (7), the only change being the replacement of $C_j(L_j)$ by $C_j(\min(L_i, L_j))$.

$$R_{i}(L_{i}) = C_{i}(L_{i}) + \sum_{j \in \Gamma_{x} \land j \in \operatorname{hp}(i)} \left\lceil \frac{R_{i}(L_{i})}{T_{j}} \right\rceil C_{j}(\min(L_{i}, L_{j}))$$

$$+ \sum_{r \in H} I_{i}^{r}(R_{i}(L_{i}))$$

$$(7)$$

Similarly, equation (6) is replaced by (8), the only change being the replacement of $R_j(L_j)$ by $R_j(\min(L_i, L_j))$.

$$E_i^r(R_i(L_i), y) = \sum_{j \in \Gamma_y} \left\lceil \frac{R_i(L_i) + R_j(\min(L_i, L_j))}{T_j} \right\rceil Y_j^r \qquad (8)$$

The analysis for SMC thus comprises: (i) a fully composable context-independent test for HI-criticality tasks, defined by (7), (2), (3), and (4), which is effectively the same as that for NMC; (ii) a deadline based context-dependent test for LO-criticality tasks, defined by (7), (2), (3), and (5); and (iii) a response time based context-dependent test for LO-criticality tasks, defined by (7), (2), (3), and (8). Note, the latter test requires that the value of $R_j(LO)$ is similarly computed for each HI-criticality task, for use as an intermediate value in (8).

Three SMC schedulability tests are evaluated in Section 5:

- CpFPPS-m-fc-SMC: Uses the context-independent test, comprising (7), (2), (3), and (4), for all tasks.
- **CpFPPS-***m***-D-SMC**: Uses the context-independent test, comprising (7), (2), (3), and (4), for *HI*-criticality tasks, and the deadline based context-dependent test, comprising (7), (2), (3), and (5), for *LO*-criticality tasks.
- CpFPPS-m-R-SMC: Uses the context-independent test, comprising (7), (2), (3), and (4), for HI-criticality tasks, and

the response time based context-dependent test, comprising (7), (2), (3), and (8), for LO-criticality tasks, and to compute the LO-criticality response times for HI-criticality tasks, used as an intermediate value in (8).

4.3 Original Adaptive Mixed Criticality (AMC)

In this section, we extend the analysis presented in section 4.2 to cater for the original Adaptive Mixed Criticality (AMC) scheme [12]. The only difference in the schedulability analysis for AMC compared to SMC is that with AMC, LO-criticality tasks no longer release new jobs in abnormal mode. The analysis of LO-criticality response times, $R_i(LO)$, for both HI- and LO-criticality tasks is therefore the same as for SMC. The response time $R_i(HI)$ for a HI-criticality task τ_i is derived as follows, using context-independent analysis:

$$R_{i}(HI) = C_{i}(HI) + \sum_{r \in H} (m-1)X_{i}^{r} + \sum_{j \in \Gamma_{x} \land j \in \mathbf{hpH}(i)} \left\lceil \frac{R_{i}(HI)}{T_{j}} \right\rceil \left(C_{j}(HI) + \sum_{r \in H} (m-1)X_{j}^{r} \right) + \sum_{k \in \Gamma_{x} \land k \in \mathbf{hpL}(i)} \left\lceil \frac{R_{i}^{*}(LO)}{T_{j}} \right\rceil \left(C_{k}(LO) + \sum_{r \in H} (m-1)X_{k}^{r} \right)$$
(9)

where $\mathbf{hpH}(i)$ is the set of HI-criticality tasks with priorities higher than that of task τ_i , and similarly $\mathbf{hpL}(i)$ is the set of LO-criticality tasks with priorities higher than that of task τ_i . Further, $R_i^*(LO)$ is the context independent LO-criticality response time of task τ_i given by:

$$R_i^*(LO) = C_i(LO) + \sum_{r \in H} (m-1)X_i^r + \sum_{k \in \Gamma_x \land k \in \text{hp}(i)} \left\lceil \frac{R_i^*(LO)}{T_j} \right\rceil \left(C_k(LO) + \sum_{r \in H} (m-1)X_k^r \right)$$
(10)

Here, (9) and (10) represent the standard analysis equations for the AMC-rtb schedulability test [12] adapted to use inflated execution time budgets, e.g. $C_j(HI) + \sum_{r \in H} (m-1)X_j^r$ and $C_k(LO) + \sum_{r \in H} (m-1)X_k^r$, in place of the original execution time budgets $C_j(HI)$ and $C_k(LO)$.

Previous work on AMC [12] assumes that abnormal mode is entered when some job of a HI-criticality task τ_k executes for $C_k(LO)$ without completing. However, this criterion is not enough when cross-core contention and interference is considered, rather an inflated execution time budget of $C_k(LO) + \sum_{r \in H} (m-1) X_k^r$ must be used instead. Given that both LO- and HI-criticality tasks may be subject to cross-core contention and interference, $R_i^*(LO)$ represents the longest possible time interval from the release of a job of task τ_i until either: (i) the job has completed, or (ii) abnormal mode has been entered. Hence, the interval in (9) during which LO-criticality jobs need to be considered is limited to $R_i^*(LO)$, rather than $R_i(LO)$. Use of the intermediate value, $R_i^*(LO)$, is necessary to ensure compliance with requirement **R2** for robust timing assurance of HI-criticality tasks, including when the behavior of other tasks is such that they do not comply with their resource sensitivity and resource stress parameters.

Three AMC schedulability tests are evaluated in Section 5:

- CpFPPS-m-fc-AMC: Uses the context-independent test, comprising (9) and (10), for HI-criticality tasks, and the context-independent test, comprising (7), (2), (3), and (4), for LO-criticality tasks.
- CpFPPS-m-D-AMC: Uses the context-independent test, comprising (9) and (10), for HI-criticality tasks, and the deadline based context-dependent test, comprising (7), (2), (3), and (5), for LO-criticality tasks.
- CpFPPS-m-R-AMC: Uses the context-independent test, comprising (9) and (10), for HI-criticality tasks, and the response time based context-dependent test, comprising (7), (2), (3), and (8), for LO-criticality tasks, and to compute the LO-criticality response times for HI-criticality tasks, used as an intermediate value in (8).

Since the AMC scheme for partitioned multi-core systems implements independent transitions from normal to abnormal mode on each core, it is interesting to consider how the resource sensitivity and resource stress parameters of tasks impact the mode change behavior. A mode change takes place when a job of a *HI*-criticality task exceeds its LO-criticality $B_k(LO) = C_k(LO) + \sum_{r \in H} (m-1) X_k^r$. This can only happen if the task's stand-alone execution exceeds $C_k(LO)$, since the additional budget terms account for the impact of the worst-case resource stress on all resources from any arbitrary tasks on the other m-1cores. In practice, if at runtime the resource stress is below the worst case assumed, then the HI-criticality task's stand-alone execution could exceed $C_k(LO)$, effectively taking up the slack, without triggering a mode change. This would not however impact the schedulability of any other tasks. The resource sensitivity values, X_{L}^{r} , for a HI-criticality task affect its own budget and hence indirectly affect when it may cause a mode change. By contrast, using resource stress values, Y_i^r , enables less pessimistic schedulability analysis for LO-criticality tasks, however, these values do not impact the timing guarantees afforded to HI-criticality tasks.

4.4 Modified Adaptive Mixed Criticality (AMCR)

In this section, we adapt the analysis presented in section 4.3 to cater for the modified AMC scheme introduced by Bate et al. in [17]. The AMCR family of schemes differ from the original AMC scheme in terms of the criterion used to trigger a change to *degraded mode* during which jobs of LO-criticality tasks are no longer released. Two different AMCR schemes were presented in [17], here we consider the simpler scheme that returns to normal mode on an idle instant.

In the context of this work, i.e. partitioned scheduling on a multi-core system with cross-core interference modelled via resource sensitivity and resource stress, the AMCR scheme operates as follows. AMCR requires that the RTOS transitions a core to degraded mode whenever a job of a HI-criticality task τ_i running on that core reaches, without completing its execution, an elapsed time equal to its LO-criticality response time $R_i(LO)$, as measured from the start of the priority level-i busy period during which it was released. The RTOS transitions the core back to normal mode on an idle instant for that core. (The efficient implementation of this scheme is discussed in [17]).

Given how the LO-criticality response time $R_i(LO)$ of each HI-criticality task τ_i is derived and calculated, it follows that under AMCR, while all tasks on all cores exhibit normal behavior (i.e comply with their LO-criticality execution time $C_j(LO)$, resource sensitivity X_j^r , and resource stress Y_j^r parameters), no job of a HI-criticality task can cause a transition to degraded mode. Hence AMCR can ensure that LO-criticality tasks meet their timing assurance requirement R1 (see Section 1) using the same analysis as the standard AMC scheme.

The following analysis for AMCR meets the more robust timing assurance required for *HI*-criticality tasks.

$$R_{i}(HI) = C_{i}(HI) + \sum_{r \in H} (m-1)X_{i}^{r} + \sum_{j \in \Gamma_{X} \land j \in hpH(i)} \left\lceil \frac{R_{i}(HI)}{T_{j}} \right\rceil \left(C_{j}(HI) + \sum_{r \in H} (m-1)X_{j}^{r} \right) + \sum_{k \in \Gamma_{X} \land k \in hpL(i)} \left\lceil \frac{R_{i}(LO)}{T_{j}} \right\rceil \left(C_{k}(LO) + \sum_{r \in H} (m-1)X_{k}^{r} \right)$$
(11)

Observe that the only difference between the analysis for HI-criticality tasks under the original AMC scheme, given by (9), and that for AMCR, given by (11), is that $R_i^*(LO)$, given by (10), is replaced by $R_i(LO)$, given by (7). Further, $R_i(LO)$ may be computed using context-dependent analysis, improving the precision of the schedulability test.

Under AMCR, once an elapsed time of $R_i(LO)$ has passed since the start of the priority level-i busy period in which a job of *HI*-criticality task τ_i was released and the job has not completed, then the RTOS ensures that degraded mode is entered. This prevents any further releases of higher priority LO-criticality tasks on that core, until after τ_i completes. Whatever caused $R_i(LO)$ to be exceeded, for example a job of a higher priority HI-criticality task τ_i on the same core exceeding its LO-criticality budget $B_j(LO) = C_j(LO) + \sum_{r \in H} (m-1)X_i^r$ or a LO-criticality task on another core misbehaving and causing more resource stress than expected, does not matter as far as the analysis is concerned. This is the case because (11) accounts for the maximum number of job releases of each LO-criticality task τ_k up to $R_i(LO)$ at their LO-criticality budget $B_k(LO) = C_k(LO) + \sum_{r \in H} (m-1)X_k^r$, and the maximum number of job releases of each HI-criticality task τ_i $R_i(HI)$ at their HI-criticality $B_j(HI) = C_j(HI) + \sum_{r \in H} (m-1)X_i^r$, hence the robust timing guarantee R2 (see Section 1) required by HI-criticality task τ_i

Three AMCR schedulability tests are evaluated in Section 5:

- CpFPPS-m-fc-AMCR: Uses the context-independent test, comprising (11) for HI-criticality tasks, and the context-independent test, comprising (7), (2), (3), and (4), for LO-criticality tasks and to provide the LO-criticality response times used in (11). Note, this is effectively the same schedulability test as the fully-composable test for the original AMC scheme.
- **CpFPPS-***m***-D-AMCR**: Uses the context-dependent test, comprising (11), for *HI*-criticality tasks, and the deadline based context-dependent test, comprising (7), (2), (3), and

- (5), for *LO*-criticality tasks and to provide the *LO*-criticality response times used in (11).
- CpFPPS-m-R-AMCR: Uses the context-dependent test, comprising (11), for HI-criticality tasks, and the response time based context-dependent test, comprising (7), (2), (3), and (8), for LO-criticality tasks, and to compute the LO-criticality response times used in (8) and in (11).

We note that although the value of $R_i(LO)$ used in (11) can be computed via context-dependent analysis (as in the -**D** and -**R** tests above), this does not mean that the schedulability guarantees afforded to HI-criticality tasks by (11) are dependent on the behavior of other tasks. The subtlety is that under AMCR, the RTOS enforces the transition to degraded mode at $R_i(LO)$ irrespective of the behavior or misbehavior of the other tasks, hence ensuring that the robust timing requirement **R2** (see Section 1) required by HI-criticality tasks holds.

4.5 Dominance Relations

A schedulability test S is said to *dominate* another test Z, for a given task model and scheduling algorithm, if every task set that is deemed schedulable according to test Z is also deemed schedulable by test S, and there exists some task sets that are schedulable according to test S, but not according to test S.

Comparing the definitions of $E_i^r(R_i(L_i), y)$ given by (5), (6), and (8), it is evident that each of the CpFPPS-m-R-MCS tests deems schedulable all task sets that are schedulable according to the corresponding CpFPPS-m-D-MCS test. This is the case, since in any schedulable system, the response time of a task is no greater than its deadline $(R_i(L_i) \leq D_i)$, and hence the $E_i^r(R_i(L_i), y)$ term for the former tests, given by (6) or (8), is less than or equal to the equivalent term, given by (5), for the latter tests. Further, it is easy to see that there exists task sets that are schedulable according to the former tests, but not according to the corresponding latter tests due to a larger contention contribution emanating from the larger $E_i^r(R_i(L_i), y)$ term. Hence, each **CpFPPS-m-R-MCS** test dominates the corresponding CpFPPS-m-D-MCS test. Similarly, comparing the definitions of $E_i^r(R_i(L_i), y)$ given by (5) and (4) it is evident that each of the CpFPPS-m-D-MCS tests dominates the corresponding CpFPPS-m-fc-MCS test.

Since dominance is transitive, we have: **CpFPPS**-m-**R**-**MCS** \rightarrow **CpFPPS**-m-**D**-**MCS** \rightarrow **CpFPPS**-m-**fc**-**MCS**, where $S \rightarrow Z$ indicates that test S dominates test Z, and **MCS** is **NMC**, **SMC**, **AMC**, or **AMCR**.

Comparing the response time equations (1), (7), (9) and (11), it is also evident that: CpFPPS-m-X-AMCR \rightarrow CpFPPS-m-X-AMC \rightarrow CpFPPS-m-X-SMC \rightarrow CpFPPS-m-X-NMC, where X is fc, D, or R

4.6 Complexity

The standard response time analysis [8, 45] for partitioned fixed priority preemptive scheduling, not considering cross-core contention, has pseudo-polynomial complexity: $O(mn^2D^{max})$ [31], where m is the number of cores, n is the number of tasks on each core, and D^{max} is the longest deadline of any task. The schedulability tests presented in this paper for mixed criticality systems under the MRSS task model inherit their complexity from

the schedulability tests for single criticality systems under the same model [30, 31]. Hence, the **-fc**, **-D**, and **-R** tests have complexity of $O(m|H|n^2D^{max})$, $O(m^2|H|n^2D^{max})$, and $O(m^3|H|n^3D^{max})$ respectively, where |H| is the number of resources. This represents an increase in complexity of |H|, m|H|, and $m^2|H|n$ over the equivalent tests that do not consider cross-core contention.

Given the high performance of the standard response time tests for fixed priority preemptive scheduling [32], in practice, all of the tests presented in this paper scale well to realistic system sizes. As a consequence, utilizing the highest performing **-R** tests is often preferable, unless a fully composable **-fc** test is deemed necessary due to design and development requirements. However, as shown in [30, 31], the **-D** tests are compatible with Audsley's Optimal Priority Assignment algorithm [7], whereas the **-R** tests are not. Thus, in some cases it may be advantageous to trade off using the technically inferior **-D** tests in order reap the performance benefits of optimal priority assignment.

5 EVALUATION

In this section, we present an empirical evaluation of the schedulability tests introduced in Section 4 for mixed-criticality task sets executing on a multi-core system, assuming a single hardware resource shared between all cores. (Note, multiple shared hardware resources resulting in the same total interference would have the same impact on schedulability, due to the summation over resources in (1)). Experiments were performed for 2 and 4 cores³.

5.1 Task Set Parameter Generation

The task set parameters used in the experiments follow the approach taken for the MRSS task model [30, 31] and for mixed criticality systems [41], with the Dirichlet-Rescale (DRS) algorithm [41] (open source Python software [40]) used to provide an unbiased distribution of utilization values that sum to the target utilization required subject to a set of individual constraints. The values selected for task resource sensitivity and task resource stress are grounded in the results obtained from the proof-of-concept case study detailed in [30, 31].

- The number of tasks per core was fixed, default n=10. The number of HI-criticality tasks n(HI) was set to $n \cdot CP$ where CP is the Criticality Proportion (default CP=0.2), with the remaining tasks of LO-criticality.
- Task utilizations were generated using the DRS algorithm. First, HI-criticality utilization values $U_i(HI)$ were generated for the n(HI) HI-criticality tasks, such that the total HI-criticality utilization of those tasks summed to $U(HI) = CP \cdot CF \cdot U$, where CF is the Criticality Factor (default CF = 2.0) characterizing the multiplier between LO-criticality and HI-criticality utilization, and U is the overall target utilization required. Second, LO-criticality utilization values $U_i(LO)$ were generated for all of the tasks, such that the total LO-criticality utilization of all tasks summed to U(LO) = U. For LO-criticality tasks, each

 $U_i(LO)$ value was constrained to be in the range [0.0, 1.0], while for HI-criticality tasks, each $U_j(LO)$ value was constrained to be in the range [0.0, $U_i(HI)$].

- Task periods T_i were generated according to a log-uniform distribution [33] with a factor of 100 difference between the minimum and maximum possible period. This represents a spread of task periods from 10ms to 1 second, as found in many real-time applications.
- Task deadlines D_i were set equal to their periods T_i .
- The stand-alone LO-criticality execution times all tasks were given by $C_i(LO) = U_i(LO) \cdot T_i$, and the stand-alone HI-criticality execution times of HI-criticality tasks by $C_i(HI) = U_i(HI) \cdot T_i$.
- Task resource sensitivity values X_i^r were determined as follows. The DRS algorithm was used to generate task resource sensitivity utilization values V_i^r , such that the total resource sensitivity utilization was given by the Sensitivity Factor SF (default SF = 0.25) times the target utilization (i.e. $\sum_{\forall i \in \Gamma_x} V_i^r = U \cdot SF$), and each individual task resource sensitivity utilization was upper bounded by the corresponding task LO-criticality utilization, i.e. $V_i^r \leq U_i(LO)$. Each task resource sensitivity value was then given by $X_i^r = V_i^r \cdot T_i$.
- Task resource stress values Y_i^r were set to a fixed proportion of the corresponding resource sensitivity value $Y_i^r = X_i^r \cdot RF$, where RF is the Stress Factor (default RF = 0.5).

5.2 Experiments

The experiments considered systems with 2 or 4 cores, with a different task set, generated according to the same parameters, assigned to each core. The per core target utilization U, shown on the x-axis of the graphs, was varied from 0.025 to 0.975. For each utilization value examined, 1000 task sets were generated for each core considered (100 in the case of experiments using the weighted schedulability measure [14]). In the experiments, a system was deemed schedulable if and only if the different task sets assigned to each of its cores were schedulable, i.e. if all of the tasks in the system were schedulable. The experiments investigated the performance of schedulability tests for the following schemes:

- Upper Bound High and Low (UBHL) [12]: This test checks if all of the tasks are schedulable in normal mode and if all of the *HI*-criticality tasks are schedulable in abnormal mode ignoring the *LO*-criticality tasks. This equates to the test for a hypothetical clairvoyant scheme discussed in [22]. (Black lines on the graphs).
- Modified Adaptive Mixed Criticality (AMCR) [17]: See section 4.4. (Red lines on the graphs).
- Original Adaptive Mixed Criticality (AMC) [12]: See section 4.3. (Blue lines on the graphs).
- Static Mixed Criticality (SMC) [11]: See section 4.2. (Green lines on the graphs).
- No Mixed Criticality (NMC): See section 4.1. (Orange lines on the graphs).

In each case, four variants of the tests were considered, the first three corresponding to the context-independent -fc (dotted lines) and context-dependent -D (dashed lines) and -R (solid lines)

³The analysis scales to more than 4 cores; however, we limited consideration to this range, since 4 cores represents a typical cluster size beyond which sharing hardware resources can become a significant performance bottleneck.

methods of accounting for cross-core contention and interference, and the fourth, for comparison purposes only, assuming no such interference -no (thin dot-dash lines).

Deadline Monotonic Priority Ordering [52] was used to assign priorities, since the context-dependent -R tests are not compatible with Audsley's Optimal Priority Assignment algorithm [7], as shown in [30, 31].

5.3 Results

The figures illustrating the results are best viewed in color.

In the first experiment, we compared the performance of the various schedulability tests using the default parameters given in Section 5.1. The *Success Ratio*, i.e. the percentage of systems generated that were deemed schedulable, is shown for each of the tests in Figure 1 for 2 cores, and in Figure 4 for 4 cores. The relative performance of the various tests follows the dominance relations discussed in Section 4.5. Observe, that for equivalent tests, overall schedulability is reduced in the case of 4 cores compared to 2 cores. This is due to the increased cross-core contention and interference with more cores. Note, even when no cross-core contention is considered (i.e. the thin dot-dash lines) then schedulability is still reduced with 4 cores. This is because the task sets on two extra cores must also be schedulable for the overall system to be deemed schedulable.

Considering the four mixed criticality schemes, AMCR and AMC substantially outperform both SMC and NMC, with SMC providing only a small improvement over NMC. The reason for this is that the robust timing guarantee **R2** required by *HI*-criticality tasks means that the schedulability of those tasks in abnormal mode is the predominant factor in overall system schedulability. AMCR and AMC enhance the schedulability of *HI*-criticality tasks in abnormal mode by suspending releases of *LO*-criticality jobs, hence providing a performance gain compared to both SMC and NMC, which both continue to release jobs of *LO*-criticality tasks, impinging on *HI*-criticality task schedulability. The small improvement that SMC brings over NMC derives from the fact that *LO*-criticality tasks do not have to be schedulable in abnormal mode.

In the second set of experiments, we used the weighted schedulability measure [14] to assess schedulability test performance while varying an additional parameter. In these experiments, the other parameters were set to the default values given in Section 5.1. In all of the weighted schedulability experiments the relative performance of the different tests follows the pattern illustrated in the first experiment, as dictated by the dominance relationships.

The results of varying the Sensitivity Factor SF, from 0.05 to 0.95 in steps of 0.05, are shown in Figure 2. Recall that the Sensitivity Factor determines the ratio of the total resource sensitivity utilization to the total LO-criticality task utilization. As expected, increasing the Sensitivity Factor, and hence the amount of interference that tasks can be subject to due to cross-core contention, results in a rapid decline in the weighted schedulability measure for all of the tests that take cross-core contention into account.

The results of varying the Stress Factor RF, from 0 to 1.8 in steps of 0.1, are shown in Figure 5. Recall that the Stress Factor

determines the ratio of the resource stress for each task to its resource sensitivity. Here, interference effective saturates once the Stress Factor reaches 1.0. By then, the total resource stress $E_i^r(t,y)$, given by (5) or (6), emanating from each additional core tends to exceed the total resource sensitivity $S_i^r(t,x)$, given by (3). Hence, the context-dependent - \mathbf{R} and - \mathbf{D} tests reduce to exactly the same performance as the context-independent - \mathbf{fc} test.

Observe that in Figure 2, the -R, -D, and -fc tests have very similar performance when combined with SMC or NMC. The reason for this is that since LO-criticality jobs continue to be released in abnormal mode, overall schedulability depends predominantly on the schedulability of the HI-criticality tasks in that mode, hence the form of analysis used for LO-criticality tasks has little bearing on the overall results. This is not the case with AMC, AMCR, or the UBHL bound, where modest gains are apparent when using the -R or -D tests for all tasks in normal mode. The same behavior is evident in Figure 5, however, in that case as the resource Stress Factor is reduced, the impact of contention on LO-criticality tasks decreases, and the performance advantage obtained using the context-dependent -R and -D tests increases

In Figure 5, when the resource Stress Factor is zero, the UBHL bound combined with the context-dependent - $\bf R$ and - $\bf D$ tests provides almost the same performance as the no contention case (- $\bf no$). This is because the HI-criticality tasks considered alone are easily schedulable in abnormal mode, and hence system schedulability according to the UBHL bound is predominantly influenced by schedulability in normal mode. This is not the case with AMC, since although LO-criticality tasks are prevented from releasing further jobs in abnormal mode, job releases prior to that point still impinge upon HI-criticality task schedulability in abnormal mode. AMCR shows a significant advantage over AMC when the resource Stress Factor is small. This is because the difference between $R_i(LO)$ used in (11) and $R_i^*(LO)$ used in (10) is amplified in this case, resulting in fewer jobs of LO-criticality tasks impinging upon HI-criticality task schedulability under AMCR.

The results of varying the Criticality Proportion *CP*, from 0.0 to 1.0 in steps of 0.1, are shown in Figure 3. With no *HI*-criticality tasks, UBHL, AMCR, AMC, SMC, and NMC all reduce to the same (-no, -R, -D, or -fc) schedulability test and hence the same performance. At the other extreme, when there are only *HI*-criticality tasks and since these tasks require the robust timing guarantees afforded by a context-independent test, the set of -R, -D, and -fc tests for each scheme all reduce to the same performance. Additionally, since there are only *HI*-criticality tasks, all of the schemes reduce to exactly the same schedulability test, and so all of the lines for tests where cross-core contention is considered meet at a single point.

In Figure 3, the performance of the SMC and NMC tests improves as a final HI-criticality task is added and there are no longer any LO-criticality tasks present. This stems from the way in which HI- and LO-criticality utilization values are generated. The total HI-criticality utilization of the HI-criticality tasks is precisely controlled by the task set generation process, as is the total LO-criticality utilization over all of the tasks. However, the LO-criticality utilization of a single LO-criticality task is not. With SMC and NMC, schedulability effectively depends on the total utilization in abnormal mode, i.e. the sum of the LO-criticality




Figure 1: Success Ratio: Varying task set utilization, 2 cores.




Figure 2: Weighted Schedulability: Varying Resource Sensitivity, 2 cores.




Figure 3: Weighted Schedulability: Varying the Criticality Proportion, 2 cores.




Figure 4: Success Ratio: Varying task set utilization, 4 cores.




Figure 5: Weighted Schedulability: Varying Resource Stress, 2 cores.




Figure 6: Weighted Schedulability: Varying the Criticality Factor, 2 cores.

1221

1223

1224

1225

1226

1230

1231

1232

1233

1234

1236

1237

1238

1239

1240

1243

1244

1245

1246

1247

1249

1250

1252

1253

1257

1258

1259

1260

1263

1264

1265

1269

1270

1271

1272

1273

1274

1276

utilization of the LO-criticality tasks and the HI-criticality utilization of the HI-criticality tasks, and this can be worse when almost but not all of the tasks are of HI-criticality.

In Figure 3 with the UBHL bound, weighted schedulability remains roughly constant until the proportion of HI-criticality tasks exceeds 50%. This is because the default Criticality Factor is 2.0, hence when more than 50% of the tasks are HI-criticality, the increased utilization of HI-criticality tasks in abnormal mode becomes the dominant factor influencing schedulability. Before then, the total LO-criticality utilization is the dominant factor and that does not vary with the Criticality Proportion.

The results of varying the Criticality Factor CF, from 1.0 to 4.0 in steps of 0.2, are shown in Figure 6. Observe that schedulability according to AMCR, AMC, SMC, and NMC, progressively decreasesas the Criticality Factor increases, so increasing the utilization of HI-criticality tasks in abnormal mode. This trend is not evident with the UBHL bound, as the default Criticality Proportion of HI-criticality tasks is 0.2, and hence even with CF = 4.0 the increased utilization of HI-criticality tasks in abnormal mode is still not the dominant factor influencing system schedulability, rather the total LO-criticality utilization is the dominant factor and that does not vary with the Criticality Factor.

Overall, the results for the modified AMCR scheme provide a useful improvement over their counterparts for the original AMC scheme, shifting the schedulability guarantees closer to the hypothetical UBHL upper bound that ignores the effects of the mode change transition. As expected, both AMCR and AMC significantly outperform SMC and NMC.

6 CONCLUSIONS

1161

1162

1163

1164

1165

1166

1167

1168

1173

1174

1175

1176

1177

1178

1179

1180

1181

1182

1185

1186

1187

1188

1189

1190

1191

1192

1193

1194

1195

1199

1200

1201

1202

1203

1205

1206

1207

1208

1212

1213

1214

1215

1216

1217

1218

The main contributions of this paper are as follows: (i) The integration of mixed criticality concepts into the MRSS [30, 31] multi-core system model that characterizes cross-core contention and interference via task resource stress and sensitivity. (ii) Consideration of the different levels of assurance needed in mixed criticality systems, specifically the need to provide HI-criticality tasks with robust timing guarantees. (iii) Derivation of schedulability analysis for four mixed criticality scheduling schemes (NMC, SMC, AMC, and AMCR), accounting for resource contention and interference on a partitioned multi-core processor, providing appropriate timing guarantees for both HI- and LO-criticality tasks.

The key observations are as follows. Firstly, as expected, the significant performance advantages that the AMCR and AMC schemes hold over the simple SMC and NMC schemes are retained when cross-core contention and interference is included via a mixed criticality multi-core resource stress and sensitivity model. Secondly, utilizing more precise context-dependent schedulability tests to bound the interference on *LO*-criticality tasks results in useful performance improvements, while still ensuring that *HI*-criticality tasks are provided with robust timing guarantees. Finally, it is interesting to note that while the AMCR and AMC schemes have identical performance in terms of schedulability when cross-core contention is not considered, once such interference is included, then the AMCR scheme dominates AMC.

ACKNOWLEDGMENTS

This research was funded in part by Innovate UK HICLASS project (113213) EPSRC Research Data Management: No new primary data was created during this study.

REFERENCES

- [1] Benny Akesson, Mitra Nasri, Geoffrey Nelissen, Sebastian Altmeyer, and Robert I. Davis. 2020. An Empirical Survey-based Study into Industry Practice in Real-time Systems. In 41st IEEE Real-Time Systems Symposium, RTSS 2020, Houston, TX, USA, December 1-4, 2020. IEEE, 3-11. https://doi.org/10.1109/RTSS49844.2020.00012
- [2] Benny Akesson, Mitra Nasri, Geoffrey Nelissen, Sebastian Altmeyer, and Robert I. Davis. 2021. A comprehensive survey of industry practice in real-time systems. Real-Time Syst. (2021), 41. https://doi.org/10.1007/s11241-021-09376-1
- [3] Sebastian Altmeyer, Robert I. Davis, Leandro Soares Indrusiak, Claire Maiza, Vincent Nélis, and Jan Reineke. 2015. A generic and compositional framework for multicore response time analysis. In 23rd International Conference on Real Time Networks and Systems, RTNS 2015, Lille, France, November 4-6, 2015, Julien Forget (Ed.). ACM, 129-138. https://doi.org/10.1145/2834848.2834862
- [4] J.H. Anderson, S.K. Baruah, and B.B. Brandenburg. 2009. Multicore Operating-System Support for Mixed Criticality. In Proc. of the Workshop on Mixed Criticality: Roadmap to Evolving UAV Certification, San Francisco.
- [5] Björn Andersson, Hyoseung Kim, Dionisio de Niz, Mark H. Klein, Ragunathan Rajkumar, and John P. Lehoczky. 2018. Schedulability Analysis of Tasks with Corunner-Dependent Execution Times. ACM Trans. Embed. Comput. Syst. 17, 3 (2018), 71:1–71:29. https://doi.org/10.1145/3203407
- [6] Sedigheh Asyaban and Mehdi Kargahi. 2018. An exact schedulability test for fixed-priority preemptive mixed-criticality real-time systems. Real Time Syst. 54, 1 (2018), 32–90. https://doi.org/10.1007/s11241-017-9287-2
- [7] Neil C. Audsley. 2001. On priority assignment in fixed priority scheduling. Inf. Process. Lett. 79, 1 (2001), 39–44. https://doi.org/10.1016/S0020-0190(00)00165-4
- [8] Neil C. Audsley, Alan Burns, Michael Richardson, Kenneth W. Tindell, and Andrew J. Wellings. 1993. Applying new scheduling theory to static priority preemptive scheduling. Software Engineering Journal 8 (September 1993), 284–292(8). Issue 5. https://digital-library.theiet.org/content/journals/10.1049/sej.1993.0034
- [9] Joshua Bakita, Shareef Ahmed, Sims Hill Osborne, Stephen Tang, Jingyuan Chen, F. Donelson Smith, and James H. Anderson. 2021. Simultaneous Multithreading in Mixed-Criticality Real-Time Systems. In 27th IEEE Real-Time and Embedded Technology and Applications Symposium, RTAS 2021, Nashville, TN, USA, May 18-21, 2021. IEEE, 278-291. https://doi.org/10.1109/RTAS52030.2021.00030
- [10] Sanjoy Baruah, Alan Burns, and Robert I. Davis. 2013. An Extended Fixed Priority Scheme for Mixed Criticality Systems. In Workshop on Real-Time Mixed Criticality Systems (ReTiMics) 2013, 21st August, Taipei, Taiwan. 18–24. https://www-users.cs.york.ac.uk/~robdavis/papers/jitterRTCSA.pdf
- [11] Sanjoy K. Baruah and Alan Burns. 2011. Implementing Mixed Criticality Systems in Ada. In Reliable Software Technologies - Ada-Europe 2011 - 16th Ada-Europe International Conference on Reliable Software Technologies, Edinburgh, UK, June 20-24, 2011. Proceedings (Lecture Notes in Computer Science, Vol. 6652), Alexander B. Romanovsky and Tullio Vardanega (Eds.). Springer, 174–188. https://doi.org/10. 1007/978-3-642-21338-0 13
- [12] Sanjoy K. Baruah, Alan Burns, and Robert I. Davis. 2011. Response-Time Analysis for Mixed Criticality Systems. In Proceedings of the 32nd IEEE Real-Time Systems Symposium, RTSS 2011, Vienna, Austria, November 29 - December 2, 2011. IEEE Computer Society, 34–43. https://doi.org/10.1109/RTSS.2011.12
- [13] Sanjoy K. Baruah and Bipasa Chattopadhyay. 2013. Response-time analysis of mixed criticality systems with pessimistic frequency specification. In 2013 IEEE 19th International Conference on Embedded and Real-Time Computing Systems and Applications, RTCSA 2013, Taipei, Taiwan, August 19-21, 2013. IEEE Computer Society, 237-246. https://doi.org/10.1109/RTCSA.2013.6732224
- [14] Andrea Bastoni, Bjorn B. Brandenburg, and James H. Anderson. 2010. Cache-Related Preemption and Migration Delays: Empirical Approximation and Impact on Schedulability. In International Workshop on Operating Systems Platforms for Embedded Real-Time Applications. 33–44.
- [15] Iain Bate, Alan Burns, and Robert I. Davis. 2015. A Bailout Protocol for Mixed Criticality Systems. In 27th Euromicro Conference on Real-Time Systems, ECRTS 2015, Lund, Sweden, July 8-10, 2015. IEEE Computer Society, 259–268. https://doi.org/10.1109/ECRTS.2015.30
- [16] Iain Bate, Alan Burns, and Robert I. Davis. 2017. An Enhanced Bailout Protocol for Mixed Criticality Embedded Software. IEEE Trans. Software Eng. 43, 4 (2017), 298–320. https://doi.org/10.1109/TSE.2016.2592907
- [17] Iain Bate, Alan Burns, and Robert I. Davis. 2022. Analysis-Runtime Co-design for Adaptive Mixed Criticality Scheduling. In IEEE Real-Time and Embedded Technology and Applications Symposium, RTAS 2022, 4-6 May 2022, Milano, Italy, Heechul Yun (Ed.). IEEE Computer Society, 14 pages.
- [18] Alan Burns and Robert I. Davis. 2013. Mixed Criticality on Controller Area Network. In 25th Euromicro Conference on Real-Time Systems, ECRTS 2013, Paris,

1280

1281

1282

1283

1284

1285

1288

1289

1290

1291

1292

1293

1294

1295

1296

1297

1298

1301

1302

1303

1304

1305

1306

1307

1308

1309

1310

1311

1312

1314

1315

1316

1317

1318

1319

1320

1321

1322

1323

1324

1325

1326

1327

1328

1329

1330

1331

1332

1333

1334

1335

1336

1337

1339

1340

1341

1342

1343

1344

1346

1347

1348

1349

1350

1351

1352

1353

1354

1355

1356

1357

1359

1360

1361

1362

1363

1365

1366

1367

1368

1369

1370

1371

1372

1373

1374

1375

1376

1377

1379

1380

1381

1382

1385

1386

1387

1388

1389

1390

1391

1392

- 1277 France, July 9-12, 2013. IEEE Computer Society, 125–134. https://doi.org/10.1109/
 1278 ECRTS.2013.23
 - [19] Alan Burns and Robert I. Davis. 2014. Adaptive Mixed Criticality Scheduling with Deferred Preemption. In Proceedings of the IEEE 35th IEEE Real-Time Systems Symposium, RTSS 2014, Rome, Italy, December 2-5, 2014. IEEE Computer Society, 21–30. https://doi.org/10.1109/RTSS.2014.12
 - [20] Alan Burns and Robert I. Davis. 2018. A Survey of Research into Mixed Criticality Systems. ACM Comput. Surv. 50, 6 (2018), 82:1–82:37. https://doi.org/10.1145/ 3131347
 - [21] Alan Burns and Robert I. Davis. 2019. Mixed Criticality Systems: A Review (12th Edition). Technical Report MCC-1(M), Available at https://www-users.cs.york.ac. uk/-burns/review.pdf. Department of Computer Science, University of York.
 - [22] Alan Burns and Robert I. Davis. 2020. Schedulability Analysis for Adaptive Mixed Criticality Systems with Arbitrary Deadlines and Semi-Clairvoyance. In 41st IEEE Real-Time Systems Symposium, RTSS 2020, Houston, TX, USA, December 1-4, 2020. IEEE, 12-24. https://doi.org/10.1109/RTSS49844.2020.00013
 - [23] Alan Burns, Robert I. Davis, Sanjoy K. Baruah, and Iain Bate. 2018. Robust Mixed-Criticality Systems. IEEE Trans. Computers 67, 10 (2018), 1478–1491. https://doi.org/10.1109/TC.2018.2831227
 - [24] Sheng-Wei Cheng, Jian-Jia Chen, Jan Reineke, and Tei-Wei Kuo. 2017. Memory Bank Partitioning for Fixed-Priority Tasks in a Multi-core System. In 2017 IEEE Real-Time Systems Symposium, RTSS 2017, Paris, France, December 5-8, 2017. IEEE Computer Society, 209–219. https://doi.org/10.1109/RTSS.2017.00027
 - [25] Micaiah Chisholm, Namhoon Kim, Bryan C. Ward, Nathan Otterness, James H. Anderson, and F. Donelson Smith. 2016. Reconciling the Tension Between Hardware Isolation and Data Sharing in Mixed-Criticality, Multicore Systems. In 2016 IEEE Real-Time Systems Symposium, RTSS 2016, Porto, Portugal, November 29 December 2, 2016. IEEE Computer Society, 57–68. https://doi.org/10.1109/RTSS. 2016.015
 - [26] Micaiah Chisholm, Bryan C. Ward, Namhoon Kim, and James H. Anderson. 2015. Cache Sharing and Isolation Tradeoffs in Multicore Mixed-Criticality Systems. In 2015 IEEE Real-Time Systems Symposium, RTSS 2015, San Antonio, Texas, USA, December 1-4, 2015. IEEE Computer Society, 305–316. https://doi.org/10.1109/RTSS.2015.36
 - [27] Dakshina Dasari, Björn Andersson, Vincent Nélis, Stefan M. Petters, Arvind Easwaran, and Jinkyu Lee. 2011. Response Time Analysis of COTS-Based Multicores Considering the Contention on the Shared Memory Bus. In IEEE 10th International Conference on Trust, Security and Privacy in Computing and Communications, TrustCom 2011, Changsha, China, 16-18 November, 2011. IEEE Computer Society, 1068-1075. https://doi.org/10.1109/TrustCom.2011.146
 - [28] Robert I. Davis, Sebastian Altmeyer, and Alan Burns. 2018. Mixed Criticality Systems with Varying Context Switch Costs. In IEEE Real-Time and Embedded Technology and Applications Symposium, RTAS 2018, 11-13 April 2018, Porto, Portugal, Rodolfo Pellizzoni (Ed.). IEEE Computer Society, 140-151. https://doi.org/10.1109/RTAS.2018.00024
 - [29] Robert I. Davis, Sebastian Altmeyer, Leandro Soares Indrusiak, Claire Maiza, Vincent Nélis, and Jan Reineke. 2018. An extensible framework for multicore response time analysis. *Real Time Syst.* 54, 3 (2018), 607–661. https://doi.org/10. 1007/s11241-017-9285-4
 - [30] Robert I. Davis, David Griffin, and Iain Bate. 2021. Schedulability Analysis for Multi-core Systems Accounting for Resource Stress and Sensitivity. In 33rd Euromicro Conference on Real-Time Systems, ECRTS 2021, July 5-9, 2021, Virtual Conference (LIPIcs, Vol. 196), Björn Brandenburg (Ed.). Schloss Dagstuhl - Leibniz-Zentrum für Informatik, 7:1–7:26.
 - [31] Robert I. Davis, David Griffin, and Iain Bate. 2022. A Framework for Multi-core Schedulability Analysis Accounting for Resource Stress and Sensitivity. *Real-Time* Syst. (2022), 1–58. https://doi.org/10.1007/s11241-022-09377-8
 - [32] Robert I. Davis, A. Zabos, and Alan Burns. 2008. Efficient Exact Schedulability Tests for Fixed Priority Real-Time Systems. IEEE Trans. Computers 57, 9 (2008), 1261–1276. https://doi.org/10.1109/TC.2008.66
 - [33] Paul Emberson, Roger Stafford, and Robert I. Davis. 2010. Techniques For The Synthesis Of Multiprocessor Tasksets. In International Workshop on Analysis Tools and Methodologies for Embedded and Real-time Systems (WATERS). 6–11. http://retis.sssup.it/waters2010/waters2010.pdf
 - [34] Rolf Ernst and Marco Di Natale. 2016. Mixed Criticality Systems A History of Misconceptions? IEEE Des. Test 33, 5 (2016), 65–74. https://doi.org/10.1109/ MDAT.2016.2594790
 - [35] Alexandre Esper, Geoffrey Nelissen, Vincent Nélis, and Eduardo Tovar. 2015. How realistic is the mixed-criticality real-time system model?. In Proceedings of the 23rd International Conference on Real Time Networks and Systems, RTNS 2015, Lille, France, November 4-6, 2015, Julien Forget (Ed.). ACM, 139–148. https: //doi.org/10.1145/2834848.2834869
 - [36] Mikel Fernández, Roberto Gioiosa, Eduardo Quiñones, Luca Fossati, Marco Zulianello, and Francisco J. Cazorla. 2012. Assessing the suitability of the NGMP multi-core processor in the space domain. In Proceedings of the 12th International Conference on Embedded Software, EMSOFT 2012, part of the Eighth Embedded Systems Week, ESWeek 2012, Tampere, Finland, October 7-12, 2012, Ahmed Jerraya, Luca P. Carloni, Florence Maraninchi, and John Regehr (Eds.). ACM, 175-184.

- https://doi.org/10.1145/2380356.2380389
- [37] Tom Fleming and Alan Burns. 2013. Extending Mixed Criticality Scheduling. In Workshop on Mixed Criticality Systems (WMC). 7–12.
- [38] Oliver Gettings, Sophie Quinton, and Robert I. Davis. 2015. Mixed criticality systems with weakly-hard constraints. In Proceedings of the 23rd International Conference on Real Time Networks and Systems, RTNS 2015, Lille, France, Nov. 4-6, 2015, Julien Forget (Ed.). ACM, 237–246. https://doi.org/10.1145/2834848.2834850
- [39] Georgia Giannopoulou, Kai Lampka, Nikolay Stoimenov, and Lothar Thiele. 2012. Timed model checking with abstractions: towards worst-case response time analysis in resource-sharing manycore systems. In Proceedings of the 12th International Conference on Embedded Software, EMSOFT 2012, part of the Eighth Embedded Systems Week, ESWeek 2012, Tampere, Finland, October 7-12, 2012, Ahmed Jerraya, Luca P. Carloni, Florence Maraninchi, and John Regehr (Eds.). ACM, 63-72. https://doi.org/10.1145/2380356.2380372
- [40] David Griffin, Iain Bate, and Robert I. Davis. 2020. Dirichlet-Rescale (DRS) algorithm software: dgdguk/drs: v1.0.0 https://doi.org/10.5281/zenodo.4118059.
- [41] David Griffin, Iain Bate, and Robert I. Davis. 2020. Generating Utilization Vectors for the Systematic Evaluation of Schedulability Tests. In 41st IEEE Real-Time Systems Symposium, RTSS 2020, Houston, TX, USA, December 1-4, 2020. IEEE, 76–88. https://doi.org/10.1109/RTSS49844.2020.00018
- [42] Jonathan L. Herman, Christopher J. Kenna, Malcolm S. Mollison, James H. Anderson, and Daniel M. Johnson. 2012. RTOS Support for Multicore Mixed-Criticality Systems. In 2012 IEEE 18th Real Time and Embedded Technology and Applications Symposium, Beijing, China, April 16-19, 2012, Marco Di Natale (Ed.). IEEE Computer Society, 197–208. https://doi.org/10.1109/RTAS.2012.24
- [43] Huang-Ming Huang, Christopher D. Gill, and Chenyang Lu. 2012. Implementation and Evaluation of Mixed-Criticality Scheduling Approaches for Periodic Tasks. In 2012 IEEE 18th Real Time and Embedded Technology and Applications Symposium, Beijing, China, April 16-19, 2012, Marco Di Natale (Ed.). IEEE Computer Society, 23-32. https://doi.org/10.1109/RTAS.2012.16
- [44] Dan Iorga, Tyler Sorensen, John Wickerson, and Alastair F. Donaldson. 2020. Slow and Steady: Measuring and Tuning Multicore Interference. In IEEE Real-Time and Embedded Technology and Applications Symposium, RTAS 2020, Sydney, Australia, April 21-24, 2020. IEEE, 200–212. https://doi.org/10.1109/RTAS48715.2020.000-6
- [45] Mathai Joseph and Paritosh K. Pandya. 1986. Finding Response Times in a Real-Time System. Comput. J. 29, 5 (1986), 390–395. https://doi.org/10.1093/comjnl/ 29.5.390
- [46] Hyoseung Kim, Dionisio de Niz, Björn Andersson, Mark H. Klein, Onur Mutlu, and Ragunathan Rajkumar. 2016. Bounding and reducing memory interference in COTS-based multi-core systems. *Real Time Syst.* 52, 3 (2016), 356–395. https://doi.org/10.1007/s11241-016-9248-1
- [47] Namhoon Kim, Bryan C. Ward, Micaiah Chisholm, James H. Anderson, and F. Donelson Smith. 2017. Attacking the one-out-of-m multicore problem by combining hardware management with mixed-criticality provisioning. *Real Time* Syst. 53, 5 (2017), 709–759. https://doi.org/10.1007/s11241-017-9272-9
- [48] Angeliki Kritikakou, Claire Pagetti, Olivier Baldellon, Matthieu Roy, and Christine Rochange. 2014. Run-Time Control to Increase Task Parallelism In Mixed-Critical Systems. In 26th Euromicro Conference on Real-Time Systems, ECRTS 2014, Madrid, Spain, July 8-11, 2014. IEEE Computer Society, 119–128. https://doi.org/10.1109/ ECRTS.2014.14
- [49] Kai Lampka, Georgia Giannopoulou, Rodolfo Pellizzoni, Zheng Wu, and Nikolay Stoimenov. 2014. A formal approach to the WCRT analysis of multicore systems with memory contention under phase-structured task sets. *Real Time Syst.* 50, 5-6 (2014), 736–773. https://doi.org/10.1007/s11241-014-9211-y
- [50] Stephen Law and Iain Bate. 2016. Achieving Appropriate Test Coverage for Reliable Measurement-Based Timing Analysis. In 28th Euromicro Conference on Real-Time Systems, ECRTS 2016, Toulouse, France, July 5-8, 2016. IEEE Computer Society, 189–199. https://doi.org/10.1109/ECRTS.2016.21
- [51] Stephen Law, Iain Bate, and Benjamin Lesage. 2020. Justifying the Service Provided to Low Criticality Tasks in a Mixed Criticality System. In 28th International Conference on Real Time Networks and Systems, RTNS 2020, Paris, France, June 10, 2020, Liliana Cucu-Grosjean, Roberto Medina, Sebastian Altmeyer, and Jean-Luc Scharbarg (Eds.). ACM, 100–110. https://doi.org/10.1145/3394810. 3304814
- [52] Joseph Y.-T. Leung and Jennifer Whitehead. 1982. On the complexity of fixed-priority scheduling of periodic, real-time tasks. *Perform. Evaluation* 2, 4 (1982), 237–250. https://doi.org/10.1016/0166-5316(82)90024-4
- [53] Claire Maiza, Hamza Rihani, Juan Maria Rivas, Joël Goossens, Sebastian Altmeyer, and Robert I. Davis. 2019. A Survey of Timing Verification Techniques for Multi-Core Real-Time Systems. ACM Comput. Surv. 52, 3 (2019), 56:1–56:38. https://doi.org/10.1145/3323212
- [54] Dorin Maxim, Robert I. Davis, Liliana Cucu-Grosjean, and Arvind Easwaran. 2017. Probabilistic analysis for mixed criticality systems using fixed priority preemptive scheduling. In Proceedings of the 25th International Conference on Real-Time Networks and Systems, RTNS 2017, Grenoble, France, October 04 - 06, 2017, Enrico Bini and Claire Pagetti (Eds.). ACM, 237-246. https://doi.org/10. 1145/3139258.3139276

1452

1453

1455

1456

1457

1458

1459

1463

1464

1465

1466

1467

1468

1469

1470

1471

1472

1476

1477

1478

1479 1480

1481

1482

1483

1484

1489

1490

1491

1492

1493

1495

1496

1497

1503

1504

1505

1506

1507

1508

[55] Malcolm S. Mollison, Jeremy P. Erickson, James H. Anderson, Sanjoy K. Baruah, and John A. Scoredos. 2010. Mixed-Criticality Real-Time Scheduling for Multicore Systems. In 10th IEEE International Conference on Computer and Information Technology, CIT 2010, Bradford, West Yorkshire, UK, June 29-July 1, 2010. IEEE Computer Society, 1864–1871. https://doi.org/10.1109/CIT.2010.320

1393

1394

1395

1396

1397

1398

1399

1400

1401

1404

1405

1406

1407

1408

1409

1410

1411

1412

1413

1414

1415

1417

1418

1419

1420

1421

1423

1424

1425

1426

1427

1431

1432

1433

1434

1435

1437

1438

1439

1440

1444

1446

1447

1448

1449

1450

- [56] Jan Nowotsch and Michael Paulitsch. 2012. Leveraging Multi-core Computing Architectures in Avionics. In Ninth European Dependable Computing Conference, Sibiu, Romania, May 8-11, 2012, Cristian Constantinescu and Miguel P. Correia (Eds.). IEEE Computer Society, 132–143. https://doi.org/10.1109/EDCC.2012.27
- [57] Marco Paolieri, Eduardo Quiñones, Francisco J. Cazorla, Robert I. Davis, and Mateo Valero. 2011. IA'3: An Interference Aware Allocation Algorithm for Multicore Hard Real-Time Systems. In 17th IEEE Real-Time and Embedded Technology and Applications Symposium, RTAS 2011, Chicago, USA, 11-14 April 2011. IEEE Computer Society, 280–290. https://doi.org/10.1109/RTAS.2011.34
- [58] Ivan Pavic and Hrvoje Dzapo. 2020. Commentary to: An exact schedulability test for fixed-priority preemptive mixed-criticality real-time systems. Real Time Syst. 56, 1 (2020), 112–119. https://doi.org/10.1007/s11241-020-09345-0
- [59] Rodolfo Pellizzoni, Andreas Schranzhofer, Jian-Jia Chen, Marco Caccamo, and Lothar Thiele. 2010. Worst case delay analysis for memory interference in multicore systems. In *Design, Automation and Test in Europe, DATE 2010, Dresden, Germany, March 8-12, 2010,* Giovanni De Micheli, Bashir M. Al-Hashimi, Wolfgang Müller, and Enrico Macii (Eds.). IEEE Computer Society, 741–746. https://doi. org/10.1109/DATE.2010.5456952
- [60] Petar Radojkovic, Sylvain Girbal, Arnaud Grasset, Eduardo Quiñones, Sami Yehia, and Francisco J. Cazorla. 2012. On the evaluation of the impact of shared resources in multithreaded COTS processors in time-critical environments. ACM Trans. Archit. Code Optim. 8, 4 (2012), 34:1–34:25. https://doi.org/10.1145/2086696.
- [61] Rapita Systems. 2019. Multicore Timing Analysis for DO-178C. https://www.rapitasystems.com/downloads/multicore-timing-analysis-do-178c.
- [62] Hamza Rihani, Matthieu Moy, Claire Maiza, Robert I. Davis, and Sebastian Altmeyer. 2016. Response Time Analysis of Synchronous Data Flow Programs on a Many-Core Processor. In Proceedings of the 24th International Conference on Real-Time Networks and Systems, RTNS 2016, Brest, France, October 19-21, 2016, Alain Plantec, Frank Singhoff, Sébastien Faucou, and Luís Miguel Pinho (Eds.). ACM, 67-76. https://doi.org/10.1145/2997465.2997472

- [63] Simon Schliecker and Rolf Ernst. 2010. Real-time performance analysis of multiprocessor systems with shared memory. ACM Trans. Embed. Comput. Syst. 10, 2 (2010), 22:1–22:27. https://doi.org/10.1145/1880050.1880058
- [64] Andreas Schranzhofer, Rodolfo Pellizzoni, Jian-Jia Chen, Lothar Thiele, and Marco Caccamo. 2010. Worst-case response time analysis of resource access models in multi-core systems. In Proceedings of the 47th Design Automation Conference, DAC 2010, Anaheim, California, USA, July 13-18, 2010, Sachin S. Sapatnekar (Ed.). ACM, 332–337. https://doi.org/10.1145/1837274.1837359
- [65] Steve Vestal. 2007. Preemptive Scheduling of Multi-criticality Systems with Varying Degrees of Execution Time Assurance. In Proceedings of the 28th IEEE Real-Time Systems Symposium (RTSS 2007), 3-6 December 2007, Tucson, Arizona, USA. IEEE Computer Society, 239–243. https://doi.org/10.1109/RTSS.2007.47
- [66] Heechul Yun, Rodolfo Pellizzoni, and Prathap Kumar Valsan. 2015. Parallelism-Aware Memory Interference Delay Analysis for COTS Multicore Systems. In 27th Euromicro Conference on Real-Time Systems, ECRTS 2015, Lund, Sweden, July 8-10, 2015. IEEE Computer Society, 184–195. https://doi.org/10.1109/ECRTS.2015.24
- [67] Heechul Yun, Gang Yao, Rodolfo Pellizzoni, Marco Caccamo, and Lui Sha. 2012. Memory Access Control in Multiprocessor for Real-Time Systems with Mixed Criticality. In 24th Euromicro Conference on Real-Time Systems, ECRTS 2012, Pisa, Italy, July 11-13, 2012, Robert Davis (Ed.). IEEE Computer Society, 299–308. https://doi.org/10.1109/ECRTS.2012.32
- [68] Qingling Zhao, Zonghua Gu, and Haibo Zeng. 2013. PT-AMC: integrating preemption thresholds into mixed-criticality scheduling. In Design, Automation and Test in Europe, DATE 13, Grenoble, France, March 18-22, 2013, Enrico Macii (Ed.). EDA Consortium San Jose, CA, USA / ACM DL, 141-146. https://doi.org/ 10.7873/DATE.2013.042
- [69] Qingling Zhao, Zonghua Gu, Haibo Zeng, and Nenggan Zheng. 2018. Schedulability analysis and stack size minimization with preemption thresholds and mixed-criticality scheduling. J. Syst. Archit. 83 (2018), 57–74. https://doi.org/10.1016/j.sysarc.2017.03.007
- [70] Qingling Zhao, Mengfei Qu, Bo Huang, Zhe Jiang, and Haibo Zeng. 2022. Schedulability analysis and stack size minimization for adaptive mixed criticality scheduling with semi-Clairvoyance and preemption thresholds. J. Syst. Archit. 124 (2022), 102383. https://doi.org/10.1016/j.sysarc.2021.102383
- [71] Yecheng Zhao and Haibo Zeng. 2017. An efficient schedulability analysis for optimizing systems with adaptive mixed-criticality scheduling. *Real Time Syst.* 53, 4 (2017), 467–525. https://doi.org/10.1007/s11241-017-9267-6