UNIVERSITY of York

This is a repository copy of Absolute keV x-ray yield and conversion efficiency in over dense Si sub-petawatt laser plasma.

White Rose Research Online URL for this paper: <u>https://eprints.whiterose.ac.uk/191777/</u>

Version: Published Version

Article:

Ryazantsev, Sergey N., Martynenko, Artem S., Sedov, Maksim V. et al. (15 more authors) (2022) Absolute keV x-ray yield and conversion efficiency in over dense Si sub-petawatt laser plasma. Plasma Physics and Controlled Fusion. 105016. ISSN 1361-6587

https://doi.org/10.1088/1361-6587/ac8b33

Reuse

Items deposited in White Rose Research Online are protected by copyright, with all rights reserved unless indicated otherwise. They may be downloaded and/or printed for private study, or other acts as permitted by national copyright laws. The publisher or other rights holders may allow further reproduction and re-use of the full text version. This is indicated by the licence information on the White Rose Research Online record for the item.

Takedown

If you consider content in White Rose Research Online to be in breach of UK law, please notify us by emailing eprints@whiterose.ac.uk including the URL of the record and the reason for the withdrawal request.



eprints@whiterose.ac.uk https://eprints.whiterose.ac.uk/

QUERY FORM

JOURNAL: Plasma Physics and Controlled Fusion

AUTHOR: S N Ryazantsev et al

TITLE: Absolute keV x-ray yield and conversion efficiency in over dense Si sub-petawatt laser plasma

ARTICLE ID: ac8b33

Your article has been processed in line with the journal style. Your changes will be reviewed by the Production Editor, and any amendments that do not comply with journal style or grammatical correctness will not be applied and will not appear in the published article.

The layout of this article has not yet been finalized. Therefore this proof may contain columns that are not fully balanced/matched or overlapping text in inline equations; these issues will be resolved once the final corrections have been incorporated.

- Q1: Please check that the names of all authors as displayed in the proof are correct, and that all authors are linked to the correct affiliations. Please also confirm that the correct corresponding author has been indicated. Note that this is your last opportunity to review and amend this information before your article is published.
- Q2: If an explicit acknowledgment of funding is required, please ensure that it is indicated in your article. If you already have an Acknowledgments section, please check that the information there is complete and correct.
- Q3: We have been provided with ORCID iDs for the authors as below. Please confirm whether the numbers are correct. Sergey N Ryazantsev 0000-0002-9118-7952 Artem S Martynenko 0000-0001-6904-9601 Christopher D Baird 0000-0001-9973-7173 Paul McKenna 0000-0001-8061-7091 Christopher D Murphy 0000-0003-3849-3229 Nigel Woolsey 0000-0002-2444-9027
- Q4: Please be aware that the colour figures in this article will only appear in colour in the online version. If you require colour in the printed journal and have not previously arranged it, please contact the Production Editor now and refer to https://publishingsupport.iopscience.iop.org/questions/figures-journal-articles for pricing.
- Q5: A standard data availability statement has been added to your article, based on the information you gave in your submission. This text cannot be changed unless there is an error. Please remove any other data statement if the information is now duplicated. If the standard statement includes a link or DOI, please check that this is also an item in the reference list. If not, please provide the reference details (author, year, data title, repository name, link) and indicate where this reference should be cited in the text of your article.
- Q6: Please note that the Crossref and PubMed database have been used to validate the references and mismatches have been updated in the following references: [1–17, 19–26, 29, 30, 32–34, 38–41, 43]. Please check and confirm that these have been updated correctly.
- Q7: Please provide author names or collaboration name for reference [18].
- Q8: Publisher location is required for book reference [36]. Please provide the missing information.

Plasma Phys. Control. Fusion 0 (2022) xxxxxx (12pp)

Plasma Physics and Controlled Fusion

https://doi.org/10.1088/1361-6587/ac8b33

Absolute keV x-ray yield and conversion efficiency in over dense Si sub-petawatt laser plasma

Q1 Q2 Q3

Sergev N Rvazantsev^{1,2,*} . Artem S Martvnenko^{2,3} . Maksim V Sedov². Igor Yu Skobelev^{1,2}, Mikhail D Mishchenko^{2,4}, Yaroslav S Lavrinenko^{1,5} Christopher D Baird⁶, Nicola Booth⁷, Phil Durey⁶, Leonard N K Döhl⁶, Damon Farley⁶, Kathryn L Lancaster⁶, Paul McKenna⁸, Christopher D Murphy⁶, Tatiana A Pikuz^{2,9}, Christopher Spindloe⁷, Nigel Woolsey⁶ and Sergey A Pikuz^{1,2}

¹ National Research Nuclear University MEPhI (Moscow Engineering Physics Institute), 115409 Moscow, Russia

² Joint Institute for High Temperatures of the Russian Academy of Sciences, Moscow 125412, Russia ³ Plasma Physics Department, GSI Helmholtzzentrum fur Schwerionenforschung, 64291 Darmstadt,

Germany

⁴ European XFEL, 22869 Schenefeld, Germany

⁵ Moscow Institute of Physics and Technology, State University, 141701 Moscow, Russia

⁶ Department of Physics, York Plasma Institute, University of York, York YO10 5DD, United Kingdom

⁷ Central Laser Facility, STFC Rutherford Appleton Laboratory, Didcot OX11 0QX, United Kingdom

⁸ Department of Physics, SUPA, University of Strathclyde, Glasgow G4 0NG, United Kingdom

⁹ Open and Transdisciplinary Research Initiative, Osaka University, Osaka 565-0871, Japan

E-mail: SNRyazantsev@mephi.ru

Received 1 February 2022, revised 12 July 2022 Accepted for publication 19 August 2022 Published xx xx xxxx



Abstract

Laser-produced plasmas are bright, short sources of x-rays commonly used for time-resolved imaging and spectroscopy. Their usage implies accurate knowledge of laser-to-x-ray conversion efficiency (CE), spectrum, photon yield and angular distribution. Here, we report on soft x-ray emission in the direction close to the target normal from a thin Si foil irradiated by a sub-PW picosecond laser pulse. These absolute measurements cover a continuous and broad spectral range that extends from 4.75 to 7.5 Å (1.7–2.6 keV). The x-ray spectrum consists of spectral line transitions from highly charged ions and broadband emission with contributions from recombination and free-free processes that occur when electrons decelerate in plasma electromagnetic fields. Angular distribution of the emission was investigated via particle-in-cell simulations, which allowed to estimate the yield into the full solid angle. We find that experimental and simulation estimations of laser to free-free emission CE are in good agreement.

Keywords: PW laser plasma, absolute emissivity of laser plasma, crystal x-ray spectrometer, laser to x-rays conversion efficiency

04

(Some figures may appear in colour only in the online journal)

Author to whom any correspondence should be addressed.

1. Introduction

Plasmas produced by irradiation of different objects (flat foils [1-3], microstuctured surfaces [4, 5], wavelengthscale spheres [6], velvet surfaces [7], nanowires [8, 9], gas jets [10-12]) by intense laser pulses (Laser Produced Plasma, referred below as LPP) are widely used as an x-rays sources for both fundamental and applied research.

This is due to the possibility to precisely synchronise a measurement with phase of evolution of aprobed object and the relatively short duration of the emission. When nanosecond pulses are used, it is usually equal to their duration [13] and, in the case of picosecond pulses, exceeds it not by more than two orders of magnitude depending on laser intensity [1] or target type [7]. It should be noted, however, that the radiation from plasma sources generated by femtosecond pulses also can lasts up to several picoseconds [14]. Broadband emission sources are often needed for bioimaging and absorption spectroscopy. LPP at the table-top scale are used as x-ray sources in commercial applications [15] and at the very large scale in inertial confinement fusion (ICF) research as very bright x-ray backlighters for capsule explosions. Petawattclass (PW) lasers facilities (such as ARC [16] and PETAL [17] or others mentioned at table E.1 in [18]) which can produce picosecond pulses of about kJ are used for these purposes. Even for ICF experiments sources of soft x-rays are required. For example, low energy photons of <2 keV are used for the backlighting of direct-drive cryogenic DT implosions [19] due to the low opacity of the plastic shell and the deuterium-tritium fuel [20]. In addition, the low energy part of the spectrum of PW short-duration plasma sources spectrum is used to study warm-dense-matter by absorption spectroscopy [21].

These two applications, the imaging of an ICF experiment and diagnosis of warm-dense-matter, require a different spectral composition of the probe radiation. A source with a narrow emission band, ideally monochromatic, is required to acquire high-quality backlit images. Absorption spectroscopy, on the other hand, is most effective when using a radiation source with a continuous spectrum without spectral line features or sharp drops in intensity [22]. Both types of the probe radiation can be obtained using LPP due to different processes, which are shown in figure 1.

Plasma ions produce characteristic spectral lines during transitions of electrons between bound energy levels. For highly charged ions even with relatively low-Z (around 10) the lines are in the keV range of photon energy. Usually transitions from the excited state with principal quantum number n = 2 to the ground state in hydrogen-like (Ly_{\alpha}) and helium-like transition (He_{\alpha}) is at the appropriate wavelength for high-contrast quasi-monochromatic backlighting imaging [20, 23]. The plasma spectrum also contains lower intensity continuous emission from free-bound (photorecombination) and free-free (bremsstrahlung and synchrotron emission) transitions. Contributions of the individual process depend on element and irradiation conditions. Therefore a significant experimental effort is required to characterize LPP sources including those produced by picosecond PW pulses.

In this work we investigate the soft x-ray emission properties of a near solid density plasma generated in a Si foil by a sub-PW laser pulse. The aim of the work is to present exact values for the x-ray source photon yield in absolute units in the direction close to the target normal and briefly describe physical processes that contribute to the emission.

2. Experimental setup

The experimental investigation of the emissivity in soft x-ray range as a relativistic-intensity picosecond duration laser pulse strikes a Si foil was performed at the Vulcan PW laser facility [24]. A schematic representation of the experimental setup is shown in figure 1. The plasma was created by irradiating $2 \mu m$ thick Si foils by pulses of p-polarised laser radiation with wavelength $\lambda = 1.054 \mu m$. Duration of the pulses was $\tau = 1$ ps. The beam was focused by an off-axis parabolic mirror to a spot with a diameter of $\approx 7 \mu m$. Initial (measured before the compressor) energy of the used pulses was ≈ 350 J, but only about 60% (≈ 210 J) of it reached the target surface due to losses in different parts of the beam optical path including a plasma mirror [25] applied to enhance the laser pulse temporal contrast. The indicated parameters values corresponds to the pulse power P = 0.2 PW and intensity $I = 3 \times 10^{20}$ W cm⁻².

X-rays emitted from the front of the target during one laser shot was registered with three focusing spectrometers with spatial resolution (FSSR) [26] installed in directions close to the surface normal. Spherically bent α -quartz crystals with Miller indexes (*hkl*) (100) (interplanar spacing 2d = 8.512 Å) and (101) (2d = 6.666 Å) were used as disperse elements for them. Two FSSRs with the (100) crystals observed the overlapping wavelength ranges 5–6.8 and 6.5–7.4 Å. The third one with the (101) crystal was aligned to register photons with wavelength from 4.75 to 6 Å. Dispersion schemes chosen for the spectrometers provided spectral and spatial resolution of $\lambda/\Delta\lambda \approx 0.5 \times 10^4$ and $\Delta X \approx 100 \ \mu$ m/pixel correspondingly. All the spectrometers were shielded against spurious radiation generated by the electrons from the interaction point as they hit the chamber walls, optical posts, and so on. Two of the FSSRs were in housings made of 5 mm lead with small windows in the direction of the target crystal. The third FSSR was installed in a separate vacuum chamber connected to the main chamber by a narrow tube with its axis oriented towards the target. Also, 0.5 T neodymium-iron-boron permanent magnets were installed between the FSSR crystals and the interaction point. As a result, the electrons accelerated towards the crystals could not reach them if their kinetic energy was less than 50 MeV. Fujifilm BAS-TR image plates (IPs) and Andor CCD DX-434 (only for one of the spectrometers) were used as x-ray detectors. The IPs were covered by two layers of 1 μ m thick polypropylene $(C_3H_6)_n$ with a thin $(0.2 \ \mu m)$ layer of Al evaporated on it or by 25 μ m thick beryllium film. The CCD sensor was shielded by a 25 μ m Be foil for all the shots. The slits of



Figure 1. Experimental setup and schematic of the processes that form the shape of the plasma soft x-ray radiation spectrum registered in the experiments.

the magnets were also covered by a single layer of 5 μ m Mylar (C₁₀H₈O₄) to avoid detector saturation.

The spectrometers observation ranges overlap to provide cross-calibration between the FSSRs. This enabled the measurement of continuous and high-resolution spectra over photon wavelengths from 4.7 to 7.3 Å (1.7 to 2.6 keV). The raw spectra registered by the individual FSSR spectrometers are shown in figure 2(a).

All data registered with the FSSRs were corrected for filtering, crystal reflectivity and detector response functions. Reflectivity was calculated by numerical modelling as described in [27] by ray tracing through the spectrometer. The actual crystallographic rocking curves of the spherically bent crystals installed in the FSSRs were used for it. They were calculated with the software XOP [28] and presented in appendix together with sensitivity functions of the IPs. Transmission functions for the filters foils were calculated using the Henke tables [29]. A summary of the response functions for each spectrometer is shown in figure 2(b). After convolution of the registered signal with them an initial plasma radiation spectrum shape was restored (figure 2(c)). Consideration of the equipment response function allowed to scale the intensity (vertical axis in the figure) in absolute units of photons $Å^{-1}$ sr⁻¹. Thus it represents the emissivity of the source radiation in the direction of the spectrometers crystals (close to the targets normal). The most significant corrections were needed around the Si K-edge at 6.7135 Å [30]. This causes a drop in reflectivity of the α -quartz (SiO₂) crystals in the wavelength range close to the He_{α} line.

3. Discussion

The spectrum shown in figure 2(c) contains both characteristic and continuous emission components. Its shape is formed by all types of electron transitions: free-free, free-bound, boundbound (figure 1). The characteristic emission of plasma ions is produced by transitions between energy states of H- and Helike Si ions. All the corresponding spectral lines are broadened due to the strong Stark effect. Their experimental shape is correctly reproduced (figure 3) by a theoretical spectrum simulated for the plasma electron temperature $T_e = 650$ eV and electron density of 4×10^{23} cm⁻³, which is about 60% of Si solid density value $N_{SS} \approx 6 \times 10^{23}$ cm⁻³. It was achieved due to the extremely high value of the laser pulse temporal contrast of 10^{10} additionally enhanced by the plasma mirror.

The most intense line is the Ly_{α} (2p \rightarrow 1s transition in an H-like ion). Emissivity of the source in this line (the narrow wavelength range from 6.05 to 6.35 Å, 1.95–2.05 keV, which contains the line itself and its dielectronic satellites) in the direction close to the targets normal is about 1.7×10^{13} photons sr⁻¹. This part of the plasma spectrum is best suited for implementation of quasi-monochromatic backlights schemes. The value for the broad peak indicated in the figure as He_{α} (range from 6.53 to 6.89 Å, 1.8–1.9 keV) is $\approx 0.8 \times 10^{13}$ photons sr⁻¹. In fact, this spectral region con-tains overlapping He_{α} (1s2p ¹P₁ \rightarrow 1s2 ¹S₀ in He-like ions), intercombination line $(1s2p {}^{3}P_{2,1} \rightarrow 1s^{2} {}^{1}S_{0})$ and dielectronic satellites emitted by Li-like ions. Note that the peak to the left of the intensity drop caused by the K-edge is not the intercombination line. This is an artefact of registration previously observed for the spectrometers used in the experiments. Emissivities of the source in the Ly_{β} (3p \rightarrow 1s) and ${\rm He}_{\beta}(1s3p~^1P_1 \rightarrow 1s^2~^1S_0)$ lines are 0.4 $\times~10^{13}$ and 0.6 $\times~$ 10^{13} photons sr⁻¹ respectively. In comparison the K_{α} line at 7.12 Å is weak as most of the Si is highly ionised. The indicated numbers correspond to a conversion efficiency (CE) of laser pulse energy to He_{α} , Ly_{α} , Ly_{β} , He_{β} lines emission in the direction close to the target normal as $\approx 1.2 \times 10^{-5} \text{ sr}^{-1}$, (a)



Figure 2. (a)—Normalized experimental emission spectra registered by the FSSRs from the front side of Si foil before convolution with the spectrometer route response functions $\chi(\lambda)$ shown in (b). $\chi(\lambda)$ is a ratio of the number of registered photons of λ wavelength to the one emitted by the source. (c)—Combined experimental emission spectrum after convolution with $\chi(\lambda)$. The blue and purple polygons qualitatively demonstrate contributions of bremsstrahlung, synchrotron emission and recombination continuum. Shape of the latter one was calculated for solid-state Si plasma ($N_i = 6 \times 10^{22} \text{ cm}^{-3}$).



Figure 3. Comparison of Ly_{α} line shape registered in the experiments with that calculated theoretically for the fixed electron temperature $T_e = 650 \text{ eV}$ and different ion densities: $N_e = 1 \times 10^{23}$ (blue line), 3×10^{23} (green) and 5×10^{23} cm⁻³ (orange). For the calculations it was assumed that the plasma has a linear size of 3 μ m. The simulated spectra were obtained with PrismSPECT software [31].

 \approx 2.5 × 10⁻⁵ sr⁻¹, \approx 0.75 × 10⁻⁵ sr⁻¹, \approx 1.0 × 10⁻⁵ sr⁻¹ respectively.

In the short wavelength part of the spectrum there is a pedestal. It results from the recombination continuum produced by free-bound transitions of plasma electrons. Spectral lines corresponding to $4p\rightarrow1s$ transitions in H- and He-like ions should be registered in this range, but they are suppressed due to ionization potential depression [32] in the dense plasma. The shape of the recombination continuum calculated using the Hummer–Mihalas [33] model for He- and H-like ions in a solid-density Si plasma is shown in figure 2(c) by the magenta area. Simulations indicate that the recombination continuum extends to 2 Å. Quite high yield (average value is $\approx3 \times 10^{13}$ photons Å⁻¹ sr⁻¹) value and absence of any spectral lines makes the recombination continuum part of the spectrum very suitable for x-ray absorption spectroscopy in the range $\leqslant 5$ Å.

Another part of the continuous emission arose from freefree processes. They contribute to the spectrum through a monotonic growth in intensity in the long wavelength part. It is approximated by an exponential function shown by the blue line in figure 2(c). An area under this curve gives an estimation for an amount of energy associated with free-free emission is $E_{cont} = 5$ mJ sr⁻¹ E_{cont} , which corresponds to CE of 2.5×10^{-5} sr⁻¹.

It is also possible to estimate a ratio $CE_{4\pi}$ of the energy emitted in the full solid angle 4π to the energy of the incident laser pulse. For bremsstrahlung and synchrotron emission it can be done semi-analytically on the base of electron energy distribution numerically obtained by particle-in-cell (PIC) simulations. We have performed two-dimensional (2D) PIC simulation via the EPOCH [34] code.

All the modelling parameters were chosen close to experimental conditions: laser wavelength $\lambda_{laser} = 1.054 \ \mu m$, focal spot radius 4 μm , angle of incidence $\alpha = 45^{\circ}$, intensity $I_{las} = 3 \times 10^{20}$ W cm⁻². The laser pulse had Gaussian spatial and 3rd order super-Gauss temporal profile (figure 4(a)). A 2 μm thick layer of fully ionized Si ions with solid-state density (5 $\times 10^{22}$ ions cm³) was used as a target. A long laser pulse requires a large simulation box to accurately describe the laser-target interaction and to accommodate the expanding plasma. In our simulations the box size was $120 \times 120 \ \mu m$ with $10 \times 10 \ nm$ grid. The simulation included a current smoothing algorithm and third order particle weighting to limit noise and numerical heating. All boundary conditions were absorbing for radiation and thermalizing for particles.

For an accurate description of the interaction of a laser pulse with a solid target, it is necessary that the minimum achievable particle density in the calculation (1 macro particle in 1 cell) be less than the critical density. On the other hand, at the edge of the simulation area particles will never interact with the laser pulse. They are needed only to maintain the quasineutrality of the plasma via the return current. Specifying a large number of macro particles for all cells in the target is a waste of computational resources. Therefore, in order to save computational time, the target was conditionally divided into several zones (figure 4(b)). The central zone 1 had 50 macro ion particles and 50 × 14 macro electron particles (1 macro electron in 1 cell corresponds to $0.9 n_{cr}$) in each cell, zone 2 had half the number of macro particles in each cell (25 ions and



Figure 4. (a)—Temporal profile of the laser pulse used in PIC simulations. (b)—Scheme of dividing the target into zones with different numbers of macroparticles.

 25×14 electrons) and zone 3 had 10 macro ion particles and 10×14 macro electron particles in each cell, respectively. The boundary of zone 1 was chosen from the condition that during the simulation time ($\tilde{1}.1$ ps) the electrons from zone 2 did not reach the focal spot.

The electron energy spectrum predicted by the PIC simulations is shown in figure 5(a). It can be roughly reproduced by a sum of three Maxwell distributions with temperatures of 5, 80 and 650 keV and electron densities $N_e = 3 \times 10^{13}$, 9×10^{13} , 1.5×10^{13} cm⁻³ respectively. On the base of these values it is possible to estimate amount of energy emitted as Bremsstrahlung and synchrotron radiation using modified Kramers formula (1) from [35] and the classical expression (2) from [36] correspondingly:

$$dI_{Brems}(E) = C \frac{Z^2 N_i n_e}{\sqrt{T_e}} \exp\left(-\frac{E}{T_e}\right) dE; C = \frac{16}{3} \sqrt{\frac{2\pi}{0.5}} \frac{e^6}{m_e^{3/2} c_s^3},$$
(1)
$$dI_{syncro}(E) = \frac{\sqrt{3}}{2\pi} \frac{e^3 H}{m_e c^2} F\left(\frac{E}{E_c}\right) dE; F(\xi) = \int_{\xi}^{\infty} K_{\frac{5}{3}}(\xi) d\xi,$$
(2)

where Z—atomic number of the target atoms, N_i —ion density $(6 \times 10^{22} \text{ cm}^{-3})$, n_e —number of electrons, T_e —electron temperature in eV, g^{ff} —Gaunt factor, e and m_e —electron charge and mass, c—speed of light, H—magnetic field (considered as constant calculated as $\sqrt{\frac{2I}{c}} = 4.5 \times 10^8 \text{ G}$), K is the modified Bessel function of the second type and E_c is an energy around which the emission of an electron with energy T_e is concentrated:

$$E_c = \hbar\omega_c; \omega_c = \frac{3eH}{2m_e c} \left(\frac{T_e}{m_e c^2}\right)^2.$$
(3)

It should be noted that according to (3) only electrons with energy ≥ 6 MeV make a significant contribution in the energy range detected by our spectrometers.

Integrating of (1) and (2) over the range of photon energies observed in the experiments gives the values of 0.1 and 0.3 J for the Bremsstrahlung and synchrotron emission, respectively. Dividing by the energy of the laser pulse used in the experiment (210 J) gives CE $_{4\pi}$ values $\eta_{Brems} = 3.3 \times 10^{-4}$ and $\eta_{syncro} = 1 \times 10^{-3}$. The EPOCH code itself able to simulate spectrum (figure 5(b)) and angular distribution (figure 5(c)) of bremsstrahlung and synchrotron emission on the base of principles described in [37–39] and predict values for CE_{4 π}. It gives $\eta_{Brems}^{4\pi} = 3.4 \times 10^{-4}$ and $\eta_{syncro}^{4\pi} = 1.3 \times 10^{-4}$. Such a significant discrepancy for the synchrotron emission CEs is caused by using a fixed value of the magnetic field for the analytical estimation based on the (2).

The predicted by PIC simulations angular distribution (figure 5(c)) is not isotropic, because absorption within the target occurs in the direction parallel to the surface of the target $(45^{\circ}-235^{\circ}$ direction). The simulated distribution together with the experimental value for the energy of the emission associated with free-free transitions registered by the spectrometers allows to estimate the total energy emitted by the source in full solid angle 4π as bremsstrahlung and syncrotron emission. The obtained values is $E_{cont} \approx 33$ mJ, which is $\approx 52\%$ of that obtained assuming an isotropic angular distribution. The corresponding $CE_{4\pi}$ value is 1.6×10^{-4} , which is about three times less than predicted by the PIC simulation. Impacts of the two types of free-free emission are indistinguishable in the experimental spectrum. Therefore, it is impossible to give separate estimates for their CEs. Nevertheless, according to the PIC results syncrotron emission should be less intense than bremsstrahlung for all the directions and the E_{cont} is distributed between them as 1:2.6.



Figure 5. (a)—Electron energy distribution retrieved from PIC simulations for different moments of the laser-target interaction; (b)—spectra of bremsstrahlung and synchrotron emission retrieved from the PIC simulation; (c)—numerically calculated angular distribution of bremsstrahlung (magenta curve) and synchrotron radiation (blue) emitted in the 4.8–7.3 Å (1.7–2.6 keV) wavelength range by a 2 μ m thick layer of fully ionized Si ions with solid-state density irradiated by a subpicosecond laser pulse with intensity 3 × 10²⁰ W cm⁻². The solid green curve is the sum of two components. The dashed green line represents the sum, when all the absorption processes were excluded from the simulations.

It can be assumed that the angular distribution for the line emission of the source also has a 'dipole' shape. Under this assumption it is possible to estimate $CE_{4\pi}$ in separate spectral lines. The values are $\approx 0.8 \times 10^{-4}$, $\approx 1.6 \times 10^{-4}$, $\approx 0.5 \times 10^{-4}$, $\approx 0.5 \times 10^{-4}$ for He_{α}, Ly_{α}, Ly_{β}, He_{β} respectively. It the presented values are comparable with results reported by other research groups. For example, in experiments with Ag/Cu foils [40, 41] carried out at the same laser facility but under slightly different conditions, values of 1–2 $\times 10^{-4}$ were obtained for the spectral lines Ag K_{α} ($E_{ph} = 22.4$ keV, $\lambda = 0.553$ Å) and Cu K_{α} ($E_{ph} = 1.54$ keV, $\lambda = 8.04$ Å).

4. Conclusions

The laser plasma produced by the sub-PW (1 ps, 210 J, 210 TW, with focal spot diameter 7 μ m, and on target intensity 3×10^{20} W cm⁻², angle of incidence is 45°) laser pulse in a 2 μ m thick Si foil is a very bright source of soft x-rays. In the direction close to the targets normal we registered emissivity of $\approx 8 \times 10^{13}$ photons sr⁻¹ (≈ 0.03 J sr⁻¹) in the wavelength range of 4.75–7.3 Å (1.7–2.6 keV), which corresponds to the CE of $\approx 1.2 \times 10^{-4}$ sr⁻¹. About half of the energy were emitted in Si XIV (Si¹³⁺) Ly_{\alpha}, Ly_{\beta} and Si XIII (Si¹²⁺) He_{\alpha} and He_{\beta} resonance spectral lines and its dielectonic satellites.

 Ly_{α} line is the most intense spectral line containing about a half of all emitted photons. This makes this lin Ly_{α} line the best choice for quasi-monochromatic x-ray backlighter imaging and is sufficiently bright for use in appoint-project Bragg crystal imaging system.

Emissivity of the source in continuous emission in direction close to the target normal is \approx 13.6 mJ sr⁻¹ (CE \approx 0.7 \times 10^{-4}). $\approx 5 \text{ mJ sr}^{-1}$ (CE $\approx 0.25 \times 10^{-4}$) of it corresponds to free-free (bremsstrahlung and synctrotron) radiation. The rest is associated with recombination continuum emission. Such a high value of emissivity in such type of continuous emission together with absence of spectral lines makes the investigated source very suitable for absorption spectroscopy purposes. The value of $CE_{4\pi}$ (a ratio between the energy emitted by the source in the full solid angle 4π and the energy of the laser pulse) in free-free emission estimated on the base of the simulated angular distribution and the experimentally measured emissivity is 1.6×10^{-4} . This is three times less than the value obtained directly from the code EPOCH. The difference of less than one order leads to the conclusion that the code reproduces processes at the interaction point quite well.

Data availability statement

The data that support the findings of this study are available upon reasonable request from the authors.

Acknowledgments

The work was performed in the period from December 2019 to August 2021. The authors would like to thank the Central Laser Facility staff, whose dedication and expertise were essential to the success of their experiment. Calculations were carried out on the computational resources of the JSCC RAS. The reported study was funded by RFBR, Project Number 19-32-60050. This study was done in the frame of the State Assignment to JIHT RAS (topic #075-00892-20-00). The work of UK team received financial support from UK EPSRC Grants EP/P026796/1, EP/L01663X/1 and EP/H012605/1.

Appendix A. Recalculation of raw data counts to number of real photons

Raw data recorded by the Fuji BAS TR IPs (below) detectors in the experiments is a 2D matrix of numbers. Each of them is proportional to a dose absorbed by a certain pixel of the detector. This matrix can be represented in a form of a grayscale image shown in figure A1. The spectrum is a profile along the bright narrow field in the centre of the image. This zone has a non-zero width in pixels, so each dot of the spectrum is a sum along the vertical axis.

The data from IPs were digitized via Fujifilm FLA 5100 scanner. A raw image produced as a result of scanning is scaled in arbitrary units (counts), which are related with absolute units called PSL (Photostimulated Luminescence) by the equation (A.1) [42]:

$$PSL = \left(\frac{R}{100}\right)^2 \left(\frac{400}{S}\right) 10^{L\left(\frac{G}{2^B - 1} - \frac{1}{2}\right)}, \qquad (A.1)$$

where *R* is the resolution in microns, *S* is a sensitivity setting, *L* is latitude, *B* is a dynamic range in bits, *G* is the raw image grayscale value, which is sometimes mentioned as a quantum yield. We used the following values for scanning: R = 25, S = 5000, L = 5, B = 16. It should be noted that the countsto-PSL recalculation function can be significantly different for other scanner models. For example, for General Electric Typhoon FLA 7000 the equation can be found in [43]. The values in PSL were recalculated to a number of photons with a given wavelength on the base of a calibration curve shown in figure A2.



Figure A1. An example of an experimental x-ray emission spectrum registered by the IP detector installed in the FSSR.



Figure A2. Sensitivity of Fuji BAS TR IPs in the soft x-ray range from [42] fitted by a hyperbola function.

Appendix B. Crystal reflectivity

The corrections associated with crystal reflectivity (CR) were also considered during spectra restoring process. The CR function here is N_r/N_e , where N_r and N_e are numbers of photons reflected by a crystal and emitted by a source, correspondingly. It depends on a solid angle covered by the spectrometer crystal (Ω_{cr}) and also on its rocking curves (diffraction profiles). Ω_{cr} was calculated directly from the distance between the source and the crystals and the surface dimensions of the latter ones. Rocking curves were obtained by the x-ray Oriented Programs (XOP) [28]. This software allowed to simulate diffraction properties of spherically-bent crystals on the base of extended dynamical theory, which is fully described, for example, in [44]. The calculated rocking curves are shown in figure B1. The curves were taken into account in a numerical simulation (modelling principles are described in [27]) of rays propagation through the spectrometers optical schemes. They were considered as profiles of probability for a photon with given energy and incidence angle to be reflected by spherically bent crystals of the FSSRs.



Figure B1. Set of rocking curves presented as a 3D surface calculated by the XOP software for spherically bent α -quartz crystals with Miller indexes (a) (100) and (b) (101) for the range of wavelengths observed in the experiments. For (101) the data is not presented for $\lambda > 6.666$ Å, because the crystal is not able to reflect photons with a wavelength longer than its interplanar spacing 2d = 6.666 Å. Dependence of the peaks amplitude (peak reflectivity for a particular wavelength) and FWHM are given on the planes (c) and (d) correspondingly: red line for (100), blue line for (101).

ORCID iDs

Sergey N Ryazantsev () https://orcid.org/0000-0002-9118-7952

Artem S Martynenko D https://orcid.org/0000-0001-6904-9601

Christopher D Baird D https://orcid.org/0000-0001-9973-7173

Paul McKenna b https://orcid.org/0000-0001-8061-7091 Christopher D Murphy b https://orcid.org/0000-0003-3849-3229

Nigel Woolsey D https://orcid.org/0000-0002-2444-9027

References

 Workman J, Maksimchuk A, Liu X, Ellenberger U, Coe J S, Chien C-Y and Umstadter D 1996 Picosecond soft-x-ray source from subpicosecond laser-produced plasmas *J. Opt. Soc. Am.* B 13 125

Q6

- [2] Wharton K B, Boley C D, Komashko A M, Rubenchik A M, Zweiback J, Crane J, Hays G, Cowan T E and Ditmire T 2001 Effects of nonionizing prepulses in high-intensity laser-solid interactions *Phys. Rev.* E 64 025401
- [3] Riley D, Angulo-Gareta J J, Khattak F Y, Lamb M J, Foster P S, Divall E J, Hooker C J, Langley A J, Clarke R J and Neely D 2005 K_{α} yields from Ti foils irradiated with ultrashort laser pulses *Phys. Rev.* E **71** 016406

- [4] Murnane M M, Kapteyn H C, Gordon S P, Bokor J, Glytsis E N and Falcone R W 1993 Efficient coupling of high-intensity subpicosecond laser pulses into solids *Appl. Phys. Lett.* **62** 1068–70
- [5] Kahaly S, Yadav S K, Wang W M, Sengupta S, Sheng Z M, Das A, Kaw P K and Kumar G R 2008 Near-complete absorption of intense, ultrashort laser light by sub- λ gratings *Phys. Rev. Lett.* **101** 145001
- [6] Sumeruk H A, Kneip S, Symes D R, Churina I V, Belolipetski A V, Donnelly T D and Ditmire T 2007 Control of strong-laser-field coupling to electrons in solid targets with wavelength-scale spheres *Phys. Rev. Lett.* **98** 045001
- [7] Kulcsár G, AlMawlawi D, Budnik F W, Herman P R, Moskovits M, Zhao L and Marjoribanks R S 2000 Intense picosecond x-ray pulses from laser plasmas by use of nanostructured "Velvet" targets *Phys. Rev. Lett.* 84 5149–52
- [8] Ovchinnikov A, Kostenko O, Chefonov O, Rosmej O, Andreev N, Agranat M, Duan J, Liu J and Fortov V 2011 Characteristic x-rays generation under the action of femtosecond laser pulses on nano-structured targets *Laser Part. Beams* 29 249–54
- [9] Hollinger R *et al* 2017 Efficient picosecond x-ray pulse generation from plasmas in the radiation dominated regime *Optica* 4 1344
- [10] Schultz K A *et al* 2019 Study of pure and mixed clustered noble gas puffs irradiated with a high intensity (7 × 10¹⁹ W/cm²) sub-ps laser beam and achievement of a strong x-ray flash in a laser-generated debris-free x-ray source *Laser Part. Beams* **37** 276–87
- [11] Kantsyrev V et al 2016 Study of x-rays produced from debris-free sources with Ar, Kr and Kr/Ar mixture linear gas jets irradiated by UNR Leopard laser beam with fs and ns pulse duration *High Energy Density Phys.* 19 11–22
- [12] Kantsyrev V L et al 2016 Influence of Xe and Kr impurities on x-ray yield from debris-free plasma x-ray sources with an Ar supersonic gas jet irradiated by femtosecond near-infrared-wavelength laser pulses Phys. Rev. E 94 053203
- [13] Hu G-Y et al 2008 Angular distribution and conversion of multi-keV L-shell x-ray sources produced from nanosecond laser irradiated thick-foil targets Laser Part. Beams 26 661–70
- [14] Rathore R, Arora V, Singhal H, Mandal T, Chakera J and Naik P 2017 Experimental and numerical study of ultra-short laser-produced collimated Cu K α x-ray source Laser Part. Beams 35 442–9
- [15] Kleine C et al 2019 Soft x-ray absorption spectroscopy of aqueous solutions using a table-top femtosecond soft x-ray source J. Phys. Chem. Lett. 10 52–58
- [16] Khan S F et al 2021 A dual high-energy radiography platform with 15 μm resolution at the national ignition facility *Rev. Sci. Instrum.* 92 043712
- [17] Casner A et al 2015 LMJ/PETAL laser facility: overview and opportunities for laboratory astrophysics High Energy Density Phys. 17 2–11
- [18] 2018 Opportunities in Intense Ultrafast Lasers (Washington, DC: National Academies Press) (available at: www.nap.edu/catalog/24939)
- [19] Sangster T C et al 2007 Cryogenic DT and D2 targets for inertial confinement fusion Phys. Plasmas 14 058101

07

- [20] Stoeckl C et al 2014 Soft x-ray backlighting of cryogenic implosions using a narrowband crystal imaging system (invited) Rev. Sci. Instrum. 85 11E501
- [21] McGuffey C et al 2018 Soft x-ray backlighter source driven by a short-pulse laser for pump-probe characterization of warm dense matter *Rev. Sci. Instrum.* 89 10F122
- [22] Martynenko A S *et al* 2021 Optimization of a laser plasma-based x-ray source according to WDM absorption

spectroscopy requirements *Matter Radiat. Extremes* 6 014405

- [23] Loupias B, Perez F, Benuzzi-Mounaix A, Ozaki N, Rabec M, Gloahec L, Pikuz T, Faenov A, Aglitskiy Y and Koenig M 2009 Highly efficient, easily spectrally tunable x-ray backlighting for the study of extreme matter states *Laser Part. Beams* 27 601–9
- [24] Danson C et al 2004 Vulcan petawatt—an ultra-high-intensity interaction facility Nucl. Fusion 44 S239–46
- [25] Scott G G et al 2015 Optimization of plasma mirror reflectivity and optical quality using double laser pulses *New J. Phys.* 17 033027
- [26] Faenov A Y, Pikuz S A, Erko A I, Bryunetkin B A, Dyakin V M, Ivanenkov G V, Mingaleev A R, Pikuz T A, Romanova V M and Shelkovenko T A 1994 High-performance x-ray spectroscopic devices for plasma microsources investigations *Phys. Scr.* 50 333–8
- [27] Lavrinenko Y S, Morozov I V, Pikuz S A and Skobelev I Y 2015 Reflectivity and imaging capabilities of spherically bent crystals studied by ray-tracing simulations J. Phys.: Conf. Ser. 653 12027
- [28] Sánchez del Río M and Dejus R J 2011 XOP v2.4: recent developments of the x-ray optics software toolkit *Proc.* SPIE 8141 814115
- [29] Henke B, Gullikson E and Davis J 1993 X-ray interactions: photoabsorption, scattering, transmission and reflection at E = 50-30,000 eV, Z = 1-92 At. Data Nucl. Data Tables 54 181-342
- [30] Li D, Bancroft G, Fleet M and Feng X H 1995 Silicon K-edge XANES spectra of silicate minerals *Phys. Chem. Miner.* 22 115–22
- [31] Macfarlane J J, Golovkin I E, Woodruff P R, Welch D R, Oliver B V, Melhorn T A and Campbell R B 2004 Simulation of the ionization dynamics of aluminum irradiated by intense short-pulse lasers *Inertial Fusion Sciences and Applications 2003 (IFSA 2003): State of the Art 2003* ed B A Hammel, D Meyerhofer, J Meyer-ter Vehn and H Azechi (La Grange Park, IL: American Nuclear Society) p 457
- [32] Hoarty D J et al 2013 Observations of the effect of ionization-potential depression in hot dense plasma Phys. Rev. Lett. 110 265003
- [33] Hummer D G and Mihalas D 1988 The equation of state for stellar envelopes. I—an occupation probability formalism for the truncation of internal partition functions *Astrophys. J.* 331 794
- [34] Arber T D *et al* 2015 Contemporary particle-in-cell approach to laser-plasma modelling *Plasma Phys. Control. Fusion* 57 113001
- [35] Raizer Y 1991 Gas Discharge Physics (Berlin: Springer)
- [36] Landau L D and Lifshitz E 1985 *The Classical Theory of Fields* vol 2 (Butterworth-Heinemann)
- [37] Vyskočil J, Klimo O and Weber S 2018 Simulations of bremsstrahlung emission in ultra-intense laser interactions with foil targets *Plasma Phys. Control. Fusion* 60 054013
- [38] Duclous R, Kirk J G and Bell A R 2011 Monte Carlo calculations of pair production in high-intensity laser-plasma interactions *Plasma Phys. Control. Fusion* 53 015009
- [39] Elkina N V, Fedotov A M, Kostyukov I Y, Legkov M V, Narozhny N B, Nerush E N and Ruhl H 2011 QED cascades induced by circularly polarized laser fields *Phys. Rev. Spec. Top. Accel. Beams* 14 054401
- [40] Park H-S, Izumi N, Key M H, Koch J A, Landen O L, Patel P K, Phillips T W and Zhang B B 2004 Characteristics of high energy $K\alpha$ and Bremsstrahlung sources generated

by short pulse petawatt lasers *Rev. Sci. Instrum.* **75** 4048–50

- [41] Park H-S et al 2006 High-energy Kα radiography using high-intensity, short-pulse lasers Phys. Plasmas 13 056309
- [42] Haugh M J, Lee J, Romano E and Schneider M 2013
 Calibrating image plate sensitivity in the 700 to 5000 eV spectral energy range *Proc. SPIE* 8850 885007
- [43] Golovin D, Mirfayzi S, Shokita S, Abe Y, Lan Z, Arikawa Y, Morace A, Pikuz T and Yogo A 2021 Calibration of imaging plates sensitivity to high energy photons and ions for laser-plasma interaction sources *J. Instrum.* 16 T02005
- [44] Authier A 2003 Dynamical Theory of X-Ray Diffraction (Oxford: Oxford University Press)