



Deposited via The University of Leeds.

White Rose Research Online URL for this paper:

<https://eprints.whiterose.ac.uk/id/eprint/79036/>

Version: Accepted Version

Proceedings Paper:

McDonagh, A, Sextro, RG and Byrne, MA Mass transport of deposited aerosol particles by surface-to-surface contact and its implications for aerosol-borne disease transmission. In: UNSPECIFIED American Association for Aerosol Research (AAAR) 29th Annual Conference, 25-29 Oct 2010, Portland, Oregon, USA.

Reuse

Items deposited in White Rose Research Online are protected by copyright, with all rights reserved unless indicated otherwise. They may be downloaded and/or printed for private study, or other acts as permitted by national copyright laws. The publisher or other rights holders may allow further reproduction and re-use of the full text version. This is indicated by the licence information on the White Rose Research Online record for the item.

Takedown

If you consider content in White Rose Research Online to be in breach of UK law, please notify us by emailing eprints@whiterose.ac.uk including the URL of the record and the reason for the withdrawal request.

**Mass Transport of Deposited Aerosol Particles by
Surface-to-Surface Contact and its Implications for
Aerosol-Borne Disease Transmission**

McDonagh A., Sextro R.G. and Byrne M.A

The spread of deposited aerosol particles from one surface to another via contact transfer, is an important factor in assessing the exposure pathways of airborne contaminants. Surface to surface contact transfer is thought to be one of the mechanisms for the spread of infectious diseases.

A study was conducted with the aim of quantifying the mass transfer efficiency of deposited aerosol particles when selected surfaces come in contact. A matrix of four variables was investigated; different surface pairs, applied pressure, contact time and contaminant loading. Among these, the variable with the greatest influence on mass transfer efficiency was the choice of surface pairs. Two types of surfaces were investigated, two soft surfaces – 100 % cotton and synthetic fleece – and two hard surfaces – brass and plastic laminate. The lowest mass transfer efficiency was observed for transfer from contaminated fleece to plastic laminate, ~ 2 %, and the highest efficiencies were seen for transfers from the two hard surfaces, brass and plastic laminate, to fleece, 41 and 30 % respectively. Other observations include an increase in the mass transferred with increased surface roughness. An increase in the applied pressure between the two surfaces in contact leads to a step change in transfer efficiency, so that two pressure regimes can be identified, with a transition pressure between them that depends on surface type. Time of

contact and contaminant loading appear to have little to no effect on the mass transfer efficiency for the surfaces studied.

Overall, contact transfer efficiencies ranging from 2 to 45 % were observed; these are very significant numbers in terms of hazardous aerosol transport in the environment. These experiments were designed as an initial quantitative exploration using a limited number of surfaces and study variables.