



This is a repository copy of *Guest editorial: characterisation of crack tip fields*.

White Rose Research Online URL for this paper:  
<http://eprints.whiterose.ac.uk/106796/>

Version: Accepted Version

---

**Article:**

Susmel, L. [orcid.org/0000-0001-7753-9176](https://orcid.org/0000-0001-7753-9176), James, M.N., Hong, Y. et al. (1 more author) (2016) Guest editorial: characterisation of crack tip fields. *Fatigue & Fracture of Engineering Materials & Structures*, 39 (8). p. 923. ISSN 8756-758X

<https://doi.org/10.1111/ffe.12451>

---

**Reuse**

Unless indicated otherwise, fulltext items are protected by copyright with all rights reserved. The copyright exception in section 29 of the Copyright, Designs and Patents Act 1988 allows the making of a single copy solely for the purpose of non-commercial research or private study within the limits of fair dealing. The publisher or other rights-holder may allow further reproduction and re-use of this version - refer to the White Rose Research Online record for this item. Where records identify the publisher as the copyright holder, users can verify any specific terms of use on the publisher's website.

**Takedown**

If you consider content in White Rose Research Online to be in breach of UK law, please notify us by emailing [eprints@whiterose.ac.uk](mailto:eprints@whiterose.ac.uk) including the URL of the record and the reason for the withdrawal request.



[eprints@whiterose.ac.uk](mailto:eprints@whiterose.ac.uk)  
<https://eprints.whiterose.ac.uk/>

## Guest editorial: characterisation of crack tip fields

### Authors

L. Susmel, M. N. James, Y. Hong, F. Iacoviello

Joint Special Issues of the International Journal of Fatigue (Elsevier) and Fatigue & Fracture of Engineering Materials & Structures (Wiley) containing selected and fully peer-reviewed papers from the 3rd International Conference on Characterisation of Crack Tip Fields held in Urbino, Italy, over 20–22 April 2015.

The advent of full-field experimental techniques capable of measuring crack tip fields across a range of size scales has led to considerable activity in the area of characterisation of crack and notch tip fields. Influences of any plastic enclave on crack tip fields ahead of the crack are maximised during cyclic loading. In the case of a parameter like the stress intensity factor,  $K$ , which characterises the crack tip field via an elastic approximation, it is not surprising that any set of plasticity-induced circumstances which perturb the assumed crack tip field leads to predictive difficulties. It is therefore still an open question in the prediction of fatigue and fracture performance which parameter, or combination of parameters, e.g.  $G$ ,  $K$ ,  $T$ , best combines ease of use with predictive capability.

The third international conference in the Crack Tip Fields series was organised by the Italian Group of Fracture ([www.gruppofrattura.it](http://www.gruppofrattura.it)). It followed the successful format of the first two conferences, based around a largely invited group of delegates, and allowing sufficient time for useful discussion after each paper and again at the end of the conference. The following points emerged from the discussions as being important to better understanding:

Combinations of models and experimental techniques are required to make real progress, e.g. linking digital image correlation, computed tomography, electronic speckle pattern interference with improved FE and analytical models of crack tip fields.

Mixed mode solutions are preferable (but add complexity); for example, thin compact tension specimens under Mode I loading may buckle, inducing Mode III loads, and cracks themselves induce multiaxial stress states.

Multi-parameter solutions are required, e.g.  $G$ ,  $K$ ,  $T$ .

Location of crack tip is important and requires sensitivity analyses.

It would be useful to rationalise the various models involving critical distance, area and volume and develop models that bridge micro- to meso- to macro-scale.

Still no certainty about the relative importance of load transfer and magnitude across crack surfaces (so-called crack closure).

Discontinuities can be mathematically difficult to handle.

The papers selected for these joint Special Issues of the International Journal of Fatigue (Elsevier) and Fatigue & Fracture of Engineering Materials & Structures (Wiley) demonstrate a range of research that is already giving detailed consideration to a number of the aforementioned aspects.

The next conference in the Characterisation of Crack Tip Fields series is proposed to take place in April or early May 2017, on the French island of Corsica in the Mediterranean; please diarise this event, and full information will be circulated about this in good time.

The Guest Editors hope that this fully peer-reviewed overview of current thinking in the area of crack tip fields in relation to fatigue and fracture is of use to the research community.