



This is a repository copy of *Editorial : A decade of Green Radio and the path to “Net Zero” : a United Kingdom perspective.*

White Rose Research Online URL for this paper:

<https://eprints.whiterose.ac.uk/187408/>

Version: Accepted Version

---

**Article:**

Thompson, J.S., Fletcher, S., Friderikos, V. et al. (5 more authors) (2022) Editorial : A decade of Green Radio and the path to “Net Zero” : a United Kingdom perspective. IEEE Transactions on Green Communications and Networking, 6 (2). pp. 657-664.

<https://doi.org/10.1109/tgcn.2022.3172596>

---

© 2022 IEEE. Personal use of this material is permitted. Permission from IEEE must be obtained for all other users, including reprinting/ republishing this material for advertising or promotional purposes, creating new collective works for resale or redistribution to servers or lists, or reuse of any copyrighted components of this work in other works. Reproduced in accordance with the publisher's self-archiving policy.

**Reuse**

Items deposited in White Rose Research Online are protected by copyright, with all rights reserved unless indicated otherwise. They may be downloaded and/or printed for private study, or other acts as permitted by national copyright laws. The publisher or other rights holders may allow further reproduction and re-use of the full text version. This is indicated by the licence information on the White Rose Research Online record for the item.

**Takedown**

If you consider content in White Rose Research Online to be in breach of UK law, please notify us by emailing [eprints@whiterose.ac.uk](mailto:eprints@whiterose.ac.uk) including the URL of the record and the reason for the withdrawal request.



[eprints@whiterose.ac.uk](mailto:eprints@whiterose.ac.uk)  
<https://eprints.whiterose.ac.uk/>

## **Editorial: A Decade of Green Radio and the Path to "Net Zero": A United Kingdom Perspective**

*John Thompson (1), Simon Fletcher (2), Vasilis Friderikos (3), Yue Gao (4), Lajos Hanzo (5), Mohammad Reza Nakhai (3), Timothy O'Farrell (6) and Patricia Wells (7).*

*(1) Institute for Digital Communications, School of Engineering, University of Edinburgh, Edinburgh, EH9 3FB, UK; Email: john.thompson@ed.ac.uk*

*(2) Real Wireless Ltd, PO Box 2218, Pulborough, West Sussex, RH20 4XB, UK*

*(3) Department of Engineering, King's College London, Strand, London, WC2R 2LS, UK*

*(4) School of Computer Science, Fudan University, Shanghai 200438, China*

*(5) School of Electronics and Computer Science, University of Southampton, Southampton SO17 1BJ, UK*

*(6) Department of Electronic and Electrical Engineering, University of Sheffield, Sheffield, UK*

*(7) NEC Telecom Modus Ltd, Olympus House, Cleeve Road, Leatherhead, Surrey, KT22 7SA, UK*

**Abstract** - It has been a decade since several major research projects, such as the UK Green Radio, EU EARTH and GreenTouch projects, initiated large scale investigations into energy efficient wireless. Moving forward, the recent Climate Change Conference in Glasgow (COP26) has started to flesh out the details of meeting the ambitious goals of the 2015 Paris (COP22) agreement. This article from UK-based authors reflects on the achievements of energy efficient wireless research to date in mitigating carbon emissions. It explores the industrial challenges ahead with the deployment of fifth generation (5G) wireless technologies and discusses potential opportunities for reducing carbon emissions in the next decade. Major research challenges that still face the wireless community are also described including the development of sixth generation (6G) wireless technologies.

### **1. Introduction**

Around ten years ago, several major research projects have studied wireless energy efficiency (EE), including the UK Green Radio, EU EARTH and GreenTouch projects. These projects showed that a range of techniques need to be adopted in base stations to save energy, including the following concepts [1,2]:

- Use of more efficient radio frequency chains;
- Reductions in base station signalling, especially under low load conditions;
- Sleep mode techniques to switch off unused parts of base stations (BSs).

Extensive studies were also performed to investigate how a network of BSs could be adapted to reduce energy consumption, for example by adjusting the cell size [3] or using wireless relays/small-cells.

Following the success of the UK Green Radio project, which was completed in 2012 [1-3], many of its findings have influenced the development of technology and practices related to the EE of radio access networks. In particular, work on BS sleep modes and equipment shutdown is found in the 5G standards on network operation and management [4] whereas discussions on energy metrics is found in ETSI standards relating to measuring EE in deployed wireless networks [5]. 5G networks also offer more flexible settings on signalling traffic, to improve the EE of lightly loaded BSs.

The Paris COP22 conference in 2015 established the importance of restricting global temperature rises due to global warming to below 2 degrees Celsius. Around the world, governments and businesses are planning how to meet these targets in time to deliver net zero carbon emissions by 2050. Information Communication Technology (ICT) is estimated to contribute around 1.8-2.8% of global carbon emissions [6]. There are significant deviations between the data presented in [6] due to differing assumptions in modelling and about the definition of ICT technologies themselves. One issue that adds to the complexity is the relationship between efficiency and use, going back to Jevon's paradox from 1865.

The English economist William Jevons noted that the use of coal had soared in England after the development of James Watt's steam engine [7]. While Watt's engine had hugely increased the efficiency of burning coal, improved efficiency actually led to increased overall coal consumption as it became so widely used. The paradox thus notes the rebound effect that can occur with improvements in EE. While Jevon's paradox originally related to coal use, similar effects have been observed in many other contexts [6]. The practical impact of Jevon's paradox in modern energy systems is debated in [7,8]. However, it is clear that ICT carbon emissions must start to be reduced very significantly in order for the COP22 targets to be met in the next 20-30 years. As ICT systems mainly run on electricity, they stand to benefit from the huge growth in renewable energy sources, such as wind and solar.

In this article we will reflect on the importance of EE issues in wireless networks one decade on. Firstly we review current industrial perspectives on EE in networks. Secondly, we briefly discuss some UK views on EE, reviewing how energy consumption has evolved in the last ten years and exploring current initiatives to improve the situation in future. We will also report on the outcomes of a panel discussion involving the authors on future research directions that was held in March 2022.

## **2. Industrial Perspective**

Reducing the power consumption of network equipment has always been an engineering challenge for the telecommunications sector. As mobile operators' roll out continues to provide connectivity to an increasing proportion of the population, the importance of the energy impact of the sector has become an area of scrutiny. Over 10 years ago the UK Green Radio programme was initiated through a strategic partnership between the Mobile VCE and UK Government, securing a combination of public and private sector R&D funds to ensure the holistic system design issues were researched. That research spawned further UK activities in both the industrial and university sectors.

**How has the supply side evolved over the last 10 years:** For industry, network architecture platforms and the enabled product lines have moved at pace over the past 10 years. Whilst the public mobile network macro towers retain their prime status as the heavy lifters for providing connectivity, the proliferation of small-cell options and the business models that support them continue to evolve. There are more and more at-scale neutral host and system integrators in the supply chain. The emergence of private networks into the vertical industry sectors along with dedicated and shared spectrum creates a new dynamic in digital infrastructure. The convergence of fixed and wireless systems and cloud-based approaches to delivery have also matured.

**Pillars to the established industrial approach:** Three fundamentals of energy efficient telecoms technologies have emerged:

- *Transition to renewable energy:* The annual reports of telecom operators show this trend is well underway in Europe, e.g. see [9]. A recent report [10] suggests that the ICT carbon footprint would reduce by 80% if all electricity used was from renewable sources.
- *Improved network equipment efficiency:* Examples include high efficiency power amplifiers and powering down unused sub-systems. This can be more difficult to implement for mixed networks comprising both small-cell and macro-cell networks due to interoperability issues.
- *Low carbon data centre applications:* The main end to end services are moving away from voice towards a plethora of low-energy data-centre-driven applications as the main value creation mechanism.

Recent industry surveys at a Telecom TV Green Networks event point to limited consensus on the priorities going forward. Artificial Intelligence (AI) and analytics, power-efficient technologies, sharing of physical network resources, and self-generation of green energy within the sector are all currently considered to be important. As industry seems divided on the priority focus, there is a research opportunity to provide evidence for policy makers to determine strategy towards 2030.

**Looking forward for the next 10yrs:** Telecoms equipment hardware platforms oscillate between software and hardware oriented approaches. The trend of the last few years has been to virtualise systems, particularly with the recent appearance of Open Radio Access Network (Open-RAN) systems and interfaces [11]. This has increased the demand on software architecture approaches and general-purpose processors (GPP). The pendulum will inevitably swing back to hardware acceleration as pressure increases to improve both capacity and EE.

Collaborative ecosystems for product development constitute an enabling concept that is appearing on the horizon and will certainly impact the way in which mobile networks will evolve. In the telecoms domain, some research and innovation (R&I) as well as standards development organisations (SDOs) already have 6G technologies on their 5-10yr roadmap, e.g. [12]. A number of governments worldwide are placing significant importance on the development of diversified supply chains in maturing 5G and 6G – bringing Open-RAN, Open Networks and Open Standards to increased attention.

The shifts in business and technical platforms are likely to be significant. Fixed networks and solar-charged satellites have some inherent advantages in their energy consumption compared to wireless networks. However, the indoor-enterprise, satellite and fixed network sectors place requirements on their business-critical telecoms solutions that will affect the overall energy consumption. Standardised energy metrics, perhaps building on those reported in [13], are needed to unify the approach across a converged deployment architecture. The ability of industry to include whole life cycle analysis in their procurement processes for ICT solutions will increasingly shape buyers' decisions in the future.

### **3. UK Views on 6G research to approach Net Zero**

In the United Kingdom, many government and industry bodies are currently discussing the development of 6G technologies, with a major focus on EE. In 2021, the UK Spectrum Policy Forum organised several major research workshops, which led to the preparation of a White Paper on 6G research. This identifies net zero carbon operation a particular priority research area for the UK to pursue [14]. The UK5G Climate and Environment Working Group was also set up in 2021 to explore EE issues around 5G networks, in order to advise the UK government and promote further research on the topic [15]. Currently, the UK5G Climate

and Environment Working Group is examining EE in 5G deployments in terms of operational energy consumption and cradle-to-grave life cycle analysis.

In order to explore how energy consumption in wireless networks has evolved, Table 1 shows an indicative comparison of energy consumption figures that were used in the UK Green Radio project discussions and other publications circa 2010 for the UK. These are compared to recent figures for the 2021 period, mainly based on references [16,17]. The report [16] presents average energy figures from mobile networks in 28 countries in Europe, Africa and Asia. It should be understood that this is not a fair and direct comparison, as the two sets of data were generated in very different ways. However, the results give some general indication of how energy consumption figures have changed over time.

The figures in Table 1 show that the energy consumed by mobile BSs in a mobile operator's energy budget has increased from around 57% in 2010 to as much as 77% in 2021. This indicates that many mobile operators have significantly improved the overall efficiency of their operations, excluding BS sites. While BS designs have also improved significantly in efficiency, there are fundamental lower limits on the power required to transmit radio signals, as defined by Maxwell's equations. The average network energy consumption per wireless link is observed to have reduced by about 45% over ten years, though the 2021 data is calculated for a wide range of different countries. Similarly, the quoted figures for power consumed for one BS site is observed to reduce by a factor of around two in the last decade. As noted in Section 2 above, renewable energy sources are now being rapidly adopted by mobile operators in many countries leading to a significant increase compared to 2010. However, in many countries, diesel generation is still used for powering on average 11% of BSs in 2021, especially in remote regions where electrical grid connections are typically not available.

Table 2 also shows how a typical UK operator has evolved from 2010 to 2021. In the last ten years, fourth generation (4G) networks have been widely deployed and 5G BS roll out is presently underway. The amount of radio spectrum owned by operators has increased by about 6-8 times and data traffic figures from Ericsson in [18] suggest a 300-fold increase in network data being processed. It is quite remarkable that the energy consumed by a network on a per link basis has reduced, despite the huge growth in mobile data and the bandwidths used to support mobile connections.

**Table 1: Energy Comparisons 2010 (UK) vs 2021 (28 Countries)**

| <b>Metric</b>                              | <b>2010 (UK)</b> | <b>2021 Data (28 Countries)</b> |
|--------------------------------------------|------------------|---------------------------------|
| Base Station Energy Consumption % of total | 57% [2]          | 73-77% [16,17]                  |
| Network Power Consumed per user/link       | 3W <sup>1</sup>  | 1.69 W [16]                     |
| Power Consumption of One Base Station Site | 7.3 kW [19]      | 3.3 kW [16]                     |
| Renewable Energy Sources Used              | 6.5% [20]        | 46% [16]                        |
| Diesel Generation                          | N/A              | 11% [16]                        |

<sup>1</sup> Informal estimate discussed in the Green Radio project, based on a typical UK mobile operator energy consumption and number of subscribers.

**Table 2: Typical UK Mobile Operator Characteristics 2010 vs 2021**

| <b>Metric</b>      | <b>2010 (UK)</b>                           | <b>2021 (UK)</b>                      |
|--------------------|--------------------------------------------|---------------------------------------|
| Network Types      | 2G + 3G networks                           | 2G + 3G + 4G + initial 5G deployments |
| Spectrum Ownership | Typical 40 MHz [21]                        | Typical 250-350 MHz [22]              |
| Data Volume        | 1x                                         | 300x [18]                             |
| Service Type       | voice/short message service with some data | mainly data services                  |

Reference [23] has evaluated the carbon emissions per hour for different wired and wireless technologies, specifically for video streaming applications. The results show that 5G networks are around 2.6 times more energy efficient than older 4G networks and around 18 times more efficient than third generation (3G) wireless systems. In terms of the bits per joule metric, 5G is also recognised as an energy efficient RAN technology in the study in [24] which illustrates the EE of 5G when delivering video services. Nonetheless, there are concerns about the absolute energy consumption in practical 5G deployments, which is expected to exceed levels in previous generations of wireless networks [25,26]. For example, early 5G BS evaluations reported by China Mobile in [27] have shown that a 5G BS using massive multiple input multiple output (MIMO) technology could deliver sixteen times higher data throughput, but requires almost four times higher peak power consumption. That is, while 5G's EE as measured in bits per joule is higher so is its underlying energy consumption, which could hinder reaching net-zero goals [15].

There are multiple reasons for this expected increase in energy consumption in 5G deployments [28]. The primary causes are attributed to an increase in the number of deployed radio units, the coexistence of “always on” RATs at BS sites and the use of more frequency bands as seen in Table 2. In the near future, mm-wave bands above 24 GHz may also be used for data services. As shown in Table 1, BSs consume the largest amount of energy in a RAN, for example, in large networks up to 77% of energy use is attributed to BSs in 2021. In 5G more BSs will be deployed through small-cells due to the short propagation distances of mm-wave carriers. Even though each small-cell consumes less energy, the densification of the RAN with more radios and backhaul connections increases the energy consumption per unit area. As noted above, a similar situation arises in massive MIMO deployments where the plurality of radio units at the BS site increases the absolute energy consumption. Often, 5G BSs will share cell sites with 2G, 3G and 4G equipment, resulting in multiple RATs concurrently consuming energy at each BS site. In the long term, solutions such as those discussed in [27] will enable more energy efficient 5G network operation. Until legacy 2G and 3G networks are decommissioned [17], which is expected in the UK by 2033, the independent control signalling in each technology may affect the ability to shutdown lightly loaded services on a temporary basis to save energy.

With the ongoing deployment of 5G and standardisation of 5G-Advanced, the UK research community is pursuing 6G research for 2030 wireless networks [12,14,29]. A key facet of this research is sustainable 6G, aimed at attaining United Nations net-zero goals [30] as well as reducing energy consumption in other sectors such as transport, manufacturing and energy supply [31]. As the vision for 6G encompasses enhanced human communication and pervasive machine communication for robots, data consumption is expected to far exceed that in 5G. Pathways to meet such unprecedented data demand include sub-THz frequency bands for sub-THz radios, extremely large antenna arrays for massive MIMO in conjunction with reflective intelligent surfaces (RIS), software-ised RAN functions for realising distributed cloud and communications systems and trusted native artificial intelligence (AI) for managing

network operation are initial examples of 6G technologies being researched in the UK [32]. However, these developments carry significant EE challenges if 6G networks are to meet net-zero goals. Higher frequency bands create even shorter propagation ranges as well as greater electronics inefficiencies making even denser deployments of infrastructure inevitable compared to 5G. Addressing these complexities through the careful co-design of radios, networks and intelligent management systems will form the basis of the UK's research strategy for developing 6G technologies.

#### **4. Panel Discussion: Major Directions for Future Wireless Research**

On Thursday 3<sup>rd</sup> March 2022, the authors held a panel meeting to talk about their views on what future research the wireless community should be engaged in. This led to a lively discussion that identified the following trends in EE research:

**a) Energy Consumption for New Applications:** As 6G technology is developed, new applications are coming into view. One example is metaverse type of applications which will offer users fully immersive experiences in ultra-high realistic virtual worlds [33]. These applications are highly multi-modal and real-time interactions might also include ultra-reliable tactile sensory perception of virtual objects in the metaverse. To this end, continuously updating a 360-degree 24k video based panoramic synthetic world with a large number of participants (avatars) will require a significant amount of edge cloud and communication resources for both uplink and downlink communication, entailing substantially higher energy consumption levels. These unprecedented requirements for creating ultra-realistic cyber environments at scale beg for a closer synergy between the metaverse creator's ecosystem and the underlying wireless network to optimize energy consumption.

The inherent trade-offs between latency, data-rate support, energy consumption and overall service quality (i.e., quality of end user interactions and perception in 3D virtual spaces) need to be considered together with the optimal service composition in the continuum between the users and edge/core clouds. Furthermore, since the above constitute competing objectives, metaverse-aware multi-objective optimization will have a prominent role to play in providing sustainable network operating points. This will require consideration of flexible operation over the so-called Pareto frontier of different parameter settings, as described further in item c) below.

**b) Energy Impacts of Open-RAN Technology:** It will be important to define a benchmark for energy and spectral efficiency performance for 5G networks. This will allow the future enhancements to be compared with a suitable baseline. This is particularly important given the current interest in evolving the design of the RAN towards Open-RAN networks as mentioned above in Section 2. This approach is very different from current BS products which are typically made by a single manufacturer and are thus vertically integrated. This enables cross-layer optimization of networks and permits high EE operation if desired. However, currently there is a trend in Open-RAN networks where individual network components are procured from different companies, enabling diversification of the network.

New technical approaches are urgently needed to measure the EE of Open-RAN networks. These systems will instead be horizontally integrated and there is a concern that without careful design they may be less energy efficient than current commercial BSs. In March 2022, the Open-RAN alliance technical priorities 2 were released, including initial specifications on EE requirements of future Open-RAN networks [34]. By comparison with existing BSs, optimizing the EE of Open-RAN will require a more granular approach to assess and optimize the energy consumed by the individual components of each BS. The radio unit (RU) of the Open-RAN system is likely to consume significant energy along with

the centralised units (CU) and distributed units (DU) that provide data and signal processing functions. The RAN intelligent controller (RIC) will thus have an important role in managing overall energy consumption. There is clearly an open research opportunity to explore how new technologies, such as artificial intelligence and software defined networks, can permit EE to be measured and optimized in future.

**c) Flexibly Using the Full Pareto Boundary:** Taking a step back in history - following Shannon's legendary treatise [35] on the attainable system capacity - decades of research effort has been invested into designing near-capacity systems before the above-mentioned bandwidth-vs. power-efficiency trade-off crystalized during the UK Green Radio era of predominantly power-optimized systems. Typically as the spectral efficiency increases, there will be a substantial degradation in terms of the corresponding power efficiency. Based on this understanding, during the run-up to 5G standardization it became broadly recognized that a single operational mode is unable to cater for the rather heterogeneous and almost conflicting requirements of the enhanced mobile broadband (eMBB), massive machine-to-machine (mM2M) and ultra-reliable low-latency communication (URLLC) specifications. This realization heralded the era of multi-component system optimization [36]. Briefly, multi-component optimization goes way beyond the typical constrained optimization problem of wireless systems, where for example the system's sum-rate is maximized under the constraint of a fixed power budget.

As an example, consider Shannon's continuous input continuous output memoryless channel (CCMC) capacity theorem [35]. He implicitly assumed having the idealized simplifying assumption that the channel inflicts random uncorrelated errors and that a potentially infinite-length as well as infinite-complexity channel code may be used. However, if we use a realistic finite-length, finite-complexity block code, finite-block-length (FBL) information theory [37] quantifies the attainable capacity. Again though, even FBL information theory fails to consider the complexity of a block-code capable of achieving it. The Pareto front of all optimal configurations will contain the specific capacity (throughput), delay and complexity associated with each individual legitimate channel coded block length. It becomes plausible that it is not possible to operate closer to Shannon's CCMC capacity for example without increasing either the codeword length and hence the delay and/or the decoding complexity or in fact potentially both.

Consider also the two prior research topics in items a) and b) above related to metaverse applications and Open-RAN networks. Again, in these cases, a range of parameters need to be optimized. As the state-of-the-art evolves, the single-component constrained optimization approach is expected to be gradually extended to twin-component, three-component and multi-component optimization, which requires the joint development of the correct objective functions (OF) to be optimized and the optimization algorithms to find the best solutions. Every time the OF incorporates a new parameter, the search-space of optimal solutions is expanded, which imposes potential challenges in terms of developing good optimization tools for solving these radical research problems. We note in closing that a range of other practical Pareto-optimization problems were listed in [38].

**d) Resolving Conflicting Requirements Through Machine Learning:** In all of the above research topics, we have identified the notion of managing complex, interdependent systems with many operating choices and potentially conflicting requirements. In this part, we discuss how novel machine learning approaches can be used to handle such situations to establish good practical operating choices.

As a first example, consider densely deployed BSs in future networks which could provide massive short-range connectivity at lower power consumption cost and higher spectral



efficiency, if the interference barrier is efficiently alleviated. Powerful optimization techniques have played pivotal roles in designing efficient power allocation algorithms in cellular networks. However, their excessive need for side-information and coordination through backhaul links could lead to a failure in tracking channel and traffic variations in a densely deployed network. These overhead requirements, however, can be significantly minimized by exploiting recent advances in optimization and online machine learning, namely online foresighted optimization [39]. An outcome of this approach can lead to online learning-based distributed optimization of power allocation. Each BS adjusts its own transmit power based on locally available statistical prediction of the transmit power levels of the other dominantly interfering BSs as well as the past historical information. In such a setup, each BS can be viewed as an intelligent agent making instantaneous autonomous decisions on its own transmit power strategy. This allows the system overall to find effective operating points in a competitive multi-agent environment of distributed BSs. The online foresighted optimization also accounts for the coupling of the optimization variables across time. This results in near-optimum instantaneous decisions at all times for the network operation.

Other applications of this approach that have already been studied include management of hybrid use of renewable energy sources and the conventional power grid to power wireless networks. Control policies can be developed for energy storage units, which are capable of storing energy in advance during low-cost off-peak intervals and supplying energy when intermittent renewable sources, such as wind or solar are unable to meet the energy demands of the network [40]. A third example arises in the emerging multi-access edge computing (MEC) that can potentially extend cloud computing power to the edge of the network. It is a very promising technology to support user applications with low latency and alleviate energy shortage issues at smart devices. Online foresighted optimization can cope with the time-varying cost and constraint functions of such massively distributed scenarios by devising online control mechanisms for task offloading management [41]. Thus, this approach has the potential to manage complex decision making that has been discussed in research topics a)-c) above.

## **5. Summary**

Ten years on, there is still a plethora of research topics leading to improved energy efficiency in the telecoms sector. Much of the research from that time is still pertinent and can be used as a springboard for research today. Power efficient radio is important from an industrial perspective as low power consumption is imperative to being competitive in the market. The issue is compounded by the diversification of the network through Open-RAN technologies and new metaverse applications. As networks become more complex the search space for optimal solutions expands. Multi-component system optimization and machine learning can prove valuable in optimizing certain aspects of the space but achieving full Pareto efficiency remains a massive challenge, providing many exciting research opportunities for the decade to come.

## **Acknowledgement**

The authors would like to thank Jenny Johnson from the Mobile VCE for her administrative assistance in organising and minuting meetings that were held to prepare this article.

## **References**

- [1] J. He, P. Loskot, T. O'Farrell, V. Friderikos, S. Armour and J. Thompson, "Energy efficient architectures and techniques for Green Radio access networks," 2010 5th International ICST Conference on Communications and Networking in China, 2010, pp. 1-6.
- [2] C. Han et al., "Green radio: radio techniques to enable energy-efficient wireless networks," in IEEE Communications Magazine, vol. 49, no. 6, pp. 46-54, June 2011.
- [3] B. Badic, T. O'Farrell, P. Loskot and J. He, "Energy Efficient Radio Access Architectures for Green Radio: Large versus Small Cell Size Deployment," In Proc. IEEE 70th Vehicular Technology Conference (Fall), Anchorage (USA), pp 1-5, 2009.
- [4] W. Guo and T. O'Farrell, "Green cellular network: Deployment solutions, sensitivity and tradeoffs," In Proc. Wireless Advanced, pp. 42-47, 2011.
- [5] European Telecommunications Standard Institute (ETSI) Standard, "Environmental Engineering (EE): Assessment of mobile network energy efficiency", ES 203 228 v1.1.1, April 2015.
- [6] C. Freitag, M. Berners-Lee, K. Widdicks, B. Knowles, G. Blair, A. Friday, "The Climate Impact of ICT: A review of estimates, trends and regulations", December 2020, Arxiv Document 2102.02622.
- [7] W.A. Jevons, "The coal question: Can Britain survive?" In: Flux, A.W. (Ed.), "The Coal Question: An Inquiry Concerning the Progress of the Nation, and the Probable Exhaustion of our Coal-Mines", Augustus M. Kelley, New York, 1865.
- [8] K. Gillingham, M. Kotchen, D. Rapson, et al. "The rebound effect is overplayed", Nature Vol 493, pp 475–476, 2013.
- [9] See URL: <https://www.vodafone.com/sustainable-business/our-purpose-pillars/planet/net-zero-by-2040>
- [10] See URL: <https://www.ericsson.com/en/reports-and-papers/industrylab/reports/a-quick-guide-to-your-digital-carbon-footprint>
- [11] Open-RAN Alliance, See URL: <https://www.o-ran.org>
- [12] NextG Alliance, "Report: Roadmap to 6G", See URL: <https://nextgalliance.org/>
- [13] H. Hamdoun, P. Loskot, T. O'Farrell, et al. Survey and applications of standardized energy metrics to mobile networks. Ann. Telecommun. Vol 67, pp 113–123, 2012.
- [14] See URL: <https://www.techuk.org/resource/uk-universities-6g-wireless-research-capacity-is-in-excellent-shape-says-new-uk-spf-report1.html>
- [15] See URL: <https://uk5g.org/5g-updates/read-articles/uk5g-climate-environment-working-group-gets-started/>
- [16] GSMA Intelligence Report, "Benchmarking the Energy Efficiency of Mobile", Version 1, June 2021, see URL: <https://data.gsmaintelligence.com/research/research/research-2021/going-green-benchmarking-the-energy-efficiency-of-mobile>
- [17] NGMN Report "Network Energy Efficiency", Version 1.1, 7/12/2021, Available at <https://www.ngmn.org/wp-content/uploads/211009-GFN-Network-Energy-Efficiency-1.0.pdf>

- [18] See URL: <https://advanced-television.com/2021/11/30/report-mobile-data-traffic-up-300-fold-over-10-years/>
- [19] J. Lorincz, T. Garma and G. Petrovic, "Measurements and modelling of base station power consumption under real traffic loads", Sensors (Basel). 2012; Vol 12, No 4, pp 4181-4310, Table 5.
- [20] See URL: <https://tinyurl.com/2p9bmtw6>
- [21] See URL: [https://www.ofcom.org.uk/data/assets/pdf\\_file/0018/40941/annex6.pdf](https://www.ofcom.org.uk/data/assets/pdf_file/0018/40941/annex6.pdf)
- [22] See URL: <https://5g.co.uk/guides/5g-uk-auction/>
- [23] See URL: <https://www.umweltbundesamt.de/en/press/pressinformation/video-streaming-data-transmission-technology>
- [24] Carbon Trust, "The carbon impact of video streaming," White Paper, June 2021. Available at <https://www.carbontrust.com/resources/carbon-impact-of-video-streaming>
- [25] GSMA Intelligence Report, "Addressing sustainability for 5G: holistic, realistic, optimistic," October 2021. See URL: <https://data.gsmainelligence.com/research/research/research-2021/addressing-sustainability-for-5g-holistic-realistic-optimistic>
- [26] L. Williams, B. K. Sovacool, T. J. Foxon, "The energy use implications of 5G: Reviewing whole network operational energy, embodied energy, and indirect effects," Renewable and Sustainable Energy Reviews, Volume 157, 2022.
- [27] C.L. I, S. Han, and S. Bian, "Energy-efficient 5G for a greener future". Nature Electron Vol 3, pp 182–184, 2020.
- [28] A. Schoentgen, T. Miller, A. Kaur, R. Rudd, V. Jervis and Y.S. Chan, "The role of spectrum policy in tackling the climate change issue," Report, published by Plum Consulting, October 2021, Available at <https://www.techuk.org/resource/report-how-spectrum-policy-can-help-to-tackle-climate-change.html>
- [29] 5G Infrastructure Association (5GIA), "European vision for the 6G network ecosystem," White Paper, June 2021, Available at <https://5g-ppp.eu/wp-content/uploads/2021/06/WhitePaper-6G-Europe.pdf>
- [30] K. Ojutkangas, E. Rossi and M. Matinmikko-Blue, "A deep dive into the birth process of linking 6G and the UN SDGs," Telecommunications Policy, Volume 46, Issue 1, 2022.
- [31] Mobile UK, "Connectivity and climate change: how 5G will lay the path to net zero," White Paper, October 2021, Available at <https://www.mobileuk.org/connectivity-and-climate-change>
- [32] NGMN Report, "6G use cases and analysis," Version 1.0, February 2022, See URL: <https://www.ngmn.org/wp-content/uploads/NGMN-6G-Use-Cases-and-Analysis.pdf>
- [33] M.Xu et. al., "A Full Dive into Realizing the Edge-enabled Metaverse: Visions, Enabling Technologies, and Challenges", March 2022, URL: <https://arxiv.org/pdf/2203.05471.pdf>
- [34] See URLs: <https://www.telefonica.com/en/communication-room/open-ran-technical-priorities-release-2/> and <https://www.o-ran.org/specifications>
- [35] C. E. Shannon, "A mathematical theory of communication", Bell System Technical Journal], Vol. 27, pp. 379--423 and 623--656, June and October 1948.

- [36] Z. Fei, B. Li, S. Yang, C. Xing, H. Chen and L. Hanzo, "A Survey of Multi-Objective Optimization in Wireless Sensor Networks: Metrics, Algorithms, and Open Problems", IEEE COMST, Vol. 19, Issue 1, 2017.
- [37] Y. Polyanskiy; H. V. Poor and S. Verdú, "Channel Coding Rate in the Finite Blocklength Regime", IEEE Transactions on Information Theory, Vol. 56, Issue: 5, 2010.
- [38] J. Wang, C. Jiang, H. Zhang, Y. Ren, K.-C. Chen and L. Hanzo, "Thirty Years of Machine Learning: The Road to Pareto-Optimal Wireless Networks", IEEE COMST, Vol. 22, Issue 3, 2020.
- [39] X. Zhang, M. R. Nakhai, G. Zheng, S. Lambotharan and B. Ottersten, "Calibrated Learning for Online Distributed Power Allocation in Small-Cell Networks", IEEE Transactions on Communications, Vol. 67, No. 11. pp. 8124-8136, 2019.
- [40] X. Zhang, M. R. Nakhai, G. Zheng, S. Lambotharan and J. A. Chambers, "Distributed Foresighted Energy Management in Smart-Grid-Powered Cellular Networks", IEEE Transactions on Vehicular Technology, Vol. 68, No. 4. pp. 4064-4068, 2019.
- [41] Z. Sun and M. R. Nakhai, "An Online Learning Algorithm for Distributed Task Offloading in Multi-Access Edge Computing", IEEE Transactions on Signal Processing, Vol. 68. pp. 3090-3102, 2020.

### **Biographies**

**John S. Thompson** (FIEEE, 2016) received the Ph.D. degree in electrical engineering from University of Edinburgh, Edinburgh, U.K., in 1995. He currently holds a personal chair in Signal Processing and Communications at the School of Engineering, University of Edinburgh. He specializes in antenna array processing, energy-efficient wireless communications and the application of machine learning to wireless communications problems. To date, he has published in excess of 350 papers on these topics. His work has been regularly cited by the wireless community and from 2015 to 2018, he was recognized by Thomson Reuters as a Highly Cited Researcher. He is currently an area editor handling wireless communications topics for the IEEE Transactions on Green Communications and Networking journal. In January 2016, he was elevated to Fellow of the IEEE for Contributions to Antenna Arrays and Multihop Communications.



**Simon Fletcher** is Chief Technology Officer at Real Wireless, a world leading wireless advisory firm. He has spent the past 20 years working in the design and development of technical telecoms infrastructure. Beginning his career in technology demonstrators in the defence sector, he moved to NEC in 1999 to play a key role in the development of 3G products. In 2006 he established a core architecture team that helped develop the first-generation of technology for 4G systems culminating in a Steering Board position in the LTE SAE Trials Initiative (LSTI), a global forum with a mission to assure the early adoption of LTE. His lengthy participation in Common Public Radio Interface (CPRI) defining early C-RAN concepts brings great foresight on an important architectural element of emerging 5G architectures and Open RAN. He was the Industrial Chair of a leading Industry and UK Government partnership research project on Radio Networks Energy Efficiency – the Green Radio programme. He is currently a director of mVCE, member the UK5G Advisory Board – leading International discussions and the Chief Strategy Officer for the Small Cell Forum. He specialises in the application of strategic research through open innovation to accelerate product and service delivery, with a focus on future cities, the application of 5G and IoT in industry verticals, and securing sustainability innovation strategies with an event horizon towards 2030 and beyond.



**Vasilis Friderikos** is currently a Reader at the Department of Engineering at King's College London, UK. He has authored more than 200 research papers in flagship IEEE, Elsevier, Springer journals, international conferences, book chapters, including patents. His research interests lie broadly within the closely overlapped areas of wireless networking, mobile computing, and architectural aspects of the future Internet. The emphasis of his research is the design and analysis of data-driven and model-based algorithms for network management and orchestration to enable sustainable mobile wireless network infrastructures.



**Yue Gao** (SMIEEE) received the Ph.D. degree from the Queen Mary University of London (QMUL), U.K., in 2007. He is currently a Professor and the Chair in wireless communications with the School of Computer Science and Electronic Engineering, Institute for Communication Systems, University of Surrey, U.K. He also leads the Antennas and Signal Processing Laboratory developing fundamental research into practice in the interdisciplinary area of smart antennas, signal processing, spectrum sharing, millimeter-wave, and the Internet of Things technologies in mobile and satellite systems. He has published over 200 peer-reviewed journal articles and conference papers, one book, and five book chapters. He is an Engineering and Physical Sciences Research Council Fellow for the period 2018–2023. He is a member of the Board of Governors and the Vice-Chair of the IEEE ComSoc Wireless Communication Technical Committee. He was a co-recipient of the EU Horizon Prize Award on Collaborative Spectrum Sharing in 2016. He has been an editor of several IEEE TRANSACTIONS and journals and the symposia chair, the track chair, and other roles in the organizing committee of several IEEE ComSoC and VTS conferences. He is a Distinguished Lecturer of the IEEE Vehicular Technology Society.



**Lajos Hanzo** (FIEEE, 2004) received his Master degree and Doctorate in 1976 and 1983, respectively from the Technical University (TU) of Budapest. He was also awarded the Doctor of Sciences (DSc) degree by the University of Southampton (2004) and Honorary Doctorates by the TU of Budapest (2009) and by the University of Edinburgh (2015). He is a Foreign Member of the Hungarian Academy of Sciences and a former Editor-in-Chief of the IEEE Press. He has served several terms as Governor of both IEEE ComSoc and of VTS. He has published 2000+ contributions at IEEE Xplore, 19 Wiley-IEEE Press books and has helped the fast-track career of 123 PhD students. Over 40 of them are Professors at various stages of their careers in academia and many of them are leading scientists in the wireless industry. He is also a Fellow of the Royal Academy of Engineering (FREng), of the IET and of EURASIP.



**Mohammad Reza Nakhai** (SMIEEE) received the Ph.D. degree in electronic engineering from King's College, University of London, U.K., in 2000. In 2001, he joined King's College London, where he is currently with the Department of Engineering as a member of academic staff. His current research interests include machine learning and artificial intelligence for wireless communications applications, wireless network optimization for energy efficiency and signal processing for communications. He served as an editor for IEEE Transactions on Wireless Communications during 2015 – 2021.



**Timothy O'Farrell** (SMIEEE) received the Ph.D. degree in electrical and electronic engineering from the University of Manchester, Manchester, U.K., in 1989. He currently holds a Chair in Wireless Communications at the Department of Electronic and Electrical Engineering, University of Sheffield. He specializes in the design of energy efficient wireless networks, direct digitisation in multiband software defined radios, and wave form design for wireless communication systems. To date, he has published over 330 papers and led 24 research projects on these topics. Professor O'Farrell was the Academic Coordinator of the mVCE Green Radio project (2009-12); the General Chair of the 5th International Workshop on Next Generation Green Wireless Networks (Next-GWiN 2018); and director of the UK Research Strategy Community Organisation in Communications, Mobile Computing and Networking (CommNet2, 2015-19). He is a director of the mVCE ([mobilevce.com](http://mobilevce.com)); a member of the UK5G Climate and Environment Working Group ([uk5g.org](http://uk5g.org)) and a member of the DCMS College of Experts ([gov.uk/dcms](http://gov.uk/dcms)).



**Patricia D. Wells** (FIET, CEng) received her Ph.D. degree in electrical engineering from Royal Military College of Science (now Cranfield University), Swindon, U.K., in 1996 on the subject of “Angle of Arrival Estimation using Artificial Neural Networks”. On graduating she joined ERA Technology in Surrey, working on various projects relating to direction finding/adaptive antennas including European research projects such as TSUNAMI II. Since 1998 she has worked for NEC Telecom MODUS Ltd leading the development of an inhouse simulation platform used for 3G/4G/5G algorithm performance verification (beamforming, MIMO etc), as well as bit true verification for product development. For over 10 years she was involved in the UK Mobile VCE programmes as an industrial sponsor and mentor, including the UK Green Radio Programme discussed in this paper.

