

This is a repository copy of *Autonomous Fire-Fighting UAV*.

White Rose Research Online URL for this paper: https://eprints.whiterose.ac.uk/193932/

Conference or Workshop Item:

Araujo, Hugo, Dubey, Shival, Kaddouh, Bilal Y. et al. (3 more authors) Autonomous Fire-Fighting UAV. In: YorRobots and RoboStar Industry Exhibition, 11-12 Oct 2022, University of York. (Unpublished)

Reuse

Items deposited in White Rose Research Online are protected by copyright, with all rights reserved unless indicated otherwise. They may be downloaded and/or printed for private study, or other acts as permitted by national copyright laws. The publisher or other rights holders may allow further reproduction and re-use of the full text version. This is indicated by the licence information on the White Rose Research Online record for the item.

Takedown

If you consider content in White Rose Research Online to be in breach of UK law, please notify us by emailing eprints@whiterose.ac.uk including the URL of the record and the reason for the withdrawal request.







Autonomous Fire-Fighting UAV

Description

The primary mission of the autonomous UAV is to search and identify a fire on the wall of a building, fly close to the fire and spray suppressant liquid onto the fire.


System Architecture

Challenges

- Accurate detection of fire sources using vision-based perception
- Navigation and alignment against centre of fire
- Fire extinguishing from aerial platform

Software Modelling


Two RoboChart controllers reflect partition between main computer and Arduino that controls the pump and nozzle gimbal



High level systems diagram with main components and connections.


RealSense D435i depth camera

MLX90640 thermal camera



Physical Modelling

- Modular RoboSim physical model
- Parts reflect decomposition between M600 platform, with GPS, IMU and battery capacity sensors (shown), and custom Payload with cameras, and nozzle gimbal and water pump actuators
- Automatic generation of SDF for simulation with Gazebo



RoboSim physical model of the UAV

4L water bag Nozzle attached to Onboard computer a two-axis gimbal 10bar water pump Arduino Nano for pump and gimbal control 3S LiPo battery 1m Carbon fibre arm

Simulation


- ROS-based simulation with Gazebo
- Aim to use code generated from RoboSim software model obtained via transformation from RoboChart, ensuring sound behaviour

Testing & Verification

- Search-based approach to explore and generate test cases from a digital model
- Conformance testing of the UAV's behaviour against the expected one
- Verification of properties pertaining to the software, platform, and scenario



after importing generated SDF



RoboSim physical model of the DJI M600











