



UNIVERSITY OF LEEDS

This is a repository copy of *A low-cost way to reduce greenhouse effects*.

White Rose Research Online URL for this paper:

<https://eprints.whiterose.ac.uk/83246/>

Version: Published Version

Conference or Workshop Item:

Salituro, A, Westwood, AVK, Ross, A et al. (1 more author) A low-cost way to reduce greenhouse effects. In: International Bioenergy Conference 2014, 11-13 Mar 2014, Manchester, UK.

Reuse

Items deposited in White Rose Research Online are protected by copyright, with all rights reserved unless indicated otherwise. They may be downloaded and/or printed for private study, or other acts as permitted by national copyright laws. The publisher or other rights holders may allow further reproduction and re-use of the full text version. This is indicated by the licence information on the White Rose Research Online record for the item.

Takedown

If you consider content in White Rose Research Online to be in breach of UK law, please notify us by emailing eprints@whiterose.ac.uk including the URL of the record and the reason for the withdrawal request.



eprints@whiterose.ac.uk
<https://eprints.whiterose.ac.uk/>

A low-cost way to reduce greenhouse effects




UNIVERSITY OF LEEDS

A. Salituro¹ (pmasal@leeds.ac.uk), A. Westwood¹, A. Ross² and R. Brydson¹


¹Institute for Materials Research and ²Energy Research Institute; School of Process, Environmental and Materials Engineering, University of Leeds, Leeds, LS2 9JT, UK

Abstract Oak wood precursor was used for preparing low-cost CO₂ sorbents. Adsorption is proposed as a cheaper alternative to chemical absorption, which is uneconomical, thus reducing the cost associated with the capture step. The raw material has been carbonised either by pyrolysis or by a hydrothermal carbonisation (HTC). Resulting biochars were then activated using CO₂. Initial chars and their activated counterparts were characterised by SEM imaging and N₂ sorption measurements at 77 K. A significant rise in the BET surface area, total pore volume and micropore volume (textural parameters) occurred for all of the pristine chars after the activation process. Fast CO₂ sorption kinetics (saturation reached in 3 mins.) and CO₂ uptakes of up to ca. 6 wt. % have been measured by thermogravimetric analysis (TGA) at 35 °C and 1 atm. The activated carbons (ACs) thus synthesised showed competitive performances compared to a commercial AC standard. Although the sorbents' performances decreased at higher temperatures, they were easily regenerated after the capture stage.

Introduction



Experimental



Raw biomass was subjected either to a dry pyrolysis, in a horizontal tube furnace at 650 or 800 °C under N₂, or to hydrothermal carbonisation (HTC) carried out in deionised water at 250 °C in stainless steel autoclaves. Carbonisation products (named OW650, OW800 and OW250, respectively) were then heat-treated under CO₂. N₂ adsorption isotherms at 77 K for both pristine chars and oak wood-based ACs (referred to as OW250A, OW650A and OW800A) were measured using a Quantachrome Autosorb 1C gas sorption analyser. The materials' surface morphology has been examined by using a LEO 1530 (Field Emission Gun) High Resolution SEM. CO₂ uptakes for the ACs produced, and a commercial carbon (denoted as GAC) included for comparison purposes, were measured by using TGA both at 35 °C (isothermal test) and with temperature increasing from 35 to 100 °C (temperature-programmed test). Finally, the atmosphere was switched to N₂ and the temperature was increased to 120 °C to regenerate the samples.

Results and discussion

From Figs. 1a-1b it is possible to see the effect of the activation on the pore structure of the biochars. The ACs' isotherms tend to be closer to type I and their pore size distributions are narrower with peaks centred over ca. 0.5 nm. As observed from Fig. 2, moderately higher surface areas and micropore volumes were found for ACs derived from pyrolysis products (OW650 and OW800).




Figure 1. (a) N₂ adsorption isotherms and (b) DFT pore size distributions for biochars and ACs




Figure 2. Enhancement of textural parameters after CO₂ activation of all the biochars (OW800, OW650, OW250).

On the other hand, the most dramatic development of texture occurred for the activated carbon derived from the hydrothermally carbonised sample (OW250), whose surface area increased nearly 100 fold compared to the starting biochars' figure.

Textural characterisation results are corroborated by SEM images (see Fig. 3).




Figure 3. SEM micrographs at 5000x for biochars & ACs.

Indeed, these clearly show development of a structure that is more porous due to the activation procedure. (Microporosity is too small to see of course)

Moreover, as seen in Fig. 3, the regular distribution of mesopores identified for OW800A confirms its more porous structure compared to OW650 and OW250 which have larger pores that are also occupied by inorganic particles.




Figure 4. (a) Isothermal CO₂ uptakes at 35 °C expressed as percentage of weight increase of the fresh sorbent (*W*) and (b) normalised by surface area (*W_s*)

From the CO₂ uptake measurements carried out under isothermal conditions (35 °C) over 30 mins. as reported in Fig. 4a, it is observed that all the sorbents tested have fast sorption kinetics towards CO₂ uptake. Indeed, saturation is always reached within 3 mins. The maximum uptake is ca. wt. 6% which is comparable or even higher than values reported in some studies and achieved under similar conditions [1-2] but it is still a long way from the best performances (ca. 21%) reported in the literature [3].




Figure 5. Effect of temperature on CO₂ uptakes

Fig. 5 shows that, for all of the samples tested, sorption capacities decrease with increasing temperature as physisorption is an exothermic process. Nevertheless, This reduction occurs only gradually over the analysis temperature range, thus indicating a relatively strong adsorption potential binding CO₂ to the pore structure of the materials even at more severe temperatures. Finally, as shown by Fig.6, all the sorbents were easily regenerated in less than 2 mins. under N₂ at 120 °C.

Nevertheless, as evidenced by Fig. 4b, where uptakes are normalised to the samples' surface area, it is interesting to note that, despite the far larger surface area possessed by the commercial activated carbon (GAC's figure is twice that of OW800A), the wood-based ACs adsorbed much more CO₂ per unit of surface area, which might suggest that the latter possess greater affinity towards CO₂ due to, e.g., basic functional groups.




Figure 6. Sorbent regeneration at 120 °C under N₂

Conclusions

Carbonisation products derived from a low-cost biomass (oak wood) were successfully activated. Significant improvements to their porous texture were obtained – in particular for the hydrochar whose surface area was increased by around 100 fold. This demonstrates that the innovative HTC process, which operates at milder temperature conditions compared to those of traditional pyrolysis, can lead to hydrochar-derived ACs with surface areas comparable to those attained for sorbents derived from pyrolysed biochars. Overall, promising CO₂ sorbents have been produced starting from a low-cost feedstock, which showed similar uptakes to those achieved by commercial ACs (around 6 wt. %) and fast sorption rates. In addition, all of the materials were completely regenerated at 120 °C in ca. 2 mins. Future work will focus on applying an appropriate chemical modification of these carbons in an attempt to maximise their performances in terms of CO₂ uptakes under post-combustion conditions since they show promise as a viable alternative to costly chemical absorption of CO₂.

[1] Arenillas et al. (2005). Surface modification of low cost carbons for their application in the environmental protection. Applied Surface Science, 252(3), 619–624
 [2] Plaza et al. (2007). CO₂ capture by adsorption with nitrogen enriched carbons. Fuel, 86(14), 2204–2212
 [3] Sevilla et al. (2012). High-performance CO₂ sorbents from algae. RSC Advances, 2(33), 12792